



European Specifications (ETIM)	
ETIM	EC001059 Crimp splices for copper conductor
AWG-range	1000-1000
Material	Copper
Surface protection	Tinned
Insulation	None
Type of connection	End connector
For pull protected connections	Y

Packaging

Insulation

raonaging	
Outer Quantity	10
Outer Dimensions (inches)	7.25x6.5x4
Weight Uom	1.12 lbs. Each

Documents / Support Tools

Catalog Page

Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

• Tapered ends enable use in high-voltage installations up to 69kV.

and minimizes voltage drop.

• Tin-Plated. Resists corrosion and extends shelf life.

North American Specifications (UNSPSC)		
UNSPSC	39121449 Wire or cable compression splice	
IGCC	4669 Wire or cable compression splice	
Туре	Tapered Splice	
Material	Copper	
Finish	Tin Plated	
Voltage Rating	69 kV	

None



TC 1000 7TAH007890R0074 78378675390 L

Copper Tin-Plated Tapered Splices - Dimpled Center Stop, Wire Size 1000 kcmil

· Produced from seamless electrolytic copper tubing which provides high conductivity



Representative