

# AD8274\* Product Page Quick Links

Last Content Update: 08/30/2016

---

## Comparable Parts

View a parametric search of comparable parts

## Documentation

### Data Sheet

- AD8274: Very Low Distortion, Precision Difference Amplifier Data Sheet

### Technical Books

- A Designer's Guide to Instrumentation Amplifiers, 3rd Edition, 2006

## Tools and Simulations

- AD8274 SPICE Macro Model

## Reference Designs

- CN0116
- CN0122

## Reference Materials

### Technical Articles

- High-performance Adder Uses Instrumentation Amplifiers

## Design Resources

- AD8274 Material Declaration
- PCN-PDN Information
- Quality And Reliability
- Symbols and Footprints

## Discussions

View all AD8274 EngineerZone Discussions

## Sample and Buy

Visit the product page to see pricing options

## Technical Support

Submit a technical question or find your regional support number

---

\* This page was dynamically generated by Analog Devices, Inc. and inserted into this data sheet. Note: Dynamic changes to the content on this page does not constitute a change to the revision number of the product data sheet. This content may be frequently modified.

## TABLE OF CONTENTS

|                                 |   |                                                  |    |
|---------------------------------|---|--------------------------------------------------|----|
| Features .....                  | 1 | Pin Configurations and Function Description..... | 5  |
| Applications.....               | 1 | Typical Performance Characteristics .....        | 6  |
| Functional Block Diagram .....  | 1 | Theory of Operation .....                        | 12 |
| General Description .....       | 1 | Circuit Information.....                         | 12 |
| Revision History .....          | 2 | Driving the AD8274.....                          | 12 |
| Specifications.....             | 3 | Power Supplies.....                              | 12 |
| Absolute Maximum Ratings.....   | 4 | Input Voltage Range.....                         | 12 |
| Thermal Resistance .....        | 4 | Configurations.....                              | 13 |
| Maximum Power Dissipation ..... | 4 | Driving Cabling .....                            | 14 |
| Short-Circuit Current .....     | 4 | Outline Dimensions .....                         | 15 |
| ESD Caution.....                | 4 | Ordering Guide .....                             | 15 |

## REVISION HISTORY

### 8/11—Rev. B to Rev. C

|                                                         |   |
|---------------------------------------------------------|---|
| Changes to Input Voltage Range Parameter, Table 2 ..... | 3 |
|---------------------------------------------------------|---|

### 1/11—Rev. A to Rev. B

|                                                           |    |
|-----------------------------------------------------------|----|
| Changes to Impedance/Differential Parameter, Table 2..... | 3  |
| Changes to Figure 17.....                                 | 8  |
| Updated Outline Dimensions .....                          | 15 |

### 12/08—Rev. 0 to Rev. A

|                                        |   |
|----------------------------------------|---|
| Changes to Figure 8 and Figure 10..... | 6 |
|----------------------------------------|---|

### 7/08—Revision 0: Initial Version

## SPECIFICATIONS

$V_S = \pm 15\text{ V}$ ,  $V_{REF} = 0\text{ V}$ ,  $T_A = 25^\circ\text{C}$ ,  $R_L = 2\text{ k}\Omega$ , unless otherwise noted.

Table 2.

| Parameter                                    | Conditions                                                             | G = ½                    |         |                          | G = 2                      |         |                            | Unit   |
|----------------------------------------------|------------------------------------------------------------------------|--------------------------|---------|--------------------------|----------------------------|---------|----------------------------|--------|
|                                              |                                                                        | Min                      | Typ     | Max                      | Min                        | Typ     | Max                        |        |
| DYNAMIC PERFORMANCE                          |                                                                        |                          |         |                          |                            |         |                            |        |
| Bandwidth                                    |                                                                        |                          | 20      |                          |                            | 10      |                            | MHz    |
| Slew Rate                                    |                                                                        | 20                       |         |                          | 20                         |         |                            | V/μs   |
| Settling Time to 0.1%                        | 10 V step on output,<br>C <sub>L</sub> = 100 pF                        |                          | 650     | 750                      |                            | 675     | 775                        | ns     |
| Settling Time to 0.01%                       | 10 V step on output,<br>C <sub>L</sub> = 100 pF                        |                          | 725     | 800                      |                            | 750     | 825                        | ns     |
| NOISE/DISTORTION <sup>1</sup>                |                                                                        |                          |         |                          |                            |         |                            |        |
| THD + Noise                                  | f = 1 kHz,<br>V <sub>OUT</sub> = 10 V p-p,<br>600 Ω load               |                          | 0.00025 |                          |                            | 0.00035 |                            | %      |
| Noise Floor, RTO <sup>2</sup>                | 20 kHz BW                                                              |                          | −106    |                          |                            | −100    |                            | dBu    |
| Output Voltage Noise<br>(Referred to Output) | f = 20 Hz to 20 kHz                                                    |                          | 3.5     |                          |                            | 7       |                            | μV rms |
|                                              | f = 1 kHz                                                              |                          | 26      |                          |                            | 52      |                            | nV/√Hz |
| GAIN                                         |                                                                        |                          |         |                          |                            |         |                            |        |
| Gain Error                                   |                                                                        |                          |         | 0.03                     |                            |         | 0.03                       | %      |
| Gain Drift                                   | −40°C to +85°C                                                         |                          | 0.5     | 2                        |                            | 0.5     | 2                          | ppm/°C |
| Gain Nonlinearity                            | V <sub>OUT</sub> = 10 V p-p,<br>600 Ω load                             |                          | 2       |                          |                            | 2       |                            | ppm    |
| INPUT CHARACTERISTICS                        |                                                                        |                          |         |                          |                            |         |                            |        |
| Offset <sup>3</sup>                          | Referred to output                                                     |                          | 150     | 700                      |                            | 300     | 1100                       | μV     |
| vs. Temperature                              | −40°C to +85°C                                                         |                          | 3       |                          |                            | 6       |                            | μV/°C  |
| vs. Power Supply                             | V <sub>S</sub> = ±2.5 V to ±18 V                                       |                          |         | 5                        |                            |         | 10                         | μV/V   |
| Common-Mode Rejection<br>Ratio               | V <sub>CM</sub> = ±40 V,<br>R <sub>S</sub> = 0 Ω,<br>referred to input | 77                       | 86      |                          | 83                         | 92      |                            | dB     |
| Input Voltage Range <sup>4</sup>             |                                                                        | 3(−V <sub>S</sub> + 1.5) |         | 3(+V <sub>S</sub> − 1.5) | 1.5(−V <sub>S</sub> + 1.5) |         | 1.5(+V <sub>S</sub> − 1.5) | V      |
| Impedance <sup>5</sup>                       |                                                                        |                          |         |                          |                            |         |                            |        |
| Differential                                 | V <sub>CM</sub> = 0 V                                                  |                          | 36      |                          |                            | 9       |                            | kΩ     |
| Common Mode <sup>6</sup>                     |                                                                        |                          | 9       |                          |                            | 9       |                            | kΩ     |
| OUTPUT CHARACTERISTICS                       |                                                                        |                          |         |                          |                            |         |                            |        |
| Output Swing                                 |                                                                        | −V <sub>S</sub> + 1.5    |         | +V <sub>S</sub> − 1.5    | −V <sub>S</sub> + 1.5      |         | +V <sub>S</sub> − 1.5      | V      |
| Short-Circuit Current Limit                  | Sourcing                                                               |                          | 90      |                          |                            | 90      |                            | mA     |
|                                              | Sinking                                                                |                          | 60      |                          |                            | 60      |                            | mA     |
| Capacitive Load Drive                        |                                                                        |                          | 200     |                          |                            | 1200    |                            | pF     |
| POWER SUPPLY                                 |                                                                        |                          |         |                          |                            |         |                            |        |
| Supply Current (per<br>Amplifier)            |                                                                        |                          | 2.3     | 2.6                      |                            | 2.3     | 2.6                        | mA     |
| TEMPERATURE RANGE                            |                                                                        |                          |         |                          |                            |         |                            |        |
| Specified Performance                        |                                                                        | −40                      |         | +85                      | −40                        |         | +85                        | °C     |

<sup>1</sup> Includes amplifier voltage and current noise, as well as noise of internal resistors.

<sup>2</sup> dBu = 20 log(V rms/0.7746).

<sup>3</sup> Includes input bias and offset current errors.

<sup>4</sup> May also be limited by absolute maximum input voltage or by the output swing. See the Absolute Maximum Ratings section and Figure 8 through Figure 11 for details.

<sup>5</sup> Internal resistors are trimmed to be ratio matched but to have  $\pm 20\%$  absolute accuracy.

<sup>6</sup> Common mode is calculated by looking into both inputs. The common-mode impedance at only one input is 18 k $\Omega$ .

ABSOLUTE MAXIMUM RATINGS

Table 3.

| Parameter                                              | Rating                 |
|--------------------------------------------------------|------------------------|
| Supply Voltage                                         | ±18 V                  |
| Maximum Voltage at Any Input Pin                       | −V <sub>S</sub> + 40 V |
| Minimum Voltage at Any Input Pin                       | +V <sub>S</sub> − 40 V |
| Storage Temperature Range                              | −65°C to +150°C        |
| Specified Temperature Range                            | −40°C to +85°C         |
| Package Glass Transition Temperature (T <sub>G</sub> ) | 150°C                  |

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL RESISTANCE

The  $\theta_{JA}$  values in Table 4 assume a 4-layer JEDEC standard board with zero airflow.

Table 4. Thermal Resistance

| Package Type | $\theta_{JA}$ | Unit |
|--------------|---------------|------|
| 8-Lead MSOP  | 135           | °C/W |
| 8-Lead SOIC  | 121           | °C/W |

MAXIMUM POWER DISSIPATION

The maximum safe power dissipation for the AD8274 is limited by the associated rise in junction temperature ( $T_J$ ) on the die. At approximately 150°C, which is the glass transition temperature, the properties of the plastic change. Even temporarily exceeding this temperature limit may change the stresses that the package exerts on the die, permanently shifting the parametric performance of the amplifiers. Exceeding a temperature of 150°C for an extended period may result in a loss of functionality.




Figure 2. Maximum Power Dissipation vs. Ambient Temperature

SHORT-CIRCUIT CURRENT

The AD8274 has built-in, short-circuit protection that limits the output current (see Figure 16 for more information). While the short-circuit condition itself does not damage the part, the heat generated by the condition can cause the part to exceed its maximum junction temperature, with corresponding negative effects on reliability. Figure 2 and Figure 16, combined with knowledge of the part's supply voltages and ambient temperature, can be used to determine whether a short circuit will cause the part to exceed its maximum junction temperature.

ESD CAUTION



**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATIONS AND FUNCTION DESCRIPTION




Figure 3. MSOP Pin Configuration




Figure 4. SOIC Pin Configuration

Table 5. Pin Function Descriptions

| Pin No. | Mnemonic | Description                                                                                                                                             |
|---------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1       | REF      | 6 k $\Omega$ Resistor to Noninverting Terminal of Op Amp. Used as reference pin in G = ½ configuration. Used as positive input in G = 2 configuration.  |
| 2       | -IN      | 12 k $\Omega$ Resistor to Inverting Terminal of Op Amp. Used as negative input in G = ½ configuration. Connect to output in G = 2 configuration.        |
| 3       | +IN      | 12 k $\Omega$ Resistor to Noninverting Terminal of Op Amp. Used as positive input in G = ½ configuration. Used as reference pin in G = 2 configuration. |
| 4       | -Vs      | Negative Supply.                                                                                                                                        |
| 5       | SENSE    | 6 k $\Omega$ Resistor to Inverting Terminal of Op Amp. Connect to output in G = ½ configuration. Used as negative input in G = 2 configuration.         |
| 6       | OUT      | Output.                                                                                                                                                 |
| 7       | +Vs      | Positive Supply.                                                                                                                                        |
| 8       | NC       | No Connect.                                                                                                                                             |

## TYPICAL PERFORMANCE CHARACTERISTICS

$V_S = \pm 15\text{ V}$ ,  $T_A = 25^\circ\text{C}$ , gain =  $\frac{1}{2}$ , difference amplifier configuration, unless otherwise noted.




Figure 5. CMR vs. Temperature, Normalized at  $25^\circ\text{C}$ , Gain =  $\frac{1}{2}$




Figure 8. Input Common-Mode Voltage vs. Output Voltage, Gain =  $\frac{1}{2}$ ,  $\pm 15\text{ V}$  Supplies




Figure 6. System Offset vs. Temperature, Normalized at  $25^\circ\text{C}$ , Referred to Output, Gain =  $\frac{1}{2}$




Figure 9. Input Common-Mode Voltage vs. Output Voltage, Gain =  $\frac{1}{2}$ ,  $\pm 5\text{ V}$  and  $\pm 2.5\text{ V}$  Supplies




Figure 7. Gain Error vs. Temperature, Normalized at  $25^\circ\text{C}$ , Gain =  $\frac{1}{2}$




Figure 10. Input Common-Mode Voltage vs. Output Voltage, Gain = 2,  $\pm 15\text{ V}$  Supplies




Figure 11. Input Common-Mode Voltage vs. Output Voltage, Gain = 2,  $\pm 5$  V and  $\pm 2.5$  V Supplies




Figure 14. Gain vs. Frequency




Figure 12. Power Supply Rejection Ratio vs. Frequency, Gain =  $\frac{1}{2}$ , Referred to Output




Figure 15. Common-Mode Rejection Ratio vs. Frequency, Referred to Input




Figure 13. Maximum Output Voltage vs. Frequency




Figure 16. Short-Circuit Current vs. Temperature




Figure 17. Output Voltage Swing vs.  $R_L$ ,  $V_S = \pm 15\text{ V}$




Figure 20. Small-Signal Step Response, Gain =  $\frac{1}{2}$




Figure 18. Output Voltage vs.  $I_{OUT}$




Figure 21. Small-Signal Pulse Response with 500 pF Capacitor Load, Gain = 2




Figure 19. Small-Signal Step Response, Gain = 2




Figure 22. Small-Signal Pulse Response for 100 pF Capacitive Load, Gain =  $\frac{1}{2}$




Figure 23. Small-Signal Overshoot vs. Capacitive Load, Gain =  $\frac{1}{2}$ , No Resistive Load




Figure 26. Small-Signal Overshoot vs. Capacitive Load, Gain = 2, 600  $\Omega$  in Parallel with Capacitive Load




Figure 24. Small-Signal Overshoot vs. Capacitive Load, Gain =  $\frac{1}{2}$ , 600  $\Omega$  in Parallel with Capacitive Load




Figure 27. Large-Signal Pulse Response, Gain =  $\frac{1}{2}$




Figure 25. Small-Signal Overshoot vs. Capacitive Load, Gain = 2, No Resistive Load




Figure 28. Large-Signal Pulse Response, Gain = 2




Figure 29. Slew Rate vs. Temperature




Figure 32. THD + N vs. Frequency, Filter = 22k Hz




Figure 30. Voltage Noise Density vs. Frequency, Referred to Output




Figure 33. THD + N vs. Frequency, Filter = 120 kHz





Figure 31. 0.1 Hz to 10 Hz Voltage Noise, RTO

Figure 34. THD + N vs. Output Amplitude,  $G = \frac{1}{2}$




Figure 35. THD + N vs. Output Amplitude,  $G = 2$




Figure 37. Harmonic Distortion Products vs. Frequency,  $G = 2$




Figure 36. Harmonic Distortion Products vs. Frequency,  $G = \frac{1}{2}$

## THEORY OF OPERATION




Figure 38. Functional Block Diagram

### CIRCUIT INFORMATION

The AD8274 consists of a high precision, low distortion op amp and four trimmed resistors. These resistors can be connected to make a wide variety of amplifier configurations, including difference, noninverting, and inverting configurations. Using the on-chip resistors of the AD8274 provides the designer with several advantages over a discrete design.

#### DC Performance

Much of the dc performance of op amp circuits depends on the accuracy of the surrounding resistors. The resistors on the AD8274 are laid out to be tightly matched. The resistors of each part are laser trimmed and tested for their matching accuracy. Because of this trimming and testing, the AD8274 can guarantee high accuracy for specifications such as gain drift, common-mode rejection, and gain error.

#### AC Performance

Because feature size is much smaller in an integrated circuit than on a printed circuit board (PCB), the corresponding parasitics are also smaller. The smaller feature size helps the ac performance of the AD8274. For example, the positive and negative input terminals of the AD8274 op amp are not pinned out intentionally. By not connecting these nodes to the traces on the PCB, the capacitance remains low, resulting in both improved loop stability and common-mode rejection over frequency.

#### Production Costs

Because one part, rather than several, is placed on the PCB, the board can be built more quickly.

#### Size

The AD8274 fits a precision op amp and four resistors in one 8-lead MSOP or SOIC package.

### DRIVING THE AD8274

The AD8274 is easy to drive, with all configurations presenting at least several kilohms ( $k\Omega$ ) of input resistance. The AD8274 should be driven with a low impedance source: for example, another amplifier. The gain accuracy and common-mode rejection of the AD8274 depend on the matching of its resistors. Even source resistance of a few ohms can have a substantial effect on these specifications.

### POWER SUPPLIES

A stable dc voltage should be used to power the AD8274. Noise on the supply pins can adversely affect performance. A bypass capacitor of  $0.1 \mu\text{F}$  should be placed between each supply pin and ground, as close as possible to each supply pin. A tantalum capacitor of  $10 \mu\text{F}$  should also be used between each supply and ground. It can be farther away from the supply pins and, typically, it can be shared by other precision integrated circuits.

The AD8274 is specified at  $\pm 15 \text{ V}$ , but it can be used with unbalanced supplies, as well. For example,  $-V_S = 0 \text{ V}$ ,  $+V_S = 20 \text{ V}$ . The difference between the two supplies must be kept below  $36 \text{ V}$ .

### INPUT VOLTAGE RANGE

The AD8274 can measure voltages beyond the rails. For the  $G = \frac{1}{2}$  and  $G = 2$  difference amplifier configurations, see the input voltage range in Table 2 for specifications.

The AD8274 is able to measure beyond the rail because the internal resistors divide down the voltage before it reaches the internal op amp. Figure 39 shows an example of how the voltage division works in the difference amplifier configuration. For the AD8274 to measure correctly, the input voltages at the internal op amp must stay within  $1.5 \text{ V}$  of either supply rail.




Figure 39. Voltage Division in the Difference Amplifier Configuration

For best long-term reliability of the part, voltages at any of the part's inputs (Pin 1, Pin 2, Pin 3, or Pin 5) should stay within  $+V_S - 40 \text{ V}$  to  $-V_S + 40 \text{ V}$ . For example, on  $\pm 10 \text{ V}$  supplies, input voltages should not exceed  $\pm 30 \text{ V}$ .

## CONFIGURATIONS

The AD8274 can be configured in several ways; see Figure 40 to Figure 47. Because these configurations rely on the internal, matched resistors, all of these configurations have excellent gain accuracy and gain drift. Note that the AD8274 internal op amp is stable for noise gains of 1.5 and higher, so the AD8274 should not be placed in a unity-gain follower configuration.




Figure 40. Difference Amplifier,  $G = \frac{1}{2}$




Figure 44. Noninverting Amplifier,  $G = \frac{1}{2}$




Figure 41. Difference Amplifier,  $G = 2$




Figure 45. Noninverting Amplifier,  $G = 2$




Figure 42. Inverting Amplifier,  $G = -\frac{1}{2}$




Figure 46. Noninverting Amplifier,  $G = 1.5$




Figure 43. Inverting Amplifier,  $G = -2$




Figure 47. Noninverting Amplifier,  $G = 3$

## DRIVING CABLING

Because the AD8274 can drive large voltages at high output currents and slew rates, it makes an excellent cable driver. It is good practice to put a small value resistor between the AD8274 output and cable, since capacitance in the cable can cause peaking or instability in the output response. A resistance of  $20\ \Omega$  or higher is recommended.





Figure 48. Driving Cabling


## OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MS-012-AA  
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS  
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR  
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 49. 8-Lead Standard Small Outline Package [SOIC\_N]  
Narrow Body (R-8)

Dimensions shown in millimeters and (inches)



COMPLIANT TO JEDEC STANDARDS MO-187-AA

Figure 50. 8-Lead Mini Small Outline Package [MSOP]  
(RM-8)

Dimensions shown in millimeters

## ORDERING GUIDE

| Model <sup>1</sup> | Temperature Range | Package Description              | Package Option | Branding |
|--------------------|-------------------|----------------------------------|----------------|----------|
| AD8274ARZ          | −40°C to +85°C    | 8-Lead SOIC_N                    | R-8            |          |
| AD8274ARZ-R7       | −40°C to +85°C    | 8-Lead SOIC_N, 7" Tape and Reel  | R-8            |          |
| AD8274ARZ-RL       | −40°C to +85°C    | 8-Lead SOIC_N, 13" Tape and Reel | R-8            |          |
| AD8274ARMZ         | −40°C to +85°C    | 8-Lead MSOP                      | RM-8           | Y1B      |
| AD8274ARMZ-R7      | −40°C to +85°C    | 8-Lead MSOP, 7" Tape and Reel    | RM-8           | Y1B      |
| AD8274ARMZ-RL      | −40°C to +85°C    | 8-Lead MSOP, 13" Tape and Reel   | RM-8           | Y1B      |

<sup>1</sup> Z = RoHS Compliant Part.

**AD8274**

## NOTES