

Maximum Ratings

Characteristic	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 8	V
Continuous Source Current @ $V_{GS} = 4.5V$, $t = 10s$ (Note 5)	I_D	$T_A = +25^\circ C$ $T_A = +70^\circ C$	A
		3.3 2.6	
Continuous Source Current @ $V_{GS} = 4.5V$, $t = 10s$ (Note 6)	I_D	$T_A = +25^\circ C$ $T_A = +70^\circ C$	A
		4.5 3.6	
Pulsed Drain Current (Pulse Duration 10 μs , Duty Cycle $\leq 1\%$)	I_{DM}	16	A
Continuous Source-Drain Diode Current	I_S	1.2	A
Pulse Diode Forward Current	I_{SM}	10	A

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Total Power Dissipation (Note 5)	P_D	0.72	W
Thermal Resistance, Junction to Ambient (Note 5)	$R_{\theta JA}$	175	$^\circ C/W$
Thermal Resistance, Junction to Case (Note 5)	$R_{\theta JC}$	40	$^\circ C/W$
Total Power Dissipation (Note 6)	P_D	1.18	W
Thermal Resistance, Junction to Ambient (Note 6)	$R_{\theta JA}$	106	$^\circ C/W$
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ C$

Electrical Characteristics (@ $T_A = +25^\circ C$, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 7)						
Drain-Source Breakdown Voltage	BV_{DSS}	20	—	—	V	$V_{GS} = 0V, I_D = 250\mu A$
Zero Gate Voltage Drain Current	I_{DSS}	—	—	1.0	μA	$V_{DS} = 20V, V_{GS} = 0V$
		—	—	1.0	mA	$V_{DS} = 20V, V_{GS} = 0V, T_J = +150^\circ C$
Gate-Body Leakage	I_{GSS}	—	—	± 100	nA	$V_{GS} = \pm 8V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 7)						
Gate Threshold Voltage	$V_{GS(TH)}$	0.4	—	0.9	V	$V_{DS} = V_{GS}, I_D = 250\mu A$
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	29	40	m Ω	$V_{GS} = 4.5V, I_D = 1.5A$
			32	50		$V_{GS} = 2.5V, I_D = 1.0A$
			36	56		$V_{GS} = 1.8V, I_D = 1.0A$
			43	70		$V_{GS} = 1.5V, I_D = 0.5A$
Body Diode Forward Voltage	V_{SD}	—	0.7	1.2	V	$V_{GS} = 0V, I_S = 1.5A$
DYNAMIC CHARACTERISTICS (Note 8)						
Input Capacitance	C_{iss}	—	1056	1400	pF	$V_{DS} = 10V, V_{GS} = 0V, f = 1.0MHz$
Output Capacitance	C_{oss}	—	117	160	pF	
Reverse Transfer Capacitance	C_{rss}	—	105	140	pF	
Gate Resistance	R_g	—	0.98	1.5	Ω	$V_{DS} = 0V, V_{GS} = 0V, f = 1MHz$
Total Gate Charge ($V_{GS} = 4.5V$)	Q_g	—	13.1	26.5	nC	$V_{DS} = 10V, I_D = 1.5A$
Total Gate Charge ($V_{GS} = 8V$)	Q_g	—	23.2	47	nC	
Gate-Source Charge	Q_{gs}	—	1.4	—	nC	
Gate-Drain Charge	Q_{gd}	—	2.1	—	nC	
Reverse Recovery Charge	Q_{RR}	—	2.16	6	nC	$I_F = 1.5A, di/dt = 100A/\mu s$
Body Diode Reverse Recovery Time	t_{RR}	—	7.92	18	ns	
Reverse Recovery Fall Time	t_A	—	6.5	—	ns	
Reverse Recovery Rise Time	t_B	—	4.12	—	ns	
Turn-On Delay Time	$t_{D(ON)}$	—	4.57	10	ns	$V_{DD} = 10V, I_D = 1.5A$ $V_{GEN} = 4.5V, R_G = 1\Omega, R_L = 6.7\Omega$
Turn-On Rise Time	t_R	—	6.33	15	ns	
Turn-Off Delay Time	$t_{D(OFF)}$	—	19.84	42	ns	
Turn-Off Fall Time	t_F	—	2.96	6	ns	
Turn-On Delay Time	$t_{D(ON)}$	—	2.88	6	ns	$V_{DD} = 10V, I_D = 1.5A$ $V_{GEN} = 8V, R_G = 1\Omega, R_L = 6.7\Omega$
Turn-On Rise Time	t_R	—	6.31	14	ns	
Turn-Off Delay Time	$t_{D(OFF)}$	—	14.9	30	ns	
Turn-Off Fall Time	t_F	—	1.71	4	ns	

- Notes:
- Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.
 - Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.
 - Short duration pulse test used to minimize self-heating effect.
 - Guaranteed by design. Not subject to production testing.




Figure 1 Typical Output Characteristic




Figure 2 Typical Transfer Characteristics




Figure 3 Typical On-Resistance vs. Drain Current and Gate Voltage




Figure 4 Typical Transfer Characteristics




Figure 5 On-Resistance Variation with Temperature




Figure 6 Gate Threshold Variation vs. Junction Temperature




Figure 7 Typical Junction Capacitance




Figure 8 Gate Charge




Figure 9 Single Pulse Maximum Power Dissipation






Figure 10 SOA, Safe Operation Area



Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

U-WLB1010-4 (Type B)




U-WLB1010-4 (Type B)			
Dim	Min	Max	Typ
A	0.4535	0.5565	0.5050
A1	0.2115	0.2585	0.2350
A2	0.2200	0.2700	0.2450
A3	0.0220	0.0280	0.0250
b	0.2880	0.3520	0.3200
D	1.030	1.070	1.050
e	0.500 BSC		
E	1.030	1.070	1.050
All Dimensions in mm			

Suggested Pad Layout

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

U-WLB1010-4 (Type B)



Dimensions	Value (in mm)
C	0.500
X	0.3200

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2018, Diodes Incorporated

www.diodes.com