

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter		Min.	Typ.	Max.	Units	Conditions
V _{(BR)DSS}	Drain-to-Source Breakdown Voltage	N-Ch	20	—	—	V	V _{GS} = 0V, I _D = 250μA
		P-Ch	-20	—	—		V _{GS} = 0V, I _D = -250μA
ΔV _{(BR)DSS} /ΔT _J	Breakdown Voltage Temp. Coefficient	N-Ch	—	0.044	—	V/°C	Reference to 25°C, I _D = 1mA
		P-Ch	—	-0.012	—		Reference to 25°C, I _D = -1mA
R _{DS(ON)}	Static Drain-to-Source On-Resistance	N-Ch	—	—	0.050	Ω	V _{GS} = 4.5V, I _D = 2.6A ③
			—	—	0.070		V _{GS} = 2.7V, I _D = 2.2A ③
		P-Ch	—	—	0.090		V _{GS} = -4.5V, I _D = -2.2A ③
			—	—	0.140		V _{GS} = -2.7V, I _D = -1.8A ③
V _{GS(th)}	Gate Threshold Voltage	N-Ch	0.70	—	—	V	V _{DS} = V _{GS} , I _D = 250μA
		P-Ch	-0.70	—	—		V _{DS} = V _{GS} , I _D = -250μA
g _{fs}	Forward Transconductance	N-Ch	8.30	—	—	S	V _{DS} = 15V, I _D = 2.6A ③
		P-Ch	4.00	—	—		V _{DS} = -15V, I _D = -2.2A ③
I _{DSS}	Drain-to-Source Leakage Current	N-Ch	—	—	1.0	μA	V _{DS} = 16V, V _{GS} = 0V
		P-Ch	—	—	-1.0		V _{DS} = -16V, V _{GS} = 0V,
		N-Ch	—	—	25		V _{DS} = 16V, V _{GS} = 0V, T _J = 125°C
		P-Ch	—	—	-25		V _{DS} = -16V, V _{GS} = 0V, T _J = 125°C
I _{GSS}	Gate-to-Source Forward Leakage	N-P	—	—	±100		V _{GS} = ± 12V
Q _g	Total Gate Charge	N-Ch	—	—	20		N-Channel
		P-Ch	—	—	22		I _D = 2.6A, V _{DS} = 16V, V _{GS} = 4.5V ③
Q _{gs}	Gate-to-Source Charge	N-Ch	—	—	2.2	nC	
		P-Ch	—	—	3.3		P-Channel
Q _{gd}	Gate-to-Drain ("Miller") Charge	N-Ch	—	—	8.0		I _D = -2.2A, V _{DS} = -16V, V _{GS} = -4.5V
		P-Ch	—	—	9.0		
t _{d(on)}	Turn-On Delay Time	N-Ch	—	9.0	—		N-Channel
		P-Ch	—	8.4	—		V _{DD} = 10V, I _D = 2.6A, R _G = 6.0Ω,
t _r	Rise Time	N-Ch	—	42	—		R _D = 3.8Ω ③
		P-Ch	—	26	—		
t _{d(off)}	Turn-Off Delay Time	N-Ch	—	32	—	ns	P-Channel
		P-Ch	—	51	—		V _{DD} = -10V, I _D = -2.2A, R _G = 6.0Ω,
t _f	Fall Time	N-Ch	—	51	—		R _D = 4.5Ω
		P-Ch	—	33	—		
L _D	Internal Drain Inductance	N-P	—	4.0	—	nH	Between lead tip
L _S	Internal Source Inductance	N-P	—	6.0	—		and center of die contact
C _{iss}	Input Capacitance	N-Ch	—	660	—		N-Channel
		P-Ch	—	610	—		V _{GS} = 0V, V _{DS} = 15V, f = 1.0MHz ③
C _{oss}	Output Capacitance	N-Ch	—	280	—	pF	
		P-Ch	—	310	—		P-Channel
C _{rss}	Reverse Transfer Capacitance	N-Ch	—	140	—		V _{GS} = 0V, V _{DS} = -15V, f = 1.0MHz
		P-Ch	—	170	—		

Source-Drain Ratings and Characteristics

	Parameter		Min.	Typ.	Max.	Units	Conditions
I _S	Continuous Source Current (Body Diode)	N-Ch	—	—	2.5	A	
		P-Ch	—	—	-2.5		
I _{SM}	Pulsed Source Current (Body Diode) ①	N-Ch	—	—	21		
		P-Ch	—	—	-17		
V _{SD}	Diode Forward Voltage	N-Ch	—	—	1.0	V	T _J = 25°C, I _S = 1.8A, V _{GS} = 0V ③
		P-Ch	—	—	-1.0		T _J = 25°C, I _S = -1.8A, V _{GS} = 0V ③
t _{rr}	Reverse Recovery Time	N-Ch	—	29	44	ns	N-Channel
		P-Ch	—	56	84		T _J = 25°C, I _F = 2.6A, di/dt = 100A/μs
Q _{rr}	Reverse Recovery Charge	N-Ch	—	22	33	nC	P-Channel ③
		P-Ch	—	71	110		T _J = 25°C, I _F = -2.2A, di/dt = 100A/μs
t _{on}	Forward Turn-On Time	N-P	Intrinsic turn-on time is negligible (turn-on is dominated by L _S +L _D)				

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 23)
- ② N-Channel I_{SD} ≤ 2.6A, di/dt ≤ 100A/μs, V_{DD} ≤ V_{(BR)DSS}, T_J ≤ 150°C
P-Channel I_{SD} ≤ -2.2A, di/dt ≤ 50A/μs, V_{DD} ≤ V_{(BR)DSS}, T_J ≤ 150°C
- ③ Pulse width ≤ 300μs; duty cycle ≤ 2%.
- ④ Surface mounted on FR-4 board, t ≤ 10sec.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 9. Maximum Drain Current Vs. Ambient Temperature




Fig 11a. Gate Charge Test Circuit




Fig 8. Maximum Safe Operating Area




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11b. Basic Gate Charge Waveform




Fig 12. Typical Output Characteristics




Fig 13. Typical Output Characteristics




Fig 14. Typical Transfer Characteristics




Fig 15. Normalized On-Resistance Vs. Temperature




Fig 16. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 17. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 18. Typical Source-Drain Diode Forward Voltage




Fig 20. Maximum Drain Current Vs. Ambient Temperature




Fig 22a. Gate Charge Test Circuit




Fig 19. Maximum Safe Operating Area




Fig 21a. Switching Time Test Circuit




Fig 21b. Switching Time Waveforms




Fig 22b. Basic Gate Charge Waveform






Fig 23. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Peak Diode Recovery dv/dt Test Circuit



* Reverse Polarity for P-Channel

** Use P-Channel Driver for P-Channel Measurements




*** $V_{GS} = 5.0V$ for Logic Level and 3V Drive Devices

Fig 24. For N and P Channel HEXFETS

Package Outline


SO-8 Outline

Dimensions are shown in millimeters (inches)



Part Marking Information

SO-8



Tape & Reel Information

SO-8

Dimensions are shown in millimeters (inches)

