

Table of Content

1 Maximum ratings3

2 Thermal characteristics3

3 Electrical characteristics4

3.1 Static characteristics4

3.2 AC characteristics4

4 Diagrams5

5 Simplified forward characteristic7

6 Package outlines8

1 Maximum ratings

Table 3 Maximum ratings

Parameter	Symbol	Values			Unit	Note/Test condition
		Min.	Typ.	Max.		
Continuous forward current	I_F	–	–	8	A	$T_C \leq 145\text{ °C}, D = 1$
		–	–	11		$T_C \leq 125\text{ °C}, D = 1$
		–	–	20		$T_C \leq 25\text{ °C}, D = 1$
Surge-repetitive forward current, sine halfwave ¹	$I_{F, RM}$	–	–	35		$T_C = 25\text{ °C}, t_p = 10\text{ ms}$
Surge non-repetitive forward current, sine halfwave	$I_{F, SM}$	–	–	47		$T_C = 25\text{ °C}, t_p = 10\text{ ms}$
		–	–	37		$T_C = 150\text{ °C}, t_p = 10\text{ ms}$
Non-repetitive peak forward current	$I_{F, max}$	–	–	530		$T_C = 25\text{ °C}, t_p = 10\text{ }\mu\text{s}$
i^2t value	$\int i^2 dt$	–	–	11	A ² s	$T_C = 25\text{ °C}, t_p = 10\text{ ms}$
		–	–	6.9		$T_C = 150\text{ °C}, t_p = 10\text{ ms}$
Repetitive peak reverse voltage	V_{RRM}	–	–	650	V	$T_C = 25\text{ °C}$
Diode dv/dt ruggedness	dv/dt	–	–	150	V/ns	$V_R = 0..480\text{ V}$
Power dissipation	P_{tot}	–	–	63	W	$T_C = 25\text{ °C}, R_{thJC, max}$
Operating and storage temperature	T_j	-55	–	175	°C	–
	T_{stg}					
Mounting torque	–	–	–	70	Ncm	M3 screw

2 Thermal characteristics

Table 4 Thermal characteristics (PG-TO-220-2)

Parameter	Symbol	Values			Unit	Note/Test condition
		Min.	Typ.	Max.		
Thermal resistance, junction-case	R_{thJC}	–	1.4	2.4	K/W	–
Thermal resistance, junction-ambient	R_{thJA}	–	–	62		lead
Soldering temperature, wavesoldering only allowed at leads	T_{sld}	–	–	260	°C	1.6 mm (0.063 in.) from case for 10 s

¹ The surge-repetitive forward current test was performed with 1000 pulses (half-wave rectified sine with the 10 ms period).

3 Electrical characteristics

3.1 Static characteristics

Table 5 Static characteristics

Parameter	Symbol	Values			Unit	Note/Test condition
		Min.	Typ.	Max.		
DC blocking voltage	V_{DC}	650	–	–	V	$T_j = 25\text{ °C}$
Diode forward voltage	V_F	–	1.25	1.35		$I_F = 8\text{ A}, T_j = 25\text{ °C}$
		–	1.5	–		$I_F = 8\text{ A}, T_j = 150\text{ °C}$
Reverse current	I_R	–	0.8	27	μA	$V_R = 420\text{ V}, T_j = 25\text{ °C}$
		–	27	–		$V_R = 420\text{ V}, T_j = 125\text{ °C}$
		–	62	–		$V_R = 420\text{ V}, T_j = 150\text{ °C}$

3.2 AC characteristics

Table 6 AC characteristics

Parameter	Symbol	Values			Unit	Note/Test Condition
		Min.	Typ.	Max.		
Total capacitive charge	Q_c	–	12.2	–	nC	$V_R = 400\text{ V}, T_j = 150\text{ °C},$ $di/dt = 200\text{ A}/\mu\text{s}, I_F \leq I_{F,MAX}$
Total capacitance	C	–	401	–	pF	$V_R = 1\text{ V}, f = 1\text{ MHz},$ $T_j = 25\text{ °C}$
		–	24	–		$V_R = 300\text{ V}, f = 1\text{ MHz},$ $T_j = 25\text{ °C}$
		–	23	–		$V_R = 600\text{ V}, f = 1\text{ MHz},$ $T_j = 25\text{ °C}$

4 Diagrams




Figure 1 Power dissipation




Figure 2 Max. forward current




Figure 3 Typ. forward characteristics




Figure 4 Typ. forward characteristics
in surge current




Figure 5 Typ. cap. charge vs. current slope




Figure 6 Typ. reverse current vs. reverse voltage




Figure 7 Max. transient thermal impedance




Figure 8 Typ. capacitance vs. reverse voltage




Figure 9 Typ. capacitance stored energy

5 Simplified forward characteristic




Figure 10 Equivalent forward current curve

Figure 11 Mathematical Equation

6 Package outlines




Figure 12 Outlines of the package PG-TO220-2, dimensions in mm/inches

Revision History

Major changes since the last revision

Revision	Date	Subject (major changes since last revision)
2.0	2017-05-23	Release of final version

Other Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2017-05-23

Published by

Infineon Technologies AG

81726 München, Germany

© 2017 Infineon Technologies AG.

All Rights Reserved.

Do you have a question about this document?

Email: erratum@infineon.com

Document reference

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.