

ABSOLUTE MAXIMUM RATINGS
(25°C unless otherwise specified)

Storage Temperature _____ -40°C to + 125°C
Operating Temperature _____ -25°C to + 100°C
Lead Soldering Temperature
(1/16 inch (1.6mm) from case for 10 secs) 260°C

INPUT DIODE

Forward Current _____ 50mA
Reverse Voltage _____ 6V
Power Dissipation _____ 70mW

OUTPUT TRANSISTOR

Collector-emitter Voltage BV_{CEO}
IL2, ILD2, ILQ2, IL5, ILD5, ILQ5 _____ 70V
IL1, ILD1, ILQ1, IL74, ILD74, ILQ74 _____ 50V
Emitter-collector Voltage BV_{ECO} _____ 6V
Collector Current _____ 50mA
Power Dissipation _____ 150mW

POWER DISSIPATION

Total Power Dissipation _____ 170mW
(derate linearly 2.67mW/°C above 25°C)


ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage (V_F)		1.2	1.65	V	$I_F = 50\text{mA}$ $V_R = 4\text{V}$
	Reverse Current (I_R)			10	μA	
Output	Collector-emitter Breakdown (BV_{CEO}) IL2, ILD2, ILQ2, IL5, ILD5, ILQ5	70			V	$I_C = 1\text{mA}$, (Note 2) $I_C = 1\text{mA}$, (Note 2) $I_E = 100\mu\text{A}$ $V_{CE} = 10\text{V}$
	IL1, ILD1, ILQ1, IL74, ILD74, ILQ74	50			V	
	Emitter-collector Breakdown (BV_{ECO})	6			V	
	Collector-emitter Dark Current (I_{CEO})			50	nA	
Coupled	Current Transfer Ratio (CTR) (Note 2)					
	IL1, ILD1, ILQ1	20		300	%	$10\text{mA } I_F, 10\text{V } V_{CE}$
	IL2, ILD2, ILQ2	100		500	%	$10\text{mA } I_F, 10\text{V } V_{CE}$
	IL5, ILD5, ILQ5	50		400	%	$10\text{mA } I_F, 10\text{V } V_{CE}$
	IL74, ILD74, ILQ74	12.5			%	$16\text{mA } I_F, 5\text{V } V_{CE}$
	Saturated Current Transfer Ratio					
	IL1, ILD1, ILQ1		75		%	$10\text{mA } I_F, 0.4\text{V } V_{CE}$
	IL2, ILD2, ILQ2		170		%	$10\text{mA } I_F, 0.4\text{V } V_{CE}$
	IL5, ILD5, ILQ5		100		%	$10\text{mA } I_F, 0.4\text{V } V_{CE}$
	IL74, ILD74, ILQ74	12.5			%	$16\text{mA } I_F, 0.5\text{V } V_{CE}$
	Collector-emitter Saturation Voltage, $V_{CE(SAT)}$			0.4	V	$16\text{mA } I_F, 2\text{mA } I_C$
	Input to Output Isolation Voltage V_{ISO}	5300			V_{RMS}	See note 1
	Input to Output Isolation Voltage V_{ISO}	7500			V_{PK}	See note 1
	Input-output Isolation Resistance R_{ISO}	5×10^{10}			Ω	$V_{IO} = 500\text{V}$ (note 1)
	Output Rise Time t_r		2		μs	$I_F = 10\text{mA}$
	Output Fall Time t_f		2		μs	$V_{CC} = 5\text{V}, R_L = 75\Omega$


Note 1 Measured with input leads shorted together and output leads shorted together.

Note 2 Special Selections are available on request. Please consult the factory.


Collector Power Dissipation vs. Ambient Temperature




Relative Current Transfer Ratio vs. Ambient Temperature




Forward Current vs. Ambient Temperature



Relative Current Transfer Ratio vs. Forward Current



Relative Current Transfer Ratio vs. Ambient Temperature



Relative Current Transfer Ratio vs. Forward Current

