

MMUN2211LT1 Series

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-Base Cutoff Current (V _{CB} = 50 V, I _E = 0)	I _{CBO}	-	-	100	nAdc
Collector-Emitter Cutoff Current (V _{CE} = 50 V, I _B = 0)	I _{CEO}	-	-	500	nAdc
Emitter-Base Cutoff Current (V _{EB} = 6.0 V, I _C = 0)	I _{EBO}	-	-	0.5	mAdc
MMUN2211LT1, G		-	-	0.2	
MMUN2212LT1, G		-	-	0.1	
MMUN2213LT1, G		-	-	0.2	
MMUN2214LT1, G		-	-	0.9	
MMUN2215LT1, G		-	-	1.9	
MMUN2216LT1, G		-	-	4.3	
MMUN2230LT1, G		-	-	2.3	
MMUN2231LT1, G		-	-	1.5	
MMUN2232LT1, G		-	-	0.18	
MMUN2233LT1, G		-	-	0.13	
MMUN2234LT1, G		-	-	4.0	
MMUN2238LT1, G		-	-	0.1	
MMUN2241LT1, G		-	-		
Collector-Base Breakdown Voltage (I _C = 10 μA, I _E = 0)	V _{(BR)CBO}	50	-	-	Vdc
Collector-Emitter Breakdown Voltage (Note 3), (I _C = 2.0 mA, I _B = 0)	V _{(BR)CEO}	50	-	-	Vdc

ON CHARACTERISTICS (Note 3)

DC Current Gain (V _{CE} = 10 V, I _C = 5.0 mA)	MMUN2211LT1, G	h _{FE}	35	60	-	
	MMUN2212LT1, G		60	100	-	
	MMUN2213LT1, G		80	140	-	
	MMUN2214LT1, G		80	140	-	
	MMUN2215LT1, G		160	350	-	
	MMUN2216LT1, G		160	350	-	
	MMUN2230LT1, G		3.0	5.0	-	
	MMUN2231LT1, G		8.0	15	-	
	MMUN2232LT1, G		15	30	-	
	MMUN2233LT1, G		80	200	-	
	MMUN2234LT1, G		80	150	-	
	MMUN2238LT1, G		160	350	-	
	MMUN2241LT1, G		160	350	-	
Collector-Emitter Saturation Voltage (I _C = 10 mA, I _B = 0.3 mA)	MMUN2211LT1, G	V _{CE(sat)}	-	-	0.25	Vdc
	MMUN2212LT1, G		-	-	0.25	
	MMUN2213LT1, G		-	-	0.25	
	MMUN2214LT1, G		-	-	0.25	
	MMUN2233LT1, G		-	-	0.25	
	MMUN2234LT1, G		-	-	0.25	
(I _C = 10 mA, I _B = 1 mA)	MMUN2215LT1, G		-	-	0.25	
	MMUN2216LT1, G		-	-	0.25	
	MMUN2232LT1, G		-	-	0.25	
	MMUN2238LT1, G		-	-	0.25	
(I _C = 10 mA, I _B = 5 mA)	MMUN2230LT1, G		-	-	0.25	
	MMUN2231LT1, G		-	-	0.25	
	MMUN2241LT1, G		-	-	0.25	

3. Pulse Test: Pulse Width < 300 μs, Duty Cycle < 2.0%.

MMUN2211LT1 Series

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Typ	Max	Unit
ON CHARACTERISTICS (Note 4)					
Output Voltage (on) (V _{CC} = 5.0 V, V _B = 2.5 V, R _L = 1.0 kΩ)	V _{OL}	-	-	0.2	Vdc
MMUN2211LT1, G		-	-	0.2	
MMUN2212LT1, G		-	-	0.2	
MMUN2214LT1, G		-	-	0.2	
MMUN2215LT1, G		-	-	0.2	
MMUN2216LT1, G		-	-	0.2	
MMUN2230LT1, G		-	-	0.2	
MMUN2231LT1, G		-	-	0.2	
MMUN2232LT1, G		-	-	0.2	
MMUN2233LT1, G		-	-	0.2	
MMUN2234LT1, G		-	-	0.2	
MMUN2238LT1, G		-	-	0.2	
(V _{CC} = 5.0 V, V _B = 3.5 V, R _L = 1.0 kΩ)		-	-	0.2	
MMUN2213LT1, G		-	-	0.2	
(V _{CC} = 5.0 V, V _B = 5.0 V, R _L = 1.0 kΩ)		-	-	0.2	
MMUN2241LT1, G		-	-	0.2	
Output Voltage (off) (V _{CC} = 5.0 V, V _B = 0.5 V, R _L = 1.0 kΩ)	V _{OH}	4.9	-	-	Vdc
MMUN2211LT1, G		4.9	-	-	
MMUN2212LT1, G		4.9	-	-	
MMUN2213LT1, G		4.9	-	-	
MMUN2214LT1, G		4.9	-	-	
MMUN2233LT1, G		4.9	-	-	
(V _{CC} = 5.0 V, V _B = 0.05 V, R _L = 1.0 kΩ)		4.9	-	-	
MMUN2230LT1, G		4.9	-	-	
MMUN2234LT1, G		4.9	-	-	
(V _{CC} = 5.0 V, V _B = 0.25 V, R _L = 1.0 kΩ)		4.9	-	-	
MMUN2215LT1, G		4.9	-	-	
MMUN2216LT1, G		4.9	-	-	
MMUN2231LT1, G		4.9	-	-	
MMUN2232LT1, G		4.9	-	-	
MMUN2238LT1, G		4.9	-	-	
MMUN2241LT1, G		4.9	-	-	
Input Resistor	R1	7.0	10	13	kΩ
MMUN2211LT1, G		15.4	22	28.6	
MMUN2212LT1, G		32.9	47	61.1	
MMUN2213LT1, G		7.0	10	13	
MMUN2214LT1, G		7.0	10	13	
MMUN2215LT1, G		3.3	4.7	6.1	
MMUN2216LT1, G		0.7	1.0	1.3	
MMUN2230LT1, G		1.5	2.2	2.9	
MMUN2231LT1, G		3.3	4.7	6.1	
MMUN2232LT1, G		3.3	4.7	6.1	
MMUN2233LT1, G		3.3	4.7	6.1	
MMUN2234LT1, G		15.4	22	28.6	
MMUN2238LT1, G		1.54	2.2	2.88	
MMUN2241LT1, G		70	100	130	
Resistor Ratio	R1/R2	0.8	1.0	1.2	
MMUN2211LT1, G		0.8	1.0	1.2	
MMUN2212LT1, G		0.8	1.0	1.2	
MMUN2213LT1, G		0.8	1.0	1.2	
MMUN2214LT1, G		0.17	0.21	0.25	
MMUN2215LT1, G		-	-	-	
MMUN2216LT1, G		-	-	-	
MMUN2230LT1, G		0.8	1.0	1.2	
MMUN2231LT1, G		0.8	1.0	1.2	
MMUN2232LT1, G		0.8	1.0	1.2	
MMUN2233LT1, G		0.055	0.1	0.185	
MMUN2234LT1, G		0.38	0.47	0.56	
MMUN2238LT1, G		-	-	-	
MMUN2241LT1, G		-	-	-	

4. Pulse Test: Pulse Width < 300 μs, Duty Cycle < 2.0%.

TYPICAL ELECTRICAL CHARACTERISTICS – MMUN2211LT1




Figure 1. Derating Curve




Figure 2. $V_{CE(sat)}$ vs. I_C




Figure 3. DC Current Gain




Figure 4. Output Capacitance




Figure 5. Output Current vs. Input Voltage




Figure 6. Input Voltage vs. Output Current

TYPICAL ELECTRICAL CHARACTERISTICS – MMUN2212LT1




Figure 7. $V_{CE(sat)}$ vs. I_C




Figure 8. DC Current Gain




Figure 9. Output Capacitance




Figure 10. Output Current vs. Input Voltage




Figure 11. Input Voltage vs. Output Current

TYPICAL ELECTRICAL CHARACTERISTICS – MMUN2213LT1




Figure 12. $V_{CE(sat)}$ vs. I_C




Figure 13. DC Current Gain




Figure 14. Output Capacitance




Figure 15. Output Current vs. Input Voltage




Figure 16. Input Voltage vs. Output Current

TYPICAL ELECTRICAL CHARACTERISTICS - MMUN2214LT1




Figure 17. $V_{CE(sat)}$ vs. I_C




Figure 18. DC Current Gain




Figure 19. Output Capacitance




Figure 20. Output Current vs. Input Voltage




Figure 21. Input Voltage vs. Output Current

TYPICAL ELECTRICAL CHARACTERISTICS - MMUN2215LT1




Figure 22. $V_{CE(sat)}$ versus I_C




Figure 23. DC Current Gain




Figure 24. Output Capacitance




Figure 25. Output Current versus Input Voltage




Figure 26. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — MMUN2216LT1




Figure 27. $V_{CE(sat)}$ versus I_C




Figure 28. DC Current Gain




Figure 29. Output Capacitance




Figure 30. Output Current versus Input Voltage




Figure 31. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — MMUN2230LT1




Figure 32. $V_{CE(sat)}$ versus I_C




Figure 33. DC Current Gain




Figure 34. Output Capacitance




Figure 35. Output Current versus Input Voltage




Figure 36. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — MMUN2231LT1




Figure 37. $V_{CE(sat)}$ versus I_C




Figure 38. DC Current Gain




Figure 39. Output Capacitance




Figure 40. Output Current versus Input Voltage




Figure 41. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS – MMUN2232LT1




Figure 42. $V_{CE(sat)}$ vs. I_C




Figure 43. DC Current Gain




Figure 44. Output Capacitance




Figure 45. Output Current vs. Input Voltage




Figure 46. Output Voltage vs. Input Current

TYPICAL ELECTRICAL CHARACTERISTICS – MMUN2233LT1




Figure 47. $V_{CE(sat)}$ vs. I_C




Figure 48. DC Current Gain




Figure 49. Output Capacitance




Figure 50. Output Current vs. Input Voltage




Figure 51. Input Voltage vs. Output Current

TYPICAL ELECTRICAL CHARACTERISTICS — MMUN2234LT1




Figure 52. $V_{CE(sat)}$ versus I_C




Figure 53. DC Current Gain




Figure 54. Output Capacitance




Figure 55. Output Current versus Input Voltage




Figure 56. Input Voltage versus Output Current

MMUN2211LT1 Series

TYPICAL APPLICATIONS FOR NPN BRTs




Figure 57. Level Shifter: Connects 12 or 24 Volt Circuits to Logic




Figure 58. Open Collector Inverter: Inverts the Input Signal

Figure 59. Inexpensive, Unregulated Current Source

MMUN2211LT1 Series

ORDERING INFORMATION


Device	Marking	R1(k)	R2(k)	Package	Shipping [†]
MMUN2211LT1	A8A	10	10	SOT-23	3000 / Tape & Reel
MMUN2211LT1G		10	10	SOT-23 (Pb-Free)	
MMUN2211LT3		10	10	SOT-23	10,000 / Tape & Reel
MMUN2211LT3G		10	10	SOT-23 (Pb-Free)	
MMUN2212LT1	A8B	22	22	SOT-23	3000 / Tape & Reel
MMUN2212LT1G		22	22	SOT-23 (Pb-Free)	
MMUN2213LT1	A8C	47	47	SOT-23	
MMUN2213LT1G		47	47	SOT-23 (Pb-Free)	
MMUN2214LT1	A8D	10	47	SOT-23	
MMUN2214LT1G		10	47	SOT-23 (Pb-Free)	
MMUN2215LT1	A8E	10	∞	SOT-23	
MMUN2215LT1G		10	∞	SOT-23 (Pb-Free)	
MMUN2216LT1	A8F	4.7	∞	SOT-23	
MMUN2216LT1G		4.7	∞	SOT-23 (Pb-Free)	
MMUN2230LT1	A8G	1.0	1.0	SOT-23	
MMUN2230LT1G		1.0	1.0	SOT-23 (Pb-Free)	
MMUN2231LT1	A8H	2.2	2.2	SOT-23	
MMUN2231LT1G		2.2	2.2	SOT-23 (Pb-Free)	
MMUN2232LT1	A8J	4.7	4.7	SOT-23	
MMUN2232LT1G		4.7	4.7	SOT-23 (Pb-Free)	
MMUN2233LT1	A8K	4.7	47	SOT-23	
MMUN2233LT1G		4.7	47	SOT-23 (Pb-Free)	
MMUN2234LT1	A8L	22	47	SOT-23	
MMUN2234LT1G		22	47	SOT-23 (Pb-Free)	
MMUN2234LT3		22	47	SOT-23	10,000 / Tape & Reel
MMUN2234LT3G		22	47	SOT-23 (Pb-Free)	
MMUN2238LT1	A8R	2.2	∞	SOT-23	3000 / Tape & Reel
MMUN2238LT1G		2.2	∞	SOT-23 (Pb-Free)	
MMUN2241LT1	A8U	100	∞	SOT-23	
MMUN2241LT1G		100	∞	SOT-23 (Pb-Free)	

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

MMUN2211LT1 Series

PACKAGE DIMENSIONS

SOT-23 (TO-236) CASE 318-08 ISSUE AN



NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. 318-01 THRU -07 AND -09 OBSOLETE, NEW STANDARD 318-08.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1.00	1.11	0.035	0.040	0.044
A1	0.01	0.06	0.10	0.001	0.002	0.004
b	0.37	0.44	0.50	0.015	0.018	0.020
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.90	3.04	0.110	0.114	0.120
E	1.20	1.30	1.40	0.047	0.051	0.055
e	1.78	1.90	2.04	0.070	0.075	0.081
L	0.10	0.20	0.30	0.004	0.008	0.012
L1	0.35	0.54	0.69	0.014	0.021	0.029
HE	2.10	2.40	2.64	0.083	0.094	0.104

STYLE 6:

1. BASE
2. EMITTER
3. COLLECTOR

SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

MMUN2211LT1/D