



ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
<b>INPUT</b>				
Reverse voltage		$V_R$	6	V
DC forward current		$I_F$	60	mA
Surge forward current	$t = 10\text{ }\mu\text{s}$	$I_{FSM}$	2.5	A
Total power dissipation		$P_{diss}$	100	mW
<b>OUTPUT</b>				
Collector emitter voltage		$V_{CEO}$	100	V
Emitter base voltage		$V_{EBO}$	7	V
Collector current		$I_C$	50	mA
	$t = 1.0\text{ ms}$	$I_C$	100	mA
Power dissipation		$P_{diss}$	150	mW
<b>COUPLER</b>				
Storage temperature range		$T_{stg}$	-55 to +150	$^{\circ}\text{C}$
Ambient temperature range		$T_{amb}$	-55 to +100	$^{\circ}\text{C}$
Junction temperature		$T_j$	100	$^{\circ}\text{C}$
Soldering temperature <sup>(1)</sup>	Max. 10 s, dip soldering: distance to seating plane $\geq 1.5\text{ mm}$	$T_{sld}$	260	$^{\circ}\text{C}$

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.
- <sup>(1)</sup> Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

ELECTRICAL CHARACTERISTICS (T <sub>amb</sub> = 25 °C, unless otherwise specified)							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
INPUT							
Forward voltage	I <sub>F</sub> = 60 mA		V <sub>F</sub>	-	1.25	1.65	V
Breakdown voltage	I <sub>R</sub> = 10 μA		V <sub>BR</sub>	6	-	-	V
Reverse current	V <sub>R</sub> = 6 V		I <sub>R</sub>	-	0.01	10	μA
Capacitance	V <sub>F</sub> = 0 V, f = 1 MHz		C <sub>O</sub>	-	25	-	pF
Thermal resistance			R <sub>thja</sub>	-	750	-	K/W
OUTPUT							
Collector emitter capacitance	f = 1 MHz, V <sub>CE</sub> = 5 V		C <sub>CE</sub>	-	6.8	-	pF
Collector base capacitance	f = 1 MHz, V <sub>CB</sub> = 5 V		C <sub>CB</sub>	-	8.5	-	pF
Emitter base capacitance	f = 1 MHz, V <sub>EB</sub> = 5 V		C <sub>EB</sub>	-	11	-	pF
Thermal resistance			R <sub>thja</sub>	-	500	-	K/W
Collector emitter leakage current	V <sub>CE</sub> =10 V	SFH601-1	I <sub>CEO</sub>	-	2	50	nA
		SFH601-2	I <sub>CEO</sub>	-	2	50	nA
		SFH601-3	I <sub>CEO</sub>	-	5	100	nA
		SFH601-4	I <sub>CEO</sub>	-	5	100	nA
COUPLER							
Saturation voltage collector emitter	I <sub>F</sub> = 10 mA, I <sub>C</sub> = 2.5 mA		V <sub>CEsat</sub>	-	0.25	0.4	V
Capacitance (input to output)	V <sub>I-O</sub> = 0, f = 1 MHz		C <sub>IO</sub>	-	0.6	-	pF

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

CURRENT TRANSFER RATIO							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
$I_C/I_F$ at $V_{CE} = 5.0\text{ V}$	$I_F = 10\text{ mA}$	SFH601-1	CTR	40	-	80	%
		SFH601-2	CTR	63	-	125	%
		SFH601-3	CTR	100	-	200	%
		SFH601-4	CTR	160	-	320	%
	$I_F = 1\text{ mA}$	SFH601-1	CTR	13	30	-	%
		SFH601-2	CTR	22	45	-	%
		SFH601-3	CTR	34	70	-	%
		SFH601-4	CTR	56	90	-	%

**Note**

- Current transfer ratio and collector emitter leakage current by dash number.

SWITCHING CHARACTERISTICS							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
NON-SATURATED							
Current	$V_{CC} = 5\text{ V}$ , $R_L = 75\ \Omega$		$I_F$	-	10	-	mA
Rise time	$V_{CC} = 5\text{ V}$ , $R_L = 75\ \Omega$		$t_r$	-	2	-	$\mu\text{s}$
Fall time	$V_{CC} = 5\text{ V}$ , $R_L = 75\ \Omega$		$t_f$	-	2	-	$\mu\text{s}$
Turn-on time	$V_{CC} = 5\text{ V}$ , $R_L = 75\ \Omega$		$t_{on}$	-	3	-	$\mu\text{s}$
Turn-off time	$V_{CC} = 5\text{ V}$ , $R_L = 75\ \Omega$		$t_{off}$	-	2.3	-	$\mu\text{s}$
SATURATED							
Current		SFH601-1	$I_F$	-	20	-	mA
		SFH601-2	$I_F$	-	10	-	mA
		SFH601-3	$I_F$	-	10	-	mA
		SFH601-4	$I_F$	-	0.5	-	mA
Rise time		SFH601-1	$t_r$	-	2	-	$\mu\text{s}$
		SFH601-2	$t_r$	-	3	-	$\mu\text{s}$
		SFH601-3	$t_r$	-	3	-	$\mu\text{s}$
		SFH601-4	$t_r$	-	4.6	-	$\mu\text{s}$
Fall time		SFH601-1	$t_f$	-	11	-	$\mu\text{s}$
		SFH601-2	$t_f$	-	14	-	$\mu\text{s}$
		SFH601-3	$t_f$	-	14	-	$\mu\text{s}$
		SFH601-4	$t_f$	-	15	-	$\mu\text{s}$
Turn-on time		SFH601-1	$t_{on}$	-	3	-	$\mu\text{s}$
		SFH601-2	$t_{on}$	-	4.2	-	$\mu\text{s}$
		SFH601-3	$t_{on}$	-	4.2	-	$\mu\text{s}$
		SFH601-4	$t_{on}$	-	6	-	$\mu\text{s}$
Turn-off time		SFH601-1	$t_{off}$	-	18	-	$\mu\text{s}$
		SFH601-2	$t_{off}$	-	23	-	$\mu\text{s}$
		SFH601-3	$t_{off}$	-	23	-	$\mu\text{s}$
		SFH601-4	$t_{off}$	-	25	-	$\mu\text{s}$




Fig. 1 - Linear Operation (without Saturation)




Fig. 2 - Switching Operation (with Saturation)

SAFETY AND INSULATION RATINGS				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Climatic classification	According to IEC 68 part 1		55 / 100 / 21	
Comparative tracking index		CTI	175	
Maximum rated withstanding isolation voltage	$t = 1 \text{ min}$	$V_{\text{ISO}}$	4420	$V_{\text{RMS}}$
Maximum transient isolation voltage		$V_{\text{IOTM}}$	8000	V
Maximum repetitive peak isolation voltage		$V_{\text{IORM}}$	890	V
Isolation resistance	$V_{\text{IO}} = 500 \text{ V}, T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$	$R_{\text{IO}}$	$\geq 10^{12}$	$\Omega$
	$V_{\text{IO}} = 500 \text{ V}, T_{\text{amb}} = 100 \text{ }^{\circ}\text{C}$	$R_{\text{IO}}$	$\geq 10^{11}$	$\Omega$
Output safety power		$P_{\text{SO}}$	700	mW
Input safety current		$I_{\text{SI}}$	400	mA
Input safety temperature		$T_{\text{SI}}$	175	$^{\circ}\text{C}$
Creepage distance	Standard DIP-4		$\geq 7$	mm
Clearance distance	Standard DIP-4		$\geq 7$	mm
Creepage distance	400 mil DIP-4		$\geq 8$	mm
Clearance distance	400 mil DIP-4		$\geq 8$	mm
Insulation thickness		DTI	$\geq 0.4$	mm

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.


**TYPICAL CHARACTERISTICS** ( $T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 3 - Current Transfer Ratio vs. Diode Current




Fig. 4 - Current Transfer Ratio vs. Diode Current




Fig. 5 - Current Transfer Ratio vs. Diode Current




Fig. 8 - Current Transfer Ratio vs. Diode Current




Fig. 6 - Current Transfer Ratio vs. Diode Current




Fig. 9 - Transistor Characteristics




Fig. 7 - Current Transfer Ratio vs. Diode Current




Fig. 10 - Output Characteristics




Fig. 11 - Forward Voltage




Fig. 14 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-2




Fig. 12 - Collector Emitter Off-state Current




Fig. 15 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-3




Fig. 13 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-1




Fig. 16 - Saturation Voltage vs. Collector Current and Modulation Depth SFH601-4




Fig. 17 - Permissible Pulse Load




Fig. 18 - Permissible Power Dissipation for Transistor and Diode






Fig. 19 - Permissible Forward Current Diode

**PACKAGE DIMENSIONS** in inches (millimeters)


18450-16

# DIP-6A

## PACKAGE DIMENSIONS in inches (millimeters)



### Note

The information in this document provides generic information but for specific information on a product the appropriate product datasheet should be used.





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.