

Absolute Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V _{CBO}	-25	V
Collector-Emitter Voltage (Forward Blocking)	V _{CEO}	-20	V
Emitter-collector voltage (Reverse Blocking)	V _{ECO}	-7	V
Emitter-Base Voltage	V _{EBO}	-7	V
Continuous Collector Current (Note 5)	I _C	-4	A
Base Current	I _B	-1	A
Peak Pulse Current	I _{CM}	-10	A

Thermal Characteristics

Characteristic		Symbol	Value	Unit
Power Dissipation Linear derating factor	(Note 5)	P _D	0.73	W
	(Note 6)		5.84	
	(Note 7)		1.05	
	(Note 8)		8.4	
	(Note 9)		1.25	
Thermal Resistance, Junction to Ambient	(Note 5)	R _{θJA}	9.6	°C/W
	(Note 6)		1.81	
	(Note 7)		14.5	
	(Note 8)		171	
Thermal Resistance, Junction to Lead	(Note 9)	R _{θJL}	119	°C/W
Operating and Storage Temperature Range	—	T _J , T _{STG}	100	°C
			69	
			74.95	
			-55 to +150	





- Notes:
- For a device surface mounted on 15mm x 15mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
 - Same as note (5), except the device is surface mounted on 25mm x 25mm with 2 oz copper.
 - Same as note (5), except the device is surface mounted on 50mm x 50mm with 2 oz copper.
 - Same as note (7), except the device is measured at t<5secs.
 - Thermal resistance from junction to solder-point (at the end of the collector lead).

ESD Ratings (Note 10)

Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge - Human Body Model	ESD HBM	4,000	V	3A
Electrostatic Discharge - Machine Model	ESD MM	400	V	C

- Note: 10. Refer to JEDEC specification JESD22-A114 and JESD22-A115.

Thermal Characteristics and Derating Information








Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Collector-Base Breakdown Voltage	BV _{CBO}	-25	-50	—	V	I _C = -100μA
Collector-Emitter Breakdown Voltage (Note 11)	BV _{CEO}	-20	-35	—	V	I _C = -10mA
Emitter-Base Breakdown Voltage	BV _{EBO}	-7	-8.2	—	V	I _E = -100μA
Emitter-Base Breakdown Voltage	BV _{ECO}	-7	-8.8	—	V	I _E = -100μA
Collector-Base Cutoff Current	I _{CBO}	—	< -1	-50	nA	V _{CB} = -20V
		—	—	-20	μA	V _{CB} = -20V, T _{amb} = +100°C
Emitter-Base Cutoff Current	I _{EBO}	—	< -1	-50	nA	V _{EB} = -5.6V
Static Forward Current Transfer Ratio (Note 11)	h _{FE}	200	350	500	—	I _C = -10mA, V _{CE} = -2V
		—	250	—		I _C = -1A, V _{CE} = -2V
		—	140	—		I _C = -4A, V _{CE} = -2V
		—	40	—		I _C = -10A, V _{CE} = -2V
Collector-Emitter Saturation Voltage (Note 11)	V _{CE(sat)}	—	-43	-55	mV	I _C = -1A, I _B = -100mA
		—	-70	-100		I _C = -1A, I _B = -20mA
		—	-120	-170		I _C = -2A, I _B = -40mA
		—	-150	-210		I _C = -4A, I _B = -200mA
Base-Emitter Saturation Voltage (Note 11)	V _{BE(sat)}	—	-930	-1050	mV	I _C = -4A, I _B = -200mA
Base-Emitter Saturation Voltage (Note 11)	V _{BE(on)}	—	-810	-900	mV	I _C = -4A, V _{CE} = -2V
Output Capacitance	C _{obo}	—	32.4	40	pF	V _{CB} = -10V, f = 1MHz
Transition Frequency	f _T	—	285	—	MHz	V _{CE} = -10V, I _C = -50mA, f = 100MHz
Delay Time	t _(d)	—	38.4	—	nS	V _{CC} = -15V, I _C = -750mA, I _{B1} = -I _{B2} = -15mA
Rise Time	t _(r)	—	49.2	—	nS	
Storage Time	t _(s)	—	168	—	nS	
Fall Time	t _(f)	—	55	—	nS	

Note: 11. Measured under pulsed conditions. Pulse width ≤ 300 μs. Duty cycle ≤ 2%.


Typical Electrical Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)



Package Outline Dimensions

Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for the latest version.

SOT23




SOT23			
Dim	Min	Max	Typ
A	0.37	0.51	0.40
B	1.20	1.40	1.30
C	2.30	2.50	2.40
D	0.89	1.03	0.915
F	0.45	0.60	0.535
G	1.78	2.05	1.83
H	2.80	3.00	2.90
J	0.013	0.10	0.05
K	0.890	1.00	0.975
K1	0.903	1.10	1.025
L	0.45	0.61	0.55
L1	0.25	0.55	0.40
M	0.085	0.150	0.110
a	8°		
All Dimensions in mm			

Suggested Pad Layout

Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.

SOT23



Dimensions	Value (in mm)
Z	2.9
X	0.8
Y	0.9
C	2.0
E	1.35

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2015, Diodes Incorporated

www.diodes.com