

FUNCTIONAL DESCRIPTION

RECEIVER

Figure 1 shows the general architecture of the ARINC 429 receiver. The receiver operates off the VCC supply only. The inputs RINA and RINB each have series resistors, typically 35K ohms. They connect to level translators whose resistance to Ground is typically 10K ohms. Therefore, any series resistance added to the inputs will affect the voltage translation.

After level translation, the inputs are buffered and become inputs to a differential amplifier. The amplitude of the differential signal is compared to levels derived from a divider between VCC and Ground. The nominal settings correspond to a One/Zero amplitude of 6.0V and a Null amplitude of 3.3V.

The status of the ARINC receiver input is latched. A Null input resets the latches and a One or Zero input sets the latches.

The logic at the output is controlled by the test signal which is generated by the logical OR of the TESTA and TESTB pins. If TESTA and TESTB are both One, then the receiver is powered down and the output pins float. The powerdown does not disconnect the internal resistors at the ARINC input.




FIGURE 1 - RECEIVER BLOCK DIAGRAM

APPLICATION INFORMATION

Figure 2 shows a possible application of the HI-8588 interfacing an ARINC receive channel to the HI-6010 which in turn interfaces to an 8-bit bus.




FIGURE 2 - APPLICATION DIAGRAM

ABSOLUTE MAXIMUM RATINGS

Voltages referenced to Ground

Supply voltages VCC.....7V
ARINC input - pins 3 & 4 Voltage at either pin.....+120V to -120V
DC current per input pin..... $\pm 10\text{mA}$
Power dissipation at 25°C plastic DIP.....0.7W ceramic DIP.....0.5W
Solder Temperature (reflow)260°C
Storage Temperature -65°C to +150°C

RECOMMENDED OPERATING CONDITIONS

Supply Voltages VCC.....5V $\pm 5\%$
Temperature Range Industrial Screening.....-40°C to +85°C Hi-Temp Screening.....-55°C to +125°C

NOTE: Stresses above absolute maximum ratings or outside recommended operating conditions may cause permanent damage to the device. These are stress ratings only. Operation at the limits is not recommended.

DC ELECTRICAL CHARACTERISTICS


OPERATING TEMPERATURE RANGE, VCC = 5.0V UNLESS OTHERWISE STATED

PARAMETERS	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
ARINC input voltage one or zero null common mode	V_{DIN} V_{NIN} V_{COM}	differential voltage, pins 3 & 4 " " " with respect to Ground	6.5 - -	10 - -	13 2.5 5.0	volts volts volts
logic input voltage high low	V_{IH} V_{IL}		3.5 -	- -	- 1.5	volts volts
ARINC input resistance RINA to RINB RINA or RINB to Gnd or VCC	R_{DIFF} R_{SUP}	supplies floating " "	30 19	75 40	- -	Kohm Kohm
logic input current source sink	I_{IH} I_{IL}	$V_{IN} = 0\text{V}$ $V_{IN} = 5\text{V}$	- -	- -	0.1 0.1	μA μA
logic output drive current one zero	I_{OH} I_{OL}	$V_{OH} = 4.6\text{V}$ $V_{OL} = 0.4\text{V}$	- 3.6	-1.6 5.6	-0.8 -	mA mA
Current drain operating powerdown	I_{CC1} I_{CC2}	pins 2, 8 = 0V; pins 3, 4 open pins 2, 8 = 5V; pins 3, 4 open	- -	2.3 0.36	6.3 0.6	mA mA

AC ELECTRICAL CHARACTERISTICSOPERATING TEMPERATURE RANGE, $V_{CC} = 5.0V$ UNLESS OTHERWISE STATED

PARAMETERS	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Receiver propagation delay		defined in Figure 3, $C_L = 50pF$				
Output high to low	t_{phlr}		-	600	-	ns
Output low to high	t_{plhr}		-	600	-	ns
Receiver output transition times						
Output high to low	t_{fr}		-	50	80	ns
Output low to high	t_{rr}		-	50	80	ns
Input capacitance (1)						
ARINC differential	C_{AD}		-	5	10	pF
ARINC single ended to Ground	C_{AS}		-	-	10	pF
Logic	C_{IN}		-	-	10	pF

Notes: 1. Guaranteed but not tested

**ORDERING INFORMATION**HI - 8588 xx x x

PART NUMBER	LEAD FINISH
Blank	Tin / Lead (Sn / Pb) Solder
F	100% Matte Tin (Pb-free, RoHS compliant)

PART NUMBER	TEMPERATURE RANGE	FLOW	BURN IN
I	-40°C TO +85°C	I	No
T	-55°C TO +125°C	T	No
M	-55°C TO +125°C	M	Yes

PART NUMBER	PACKAGE DESCRIPTION
PD	8 PIN PLASTIC DIP (8P) not available with "M" flow
PS	8 PIN PLASTIC NARROW BODY SOIC (8HN)
CR	8 PIN Cerdip (8D) not available Pb-free


REVISION HISTORY

P/N	Rev	Date	Description of Change
DS8488	E	08/05/14	Update ARINC input pins 3 & 4 Absolute Maximum Rating to +/-120V. Update solder reflow temperature. Remove Mil. temperature rating. Update SOIC-8 (8HN) package drawing.

8-PIN PLASTIC DIP

inches (millimeters)

Package Type: 8P




BSC = "Basic Spacing between Centers" is theoretical true position dimension and has no tolerance. (JEDEC Standard 95)

8-PIN PLASTIC SMALL OUTLINE (SOIC) - NB (Narrow Body)

millimeters (inches)

Package Type: 8HN




BSC = "Basic Spacing between Centers" is theoretical true position dimension and has no tolerance. (JEDEC Standard 95)

8-PIN CERDIP

inches (millimeters)

Package Type: 8D



BSC = "Basic Spacing between Centers"
is theoretical true position dimension and
has no tolerance. (JEDEC Standard 95)