

Customer Information Sheet


DRAWING No. : M50-350XX42		IF IN DOUBT - ASK	(C)	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm
---------------------------	--	-------------------	-----	--------------	------------------------	----------------------

NOTES:

1. ALL TOLERANCES ARE ± 0.20 UNLESS OTHERWISE STATED.

2. RECOMMENDED PCB HOLE SIZE = $\varnothing 0.70 \pm 0.05\text{mm}$.

1.27 x No. OF CONTACTS
PER ROW ± 0.30



1.27 ± 0.10

3.00


1.00 ± 0.15

1.27 ± 0.10 TYP

0.40 SQUARE TYP

6.30

(2.30)



ORDER CODE:

M50-350XX42

No. OF CONTACTS PER ROW
02 TO 50

FINISH:
42 = SELECTIVE GOLD + 100% TIN

MGPISSDATECN/CO

NAMEISSDATECN/CO

APPROVED: MGP

CHECKED: RA

DRAWN: W. J. BOURNE

CUSTOMER REF.:

ASSEMBLY DRG:

SPECIFICATION:

MATERIAL:

MOULDING = HIGH TEMP THERMOPLASTIC UL94V-0, BLACK

CONTACT = HIGH STRENGTH COPPER ALLOY

FINISH (CONTACT):

42 = 0.70 - 1.30 μm NICKEL ALL OVER,
0.15 - 0.08 μm GOLD ON CONTACT AREA,
2.50 - 3.00 μm 100% TIN ON TAILS.

ELECTRICAL:

CURRENT RATING = 1A MAX

CONTACT RESISTANCE = 20m Ω MAX

INSULATION RESISTANCE = 1,000 M Ω MIN

DIELECTRIC STRENGTH = 500V ACrms/DC FOR ONE MINUTE

MECHANICAL:

DURABILITY = 300 OPERATIONS

ENVIRONMENTAL:

TEMPERATURE RANGE = -40°C TO +105°C

FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C029XX (LATEST ISSUE)

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.		TOLERANCES X.X = $\pm 1\text{mm}$ X.XX = $\pm 0.50\text{mm}$ X.XXX = $\pm 0.20\text{mm}$ X.XXX = $\pm 0.01\text{mm}$ ANGLES = $\pm 5^\circ$ UNLESS STATED		MATERIAL: SEE ABOVE		TITLE: 1.27mm PITCH DIL VERTICAL PIN HEADER		SHT 2 OF 2	
FINISH: SEE ABOVE		S/AREA: mm ²		DRAWING NUMBER: M50-350XX42					