¥

PIN PLATING CODES:												
XXXXX-1YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-2YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-3YY	50u"/1.27u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-4YY	100u"/2.54u MIN Sn OVER 50u"/1.27u MIN Ni (SEE NOTE 15)											
XXXXX-4YYHLF	1000 / 2.010 WIN ON OVER OUD / 1.270 WIN IN (SEE NOTE 10)											
XXXXX-5YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-6YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-7YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-8YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-9YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											
XXXXX-0YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni											

NOTES

1. PART NUMBER OPTIONS:

PIN PLATING CODES (SEE ABOVE)

HIGH TEMPERATURE MATERIAL:

PART NUMBERS WITH AND WITHOUT "H" WILL BE SUPPLIED WITH HIGH TEMPERATURE PLASTIC.

NUMBER OF POSITIONS:

EVEN NUMBER OF POSITIONS FROM 2 (2X1) THROUGH 72 (2X36). -X00H INDICATES BERGSTRIP PRODUCT. SEE PAGE 3 FOR SPECIAL GEOMETRY OF THIS CONTINUOUS STRIP PRODUCT. AUTOMATED REELS WILL CONTAIN 45,000 PINS. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

PACKAGING:

PACKAGED IN POLY BAGS.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "T" ARE PACKAGED IN TUBES. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "G" ARE PACKAGED IN GPAX FOR IBM ONLY. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

PART NUMBERS FOLLOWED BY A "C" ARE PACKAGED IN TUBES WITH A PICKUP CAP APPLIED.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "A" ARE PACKAGED IN TAPE/REEL WITH PICKUP CAP P/N 95730-003 APPLIED.

LEAD FREE:

ADD "HLF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION, NOT AVAILABLE FOR -5YY, -5YYH, -6YY & -6YYH

HALOGEN FREE:

ADD "HF" SUFFIX AT THE END OF PART NUMBER FOR HOLOGEN FREE OPTION

2. BODY MATERIAL:

BODY MATERIAL: MANUFACTURER'S OPTION OF NYLON, PCT GLASS FIBER REINFORCED OR MINERAL FILLED LCP FLAME RETARDENT PER UL-94V-0. COLOR: BLACK

BERGSTRIP™PRODUCED WITH HIGH TEMPERATURE LCP THERMOPLASTIC, FLAME RETARDENT PER UL-94V-O. COLOR: BLACK

1

PART NUMBERS WITH "H" AND WITHOUT SUFFIX WILL WITHSTAND EXPOSURE TO 260° C PEAK TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS.

- 3. PIN MATERIAL: PHOS BRONZE.
- 4. MEASURED WITH PART IN RESTRAINED CONDITION.
- 5. TWO SIDES OF PIN TIPS NOT PLATED. TYPICAL BOTH ENDS
- 6. 2LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION.
- 7. MILITARY BERGSTIK HEADER P/N XXXXX-XYY-MIL NOT AVAILABLE.
- 8. ±.010/0.25 TOL APPLIES TO ALL "G" TAILS EXCEPT INDICATED PARTS ON TABLE WHERE +.010/0.25 -.000/0.00 APPLIES.
- 9. NOTCH CONFIGURATION WILL VARY PER VENDOR'S DISCRETION.
- 10. BERGSTRIP™ PART NUMBERS FOLLOWED BY BY A "B" ARE BULK PRICED.
- 11. TAIL LENGTH (DIM. G) TO BE ±.008/.0.20.
- 12. POSITIONS PER ROW 37 TO 50 CAN BE PRODUCED, BUT FLATNESS AND CURVATURE MAY NOT BE HELD AS CLOSE AS 36 POSITIONS.
- 13. THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- 14. PLATING OPTIONS:

 PERFORMANCE PLATING WILL BE EITHER GOLD OR GXT ON POST OR TAIL,

 OPTIONALLY (78~295u"/2~7.5u) TIN ON TAIL.
- 15. "THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVIRONMENTS."
- 16. THE OAL DON'T EXCEED 34.5mm
- 17. INCREMENTS BY 0.1mm IN LENGTHS ONLY
- 18. FOR SPECIAL PACKAGING REQUEST PLEASE CONTACT PRODUCT MANAGER FOR AVAILABILITY
- 19. TO DETERMINE DIMENSIONS:

 N=NUMBER OF POSITION PER ROW
 EXAMPLE: 10 POS. N X .100/2.54
- 20. PART NUMBERS 68602 OR 67996 FOLLOWED BY A "D" ARE PACKAGED IN TAPE/REEL WITHOUT PICKUP CAP.

		4 F	DS	: Rev	/ :DI	K			STA	TUS	:Re	eas	ed		Prir	nted	: No	ov 10	6, 20	20				
ind	index		et	1-8																				D
she	sheet revision DK		sion	DK																				
						appd	T.	T.HANNA		07/21/99					typ:	e I	Prod	uct	Cus	tom	er [Draw	ing	ĺ
						chr	J.1	J.MURPHY		ER 12/21/94 07/21/99 07/21/99		Amphenol FCi										ĺ		
					en		T.	ИАН.	IA						67996 A					Аз				
					dr	T.BF							dwg	, no			S	heet	2 c	of 8	size	ŀ		
						0°±2	=2°		.xxxx±0.0020/.xxx±0.051			sca	le 2	: 1		.10	0/2	54	FCC STRAIGHT					ĺ
						ungi	اا 🛅	linear	.XXX±0.005/.XX±0.13						.100/2.54cc STRAIGHT								ĺ	
DK	DK			angles		.XX±0.01/0.3			ling	CH/N	им	BERGSTIK II HEADER D/F						Ŕ	ĺ					
ltr	ecr	n no	dr	dat	е	tolera	nces i	unless	otherw	ise sp	ecified	7	クト	7	title	9								ĺ
SEE NOTES 1 & 2				2	ISO 1302 √ IS				ISO 406 ISO 1101			\(\)		BERGSTIK								ĺ		
mat'l. code					surface / tol				rand	ce	projection			product family							ĺ			

Downloaded from Arrow.com.

2











