


## Pin Descriptions

| Pin Number | Pin Name |         | Function                                |
|------------|----------|---------|---|
|            | AM4406   | AM4406F |   |
| 1          | VCC      | VCC     | Power supply                            |
| 2          | HS (+)   | HS (+)  | Hall input (+)                          |
| 3          | RD       | FG      | Rotation detection/Frequency generation |
| 4          | HS (-)   | HS (-)  | Hall input (-)                          |
| 5          | GND      | GND     | Ground                                  |
| 6          | CT       | CT      | Timing capacitor                        |
| 7          | OUT2     | OUT2    | Driver output 2                         |
| 8          | OUT1     | OUT1    | Driver output 1                         |

## Functional Block Diagram



## Absolute Maximum Ratings (Note 2)

| Symbol           | Parameter                 | Value        | Unit |
|------------------|---------------------------|--------------|------|
| V <sub>CC</sub>  | Supply Voltage            | 30           | V    |
| I <sub>OUT</sub> | Output Current            | 70           | mA   |
| P <sub>D</sub>   | Power Dissipation         | 550 (Note 3) | mW   |
| T <sub>STG</sub> | Storage Temperature Range | -55 to +125  | °C   |
| ESD              | ESD (Human Body Model)    | 3000         | V    |
| ESD              | ESD (Machine Model)       | 300          | V    |

Note 2: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

Note 3: Reduced by 5.5mW/°C when T<sub>A</sub> is over +25°C.

## Recommended Operating Conditions

| Symbol              | Parameter                       | Min | Max                  | Unit |
|---------------------|---------------------------------|-----|----------------------|------|
| V <sub>CC</sub>     | Supply Voltage                  | 4   | 28                   | V    |
| V <sub>HS</sub> (+) | Hall Input Voltage (+) (Note 4) | 1.0 | V <sub>CC</sub> -0.5 | V    |
| V <sub>HS</sub> (-) | Hall Input Voltage (-) (Note 4) | 1.0 | V <sub>CC</sub> -0.5 | V    |
| T <sub>A</sub>      | Operating Temperature           | -40 | +95                  | °C   |


Note 4: Hall input voltage range includes the amplitude of signal.

**Electrical Characteristics** ( $V_{CC}=12V$ ,  $T_A=+25^{\circ}C$ , unless otherwise specified.)


| Symbol        | Parameter                           | Conditions                                   | Min  | Typ  | Max  | Unit    |
|---------------|-------------------------------------|--|------|------|------|---------|
| $I_{CC}$      | Supply Current                      | No load                                      | —    | 3.2  | 5.0  | mA      |
| $V_{HYS (+)}$ | Hall Amplifier Input Hysteresis (+) | Zero to peak including offset and hysteresis | 3    | —    | 15   | mV      |
| $V_{HYS (-)}$ | Hall Amplifier Input Hysteresis (-) | Zero to peak including offset and hysteresis | -3   | —    | -15  | mV      |
| $I_{CHG}$     | CT Charge Current                   | $V_{CT}=1.5V$                                | 2    | 3.45 | 5.25 | $\mu A$ |
| $I_{DHG}$     | CT Discharge Current                | $V_{CT}=1.5V$                                | 0.35 | 0.8  | 1.45 | $\mu A$ |
| $R_{CD}$      | CT Charge and Discharge Ratio       | $I_{CHG}/I_{DHG}$                            | 3    | 4.5  | 8    | —       |
| $V_{CL}$      | CT Clamp Voltage                    | —  | 2.2  | 2.6  | 3    | V       |
| $V_{CP}$      | CT Comparator Voltage               | —  | 0.4  | 0.6  | 0.8  | V       |
| $V_{OH1}$     | OUT1 High Level Voltage             | $I_{OUT1}=10mA$                              | 10   | 10.5 | —    | V       |
| $V_{OH2}$     | OUT2 High Level Voltage             | $I_{OUT2}=10mA$                              | 10   | 10.5 | —    | V       |
| $V_{RDL}$     | RD Output Low Level Voltage         | $I_{RD}=5mA$                                 | —    | 0.2  | 0.5  | V       |
| $I_{RD}$      | RD Current Capacity                 | $V_{RD}=2V$                                  | 8    | 18   | —    | mA      |
| $V_{FGL}$     | FG Output Low Level Voltage         | $I_{FG}=5mA$                                 | —    | 0.2  | 0.5  | V       |
| $I_{FG}$      | FG Current Capacity                 | $V_{FG}=2V$                                  | 8    | 18   | —    | mA      |

## Performance Characteristics


Supply Current vs. Supply Voltage




Output Voltage vs. Output Current




RD/FG Current vs. RD/FG Supply Voltage




RD/FG Low Voltage vs. RD/FG Current



Power Dissipation vs. Ambient Temperature



## Operating Diagram




Note 5: Automatic restart is performed in the following manner. A motor lock condition is detected when the Hall signal stops switching. The output is ON when CT pin is being charged. C2 is the external capacitor of the CT pin. Output ON time and OFF time are determined by the capacitance of C2.

Note 6: RD pin is ON during normal operation, and OFF when the motor is locked. It is an open collector output pin.


$$T_{ON} = \frac{C2 * (V_{CL} - V_{CP})}{I_{CHG}} (Sec.)$$

$$T_{OFF} = \frac{C2 * (V_{CL} - V_{CP})}{I_{DHG}} (Sec.)$$

Note 7: The RD pin may maintain HIGH level for a few hundred milliseconds when the power is turned on.




## Ordering Information



| Package | Temperature Range | Part Number    |                          | Marking ID     |                          | Packing     |
|---------|-------------------|----------------|--------------------------|----------------|--------------------------|-------------|
|         |                   | RoHS Compliant | RoHS Compliant and Green | RoHS Compliant | RoHS Compliant and Green |             |
| SOIC-8  | -40 to +95°C      | AM4406M-E1     | AM4406M-G1               | AM4406M        | AM4406M-G1               | Tube        |
|         |                   | AM4406MTR-E1   | AM4406MTR-G1             | AM4406M        | AM4406M-G1               | Tape & Reel |
|         |                   | —              | AM4406FMTR-G1            | —              | AM4406FM-G1              | Tape & Reel |

**Package Outline Dimensions** (All dimensions in mm(inch).)

**(1) Package Type: SOIC-8**


Note: Eject hole, oriented hole and mold mark is optional.

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2018, Diodes Incorporated

**[www.diodes.com](http://www.diodes.com)**