


Circuits



Environmental Data

Test	Condition	$\Delta R\%$ (+0.1 Ω)	
		$\pm 200\text{ppm}/^{\circ}\text{C}$ TCR	$\pm 100\text{ppm}/^{\circ}\text{C}$ TCR
Load life	1000 hrs cyclic load @ 70 $^{\circ}\text{C}$	3	1
Short term overload	2.5 x rated voltage for 5s	2	0.25
High temperature operation	1000 hrs @ 155 $^{\circ}\text{C}$	3	1
Temperature cycling	5 cycles, -55 to +155 $^{\circ}\text{C}$	1	1
Moisture resistance	1000 hrs @ 40 $^{\circ}\text{C}$, 95% RH	3	1
Resistance to solder heat	260 $^{\circ}\text{C}$ for 10s	1	0.25
Sulphur resistance ¹	1000 hrs @ 50 $^{\circ}\text{C}$, 92% RH, 3-5ppm H ₂ S	0.5	0.5


Note 1 – Anti-sulphur construction only

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BI Technologies IRC Welwyn

www.ttelectronics.com/resistors


Physical Data (Inch /mm)




General Note



TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Physical Data (Inch /mm)

Exterior Termination (Convex) Square Edge: Models BCN 16 8R, 8S 							
L	W	T	A	B1	B2	C	P
.126 ±.008	.063 ±.008	.020 ±.004	.012 ±.006	.014 ±.006	.020 ±.006	.008	.025
3.20 ±0.20	1.60 ±0.20	0.50 ±0.10	0.30 ±0.15	0.36 ±0.15	0.50 ±0.15	0.20	0.64

Interior Termination (Concave) Square Edge: Models BCN 21 						
L	W	T	A	B	C	D
.157 ±.008	.083 ±.008	.021 ±.004	.020 ±.008	.010 ±.008	.020 ±.008	.012 ±.008
4.00 ±0.20	2.10 ±0.20	0.55 ±0.10	0.50 ±0.20	0.25 ±0.20	0.50 ±0.20	0.30 ±0.20
A1	B1	C1	D1	E	P	
.016 ±.008	.014 ±.008	.020 ±.008	.014 ±.008	.012	.032	
0.40 ±0.20	0.40 ±0.20	0.50 ±0.20	0.35 ±0.20	0.30 Typ.	0.80 Typ.	

Solder pad layout (Inch / mm)



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Solder pad layout (Inch / mm)

BCN 10

The diagram illustrates the BCN 10 layout, which consists of two rows of four rectangular pads each. The top row is labeled 'A' on the left and 'B' on the right. The bottom row is labeled 'X' and 'X1' below the pads. Dimensions are indicated by arrows: 'L' is the total length of the top row; 'P' is the pitch between the first two pads; 'P1' is the pitch between the second and third pads; 'A' is the height of the top row; 'B' is the height of the bottom row; 'X' is the width of the bottom row; 'X1' is the width of the bottom row; 'Y' is the height of the top row; and 'B' is the total width of the top row.

BCN 10

P	P1	A	B	X	X1	Y	L
.024	.020	.020 ±.004	.060 ±.004	010 ±.004	.018 ±.004	.020 ±.004	.085 ±.004
0.60	0.50	0.50 ±0.10	1.50 ±0.10	0.25 ±0.15	0.45 ±0.10	0.50 ±0.10	2.15 ±0.10

BCN 21


The diagram illustrates the BCN 21 layout, which consists of two rows of four rectangular pads each. The top row is labeled 'A' on the left and 'B' on the right. The bottom row is labeled 'X' and 'Y' below the pads. Dimensions are indicated by arrows: 'L' is the total length of the top row; 'A' is the height of the top row; 'B' is the height of the bottom row; 'C' is the height of the top row; 'X' is the width of the bottom row; 'Y' is the width of the bottom row; 'W' is the width of the bottom row; 'W1' is the width of the bottom row; 'W2' is the width of the bottom row; 'W3' is the width of the bottom row; and 'L' is the total length of the top row.

BCN 21

P	A	B	C	X	Y	W	W1	W2	W3	L
.032	.060 ±.008	.120 ±.008	.016 ±.004	.016 ±.004	.030 ±.004	.012 ±.001	.015 ±.004	.030 ±.004	.030 ±.004	.196 ±.008
0.80	1.20 ±0.20	3.00 ±0.20	0.40 ±0.10	0.40 ±0.10	0.75 ±0.10	0.31 ±0.02	0.38 ±0.10	0.75 ±0.10	0.75 ±0.10	4.98 ±0.20

BCN Series

Construction



Ordering Procedure

Example: BCN164ABZ102J7S (BCN 1.6mm wide, 4 resistors, isolated circuit, square edge, convex terminations with TCR $\pm 100\text{ppm}/^\circ\text{C}$ at 1 kilohm $\pm 5\%$, on a 7" reel, anti-sulphur construction, Pb-free).

B	C	N	1	6	4	A	B	Z	1	0	2	J	7	S
1	2	3	4	5	6	7	8	9	10	11				

1	2	3	4	5	6	7	8	9	10	11
Series	Width	Number of Resistors	Circuit	Edge	Termination	TCR (ppm/°C)	Value	Tolerance	Packaging	Construction
BCN	Blank=3.1mm	4	A=Isolated	Blank=Scalloped	Blank=External (convex)	Blank=±200	3 digits for E24 at 2% or 5%	F=±1%	7=7" reel 13=13" reel	Blank=Standard
		8	D=Isolated					G=±2%		
	10=1.0mm	S=Standard bussed	B=Square	I=Internal (concave)	Z=±100	4 digits for uniquely E96 and for all values at 1%	J=±5%	S=Anti-sulphur		
	16=1.6mm						(Blank for jumper)			
	21=2.1mm						R=Reverse bussed			
	31=3.1mm									
							JP=Jumper			

Valid Combinations (1 – 6)	Valid Options (7, 8 & 11)	Packaging Quantity & Tape (10)
B C N 1 0 4 A B	JP=Jumper, S=Anti-sulphur	7=10,000/reel, 13=40,000/reel, Paper tape
B C N 1 6 4 A	Z= $\pm 100\text{ppm}/^\circ\text{C}$, JP=Jumper, S=Anti-sulphur	7=5000/reel, 13=20,000/reel, Paper tape
B C N 1 6 4 A B	Z= $\pm 100\text{ppm}/^\circ\text{C}$, JP=Jumper, S=Anti-sulphur	
B C N 1 6 4 A B I	JP=Jumper	
B C N 1 6 8 S B		
B C N 1 6 8 R B	S=Anti-sulphur	
B C N 2 1 8 S B I		7=4000/reel, 13=16,000/reel, Plastic tape
B C N 4 4 D	JP=Jumper, S=Anti-sulphur	
B C N 4 4 D B I	JP=Jumper	
B C N 3 1 8 S B		
B C N 3 1 8 R B		
B C N 3 1 8 S B I		
B C N 3 1 8 R B I		