

Absolute Maximum Ratings @ 25°C

Parameter	Ratings	Units
SSR Output Blocking Voltage	70	V _P
TVS Working Voltage, Maximum	40.2	V
Reverse Input Voltage	5	V
Input Control Current	50	mA
Peak (10ms)	1	A
Input Power Dissipation ¹	150	mW
SSR Output Power Dissipation ²	400	mW
TVS Peak Pulse Power (I _{PP} =9.3A, 10/1000µs pulse)	600	W
Isolation Voltage, Input to Output	3750	V _{rms}
Operating Temperature, Ambient	-40 to +85	°C
Storage Temperature	-40 to +125	°C

¹ Derate linearly 1.33 mW / °C

² Derate output linearly 6.67 mW / °C

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.

Typical values are characteristic of the device at +25°C, and are the result of engineering evaluations. They are provided for information purposes only, and are not part of the manufacturing testing requirements.

TVS Electrical Characteristics

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Clamping Voltage	I _{PP} =9.3A	V _C	-	-	66.5	V
Reverse Breakdown Voltage	I=1mA	V _{BR}	44.4	-	-	V
Reverse Leakage Current	V _{WM} =40.2V	I _L	-	-	5	µA


SSR Electrical Characteristics @ 25°C

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Output Characteristics						
Blocking Voltage	I _L =1µA	V _{DRM}	70	-	-	V _P
Load Current, AC/DC	-	I _L	-	-	150	mA _{rms} / mA _{DC}
Continuous	-	I _L	-	-	150	mA _{rms} / mA _{DC}
Peak	t=10ms	I _{LPK}	-	-	±400	mA _P
On-Resistance ¹	I _L =150mA, I _F =1mA	R _{ON}	-	7	16	Ω
Off-State Leakage Current	V _L =70V _P	I _{LEAK}	-	-	1	µA
Switching Speeds	-	-	-	-	-	-
Turn-On	I _F =5mA, V _L =10V (See Timing Diagram)	t _{on}	-	-	2.5	ms
Turn-Off	I _F =5mA, V _L =10V (See Timing Diagram)	t _{off}	-	-	2.5	ms
Output Capacitance	I _F =0mA, V _L =50V, f=1MHz	C _{OUT}	-	25	-	pF
Input Characteristics						
Input Control Current to Activate ²	I _L =150mA	I _F	-	-	1	mA
Input Dropout Current to Deactivate	-	I _F	0.1	-	-	mA
Input Voltage Drop	I _F =5mA	V _F	0.9	1.2	1.4	V
Common Characteristics						
Capacitance, Input to Output	V _{IO} =0V, f=1MHz	C _{IO}	-	3	-	pF













¹ Measurement taken within 1 second of turn-on time.

² For applications requiring high temperature operation (> 60°C) a minimum LED drive current of 3mA is recommended.

Timing Diagram













PERFORMANCE DATA*



*Unless otherwise noted, data presented in these graphs is typical of device operation at 25°C .

PERFORMANCE DATA*



*Unless otherwise noted, data presented in these graphs is typical of device operation at 25°C.

Manufacturing Information

Moisture Sensitivity



All plastic encapsulated semiconductor packages are susceptible to moisture ingress. IXYS Integrated Circuits classifies its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a **Moisture Sensitivity Level (MSL)** classification as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

Device	Moisture Sensitivity Level (MSL) Classification
CPC1317P	MSL 3

ESD Sensitivity



This product is ESD Sensitive, and should be handled according to the industry standard **JESD-625**.

Soldering Profile

Provided in the table below is the **IPC/JEDEC J-STD-020** Classification Temperature (T_C) and the maximum dwell time the body temperature of these surface mount devices may be ($T_C - 5$)°C or greater. The Classification Temperature sets the Maximum Body Temperature allowed for these devices during reflow soldering processes.

Device	Classification Temperature (T_C)	Dwell Time (t_p)	Max Reflow Cycles
CPC1317P	245°C	30 seconds	3


Board Wash

IXYS Integrated Circuits recommends the use of no-clean flux formulations. Board washing to reduce or remove flux residue following the solder reflow process is acceptable provided proper precautions are taken to prevent damage to the device. These precautions include but are not limited to: using a low pressure wash and providing a follow up bake cycle sufficient to remove any moisture trapped within the device due to the washing process. Due to the variability of the wash parameters used to clean the board, determination of the bake temperature and duration necessary to remove the moisture trapped within the package is the responsibility of the user (assembler). Cleaning or drying methods that employ ultrasonic energy may damage the device and should not be used. Additionally, the device must not be exposed to halide flux or solvents.




MECHANICAL DIMENSIONS

CPC1317P



CPC1317PTR Tape & Reel



For additional information please visit our website at: <https://www.ixysic.com>