

308 Constitution Drive

www.circuitprotection.com

Menlo Park, CA USA

2Pro™ Device Series

PRODUCT: PSR-26903-0.157

DOCUMENT: SCD27153 REV LETTER: F

REV DATE: APRIL 11, 2014

PAGE NO.: 2 OF 2

TABLE II. PPTC-SECTION (TERMINALS 1-2) PERFORMANCE RATINGS @ 20°C:

Ľ	TABLE II. FF TC-SECTION (TENMINALS 1-2) FENT ONMANCE HATINGS @ 20 C.						
	HOLD CURRENT (A)	TRIP CURRENT (A)	RESISTANCE (Ω)†			TIME TO TRIP† (s) @ 1A	
			R MIN	R MAX	R _{1 MAX} *	TYP	MAX
	0.15	0.30	6.5	14.0	16.0	0.9	3

^{*}Maximum device resistance at 20°C measured 1 hour post trip.

TABLE III. MOV-SECTION (TERMINALS 2-3) PERFORMANCE RATINGS @ 20°C:

VARISTOR VOLTAGE @ 1mA		DC RESISTANCE @ 100V	MAXIMUM CLAMPING VOLTAGE @ 25A	RATED WATTAGE	
DC (V)	TOLERANCE	(MΩ)	(V)	(W)	
430	± 10 %	>10	710	0.25	

TABLE IV. SURGE IMMUNITY FOR THE ASSEMBLY (TERMINALS 1-3) @ 20°C:

	VOLTAGE - Open Circuit		CURRENT - Short Circuit		
Parameter	Voltage	Waveform	Current	Waveform	Repetitions
	(V)	(µs)	(A)	(µs)	
IEC / EN 61000-4-5	2000	1.2 x 50	1000	8 x 20	5 ea. Polarity

TABLE V. APPLICABLE PART DESCRIPTIONS:

PART DESCRIPTION	PACKAGING	NOTES
PSR-26903-0.157	Bulk	N/A

Agency Recognitions: Made from components certified to:

MOV UL1449 File# E332226 PPTC UL1434 File# E74889 Raychem PS300 for PPTC section

Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information

ROHS Compliant

Reference Documents:

ELV Compliant

Pb-Free

Directive 2002/95/EC Compliant Directive 2000/53/EC Compliant



Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Tyco Electronics Corporation and its affiliates in the TE Connectivity Ltd. group of companies ("TE") reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product. This publication supersedes and replaces all information previously supplied. Without expressed or written consent by an officer of TE, TE does not authorize the use of any products as components in nuclear facility applications, aerospace, or in critical life support devices or systems. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. TE' only obligations are those in the TE Standard Terms and Conditions of Sale and in no case will TE be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products

© 2007, 2014 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All rights reserved. 2Pro, TE Connectivity, and TE connectivity (™), are trademarks.

[†] Corresponds to operations below varistor switch voltage.