

## Low Leakage Schottky Barrier Rectifier

### Characteristics

#### Static Electrical Characteristics


Symbol	Parameter	Test Conditions		Typ	max	Units
$V_F^{(2)}$	Maximum forward voltage	$T_J = 25^\circ\text{C}$	$I_F = 0.1\text{ A}$		0.455	V
			$I_F = 1.0\text{ A}$		0.530	
			$I_F = 3.0\text{ A}$		0.595	
		$T_J = 100^\circ\text{C}$	$I_F = 0.1\text{ A}$		0.360	
			$I_F = 1.0\text{ A}$		0.455	
			$I_F = 3.0\text{ A}$		0.540	
$I_R^{(2)}$	Maximum instantaneous reverse current	$T_J = 25^\circ\text{C}$	$V_R = 20\text{V}$		10	$\mu\text{A}$
			$V_R = 10\text{V}$		1.0	
			$V_R = 5\text{V}$		0.5	
		$T_J = 100^\circ\text{C}$	$V_R = 20\text{V}$		1600	
			$V_R = 10\text{V}$		500	
			$V_R = 5\text{V}$		300	
$C_T$	Junction capacitance	$V_R = 5\text{V}, f = 1\text{MHz}$				pF

<sup>(2)</sup> Measured with a test pulse of 380 $\mu\text{s}$  to minimize self-heating effect

#### Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Junction to case (bottom)	15	$^\circ\text{C/W}$
$R_{\theta JA}$	Junction to ambient <sup>(3)</sup>	240	$^\circ\text{C/W}$

<sup>(3)</sup> Mounted on FR-4 PC board using 1oz copper with recommended minimum foot print




Reverse power dissipation and the possibility of thermal runaway must be considered when operating this device under any reverse voltage conditions. Calculations of  $T_J$  therefore must include forward and reverse power effects. The allowable operating  $T_J$  may be calculated from the equation:


$T_J = T_{J\max} = r(t)(P_f + P_r)$  where  
 $r(t)$  = thermal impedance under given conditions.  
 $P_f$  = forward power dissipation, and  
 $P_r$  = reverse power dissipation

This graph displays the de-rated allowable  $T_J$  due to reverse bias under DC conditions only and is calculated as  $T_J = T_{J\max} - r(t) P_r$ , Where  $r(t) = R_{\theta JA}$ . For other power applications further calculations must be performed.

## Low Leakage Schottky Barrier Rectifier



Thermal Impedance Junction to Case (bottom)



Thermal Impedance Junction to Ambient


## Mechanical Characteristics

### Physical dimensions

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.73	0.99	0.029	0.039
B	0.40	0.66	0.016	0.026
C	1.77	2.03	0.070	0.080
D	2.21	2.46	0.087	0.097
E	0.50	0.76	0.020	0.030
F	1.29	1.54	0.051	0.061
G	0.53	0.78	0.021	0.031
H	0.10	0.20	0.004	0.008
I	1.77	2.03	0.070	0.080
J	0.89	1.14	0.035	0.045

## Low Leakage Schottky Barrier Rectifier

### Footprint dimensions



Powermite 1<sup>®</sup> footprint dimensions in *mm (inches)*

### Package materials & information

**Case :** Epoxy meets UL94V-0

**Electrode finish :** Matte Sn plating - fully RoHS compliant

**Marking code :**

# 20E

### Ordering information

Product order code	Marking	Package	Weight	Base qty	Delivery mode
UPS120Ee3 / TR7	20E	Powermite 1 (DO-216AA)	0.016 g	3000	Tape and reel (7 inch)
UPS120Ee3 / TR13	20E	Powermite 1 (DO-216AA)	0.016 g	12000	Tape and reel (13 inch)

*Commercial Business Unit  
Microsemi Corporation*

Microsemi Commercial Offshore de Macau Limitada  
Avenida Doutor Mario Soares  
Bank of China Building, 18/F, Unit D  
Macau SAR

Please refer to [www.microsemi.com](http://www.microsemi.com) for the terms and conditions of purchase