

Vendor :	C2G
Weight :	0.200 LB

Fiber Core Characteristics

- Optical Fiber Type - 50 Multimode
- ISO/IEC 11801 Nomenclature - OM3
- Wavelength (nm) - 850/1300
- Maximum Attenuation (dB/km) - 3.0/1.0
- Minimum Over Filled Launch (OFL) - 1500/500 MHz km
- Minimum Effective Modal - 4700/— (MHz km)
- Serial 1 Gigabit Ethernet Distance (m) - 600
- Serial 10 Gigabit Ethernet Distance (m) - 300
- Maximum Connector Loss: 0.50 dB

Physical Specifications

- Jacket material: PVC (OFNP plenum rated)
- Jacket OD: 3.0 mm
- Installation Tensile Load: 100 N (445 lbs)
- Long-Term Tensile Load: 50 N (222 lbs)
- Installation Minimum Bend Radius: 4.5 cm (1.8 in)
- Long-Term Minimum Bend Radius: 3.0 cm (1.2 in)
- Typical Return Loss: -22 dB
- Operating Temperature: -20°C to +70°C

Please Note: Attenuation testing performed in accordance with EIA/TIA-455-171A.

Info

[About Us](#)
[Order History](#)
[Where To Buy](#)
[More ▾](#)

Service

[Contact Us](#)
[OEM Solutions](#)
[Tech Support](#)
[More ▾](#)

Resources

[Connector Guides](#)
[ConnectXpress](#)
[Drivers & Manuals](#)
[More ▾](#)

Have A Question?

Get help with [Chat](#)
Call C2G **800.506.9607**
[f](#) [t](#) [v](#) [b](#)



United States | Europe +
Copyright © 2019 C2G. All Rights Reserved

