

TABLE OF CONTENTS

Features	1
Applications	1
General Description	1
Pin Configurations	1
Revision History	2
Specifications	3
Electrical Characteristics	3

Absolute Maximum Ratings	5
Thermal Resistance	5
ESD Caution	5
Typical Performance Characteristics	6
Outline Dimensions	13
Ordering Guide	15

REVISION HISTORY

9/11—Rev. D to Rev. E

Changes to Thermal Resistance Section	5
---	---

7/11—Rev. C to Rev. D

Changes to Figure 6	1
---------------------------	---

11/10—Rev. B to Rev. C

Changes to Figure 6	1
Added Thermal Resistance Section and Table 4	5
Updated Outline Dimensions	13
Changes to Ordering Guide	15

4/05—Rev. A to Rev. B

Added AD8643	Universal
Added 14-Lead SOIC	Universal
Added 16-Lead LFCSP	Universal
Updated Outline Dimensions	13
Changes to Ordering Guide	14

3/05—Rev. 0 to Rev. A

Added AD8642	Universal
Changes to General Description	1
Added Figure 3 and Figure 4	1
Changes to Specifications	3
Changes to Absolute Maximum Ratings	5
Changes to Figure 22	8
Changes to Figure 23	9
Changes to Figure 41	12
Updated Outline Dimensions	13
Changes to Ordering Guide	14

10/04—Initial Version: Revision 0

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS

$V_S = 5.0\text{ V}$, $V_{CM} = 2.5\text{ V}$, $T_A = 25^\circ\text{C}$, unless otherwise noted.

Table 1.

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V _{OS}	AD8643 LFCSP only −40°C < T _A < +85°C +85°C < T _A < +125°C, V _{CM} = 1.5 V		50	750	μV mV mV mV
Input Bias Current	I _B	−40°C < T _A < +125°C		0.25	1	pA
Input Offset Current	I _{OS}	−40°C < T _A < +125°C			180	pA
Input Voltage Range		−40°C < T _A < +125°C	0		60	pA
Common-Mode Rejection Ratio	CMRR	V _{CM} = 0 V to 2.5 V	74	93	3	V dB
Large Signal Voltage Gain	A _{VO}	R _L = 10 kΩ, V _O = 0.5 to 4.5 V	80	140		V/mV
Offset Voltage Drift	ΔV _{OS} /ΔT	−40°C < T _A < +125°C		2.5		μV/°C
OUTPUT CHARACTERISTICS						
Output Voltage High	V _{OH}	I _L = 1 mA, −40°C to +125°C	4.95			V
Output Voltage Low	V _{OL}	I _L = 1 mA, −40°C to +125°C	4.94		0.05	V
Output Current	I _{OUT}			0.01	0.05	V
				±6		mA
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	V _S = 5 V to 26 V	90	107		dB
Supply Current/Amplifier	I _{SY}	−40°C < T _A < +125°C		195	250	μA
					270	μA
DYNAMIC PERFORMANCE						
Slew Rate	SR			2		V/μs
Gain Bandwidth Product	GBP	AD8641, AD8642		3		MHz
		AD8643		2.5		MHz
Phase Margin	∅ _m			50		Degrees
NOISE PERFORMANCE						
Voltage Noise	e _N p-p	f = 0.1 Hz to 10 Hz		4.0		μV p-p
Voltage Noise Density	e _N	f = 1 kHz		28.5		nV/√Hz
Current Noise Density	i _N	f = 1 kHz		0.5		fA/√Hz

$V_S = \pm 13\text{ V}$, $V_{CM} = 0\text{ V}$, $T_A = 25^\circ\text{C}$, unless otherwise noted.

Table 2.

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	AD8643 LFCSP only $-40^\circ < T_A < +125^\circ\text{C}$		70	750	μV
					1	mV
Input Bias Current	I_B	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$		0.25	1.5	mV
					1	pA
Input Offset Current	I_{OS}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$			260	pA
					0.5	pA
Input Voltage Range		$-40^\circ\text{C} < T_A < +125^\circ\text{C}$			65	pA
					+10	V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = -13\text{ V to } +10\text{ V}$	-13	90	107	dB
Large Signal Voltage Gain	A_{VO}	$R_L = 10\text{ k}\Omega$, $V_O = -11\text{ V to } +11\text{ V}$	215	290		V/mV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$		2.5		$\mu\text{V}/^\circ\text{C}$
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	$I_L = 1\text{ mA}$, $-40^\circ\text{C to } +125^\circ\text{C}$	+12.95			V
			+12.94			V
Output Voltage Low	V_{OL}	$I_L = 1\text{ mA}$, $-40^\circ\text{C to } +125^\circ\text{C}$			-12.95	V
					-12.94	V
Output Current	I_{OUT}			± 12		mA
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_S = \pm 2.5\text{ V to } \pm 13\text{ V}$	90	107		dB
Supply Current/Amplifier	I_{SY}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$		200	290	μA
					330	μA
DYNAMIC PERFORMANCE						
Slew Rate	SR			3		V/ μs
Gain Bandwidth Product	GBP			3.5		MHz
Phase Margin	ϕ_m			60		Degrees
NOISE PERFORMANCE						
Voltage Noise	e_N p-p	$f = 0.1\text{ Hz to } 10\text{ Hz}$		4.2		$\mu\text{V p-p}$
Voltage Noise Density	e_N	$f = 1\text{ kHz}$		27.5		nV/ $\sqrt{\text{Hz}}$
Current Noise Density	i_N	$f = 1\text{ kHz}$		0.5		fA/ $\sqrt{\text{Hz}}$

ABSOLUTE MAXIMUM RATINGS

Absolute maximum ratings apply at 25°C, unless otherwise noted.

Table 3.

Parameter	Rating
Supply Voltage	27.3 V
Input Voltage	VS– to VS+
Differential Input Voltage	±Supply Voltage
Output Short-Circuit Duration	Indefinite
Storage Temperature Range	
KS-5, R-8, RM-8, R-14, CP-16 Packages	–65°C to +150°C
Operating Temperature Range	–40°C to +125°C
Junction Temperature Range	
KS-5, R-8, RM-8, R-14, CP-16 Packages	–65°C to +150°C
Lead Temperature (Soldering, 60 sec)	300°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL RESISTANCE

θ_{JA} is specified for the worst-case conditions, that is, a device soldered in a circuit board for surface-mount packages. This was measured using a standard 4-layer board. For the LFCSP package, solder the exposed pad to a copper plane, which should be connected to V+.

Table 4.

Package Type	θ_{JA}	θ_{JC}	Unit
5-Lead SC70 (KS)	430	149	°C/W
8-Lead SOIC (R)	121	43	°C/W
8-Lead MSOP (RM)	142	45	°C/W
14-Lead SOIC (R)	110	36	°C/W
16-Lead LFCSP (CP)	81	16	°C/W

ESD CAUTION



ESD (electrostatic discharge) sensitive device.

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 7. Input Offset Voltage




Figure 10. Offset Voltage Drift




Figure 8. Offset Voltage Drift




Figure 11. Input Bias Current vs. V_{CM} 

Figure 9. Input Offset Voltage

Figure 12. Input Bias Current vs. V_{CM}






Figure 13. Input Bias Current vs. Temperature

05072-008

Figure 16. Input Offset Voltage vs. V_{CM}

05072-011

Figure 14. Input Bias Current vs. V_{CM}

05072-009





Figure 17. Open-Loop Gain vs. Load Resistance

05072-012

Figure 15. Input Offset Voltage vs. V_{CM}

05072-010




Figure 18. Open-Loop Gain vs. Temperature

05072-013




Figure 19. Input Error Voltage vs. Output Voltage for Resistive Loads




Figure 22. Output Saturation Voltage vs. Load Current




Figure 20. Input Error Voltage vs. Output Voltage Within 300 mV of Supply Rails




Figure 23. Output Saturation Voltage vs. Load Current




Figure 21. Quiescent Current vs. Supply Voltage at Different Temperatures




Figure 24. Open-Loop Gain and Phase Margin vs. Frequency




Figure 25. Open-Loop Gain and Phase Margin vs. Frequency




Figure 28. CMRR vs. Frequency




Figure 26. Closed-Loop Gain vs. Frequency




Figure 29. CMRR vs. Frequency




Figure 27. Closed-Loop Gain vs. Frequency




Figure 30. PSRR vs. Frequency




Figure 31. PSRR vs. Frequency




Figure 34. No Phase Reversal




Figure 32. Output Impedance vs. Frequency




Figure 35. Output Swing and Error vs. Settling Time




Figure 33. Output Impedance vs. Frequency




Figure 36. Small Signal Overshoot vs. Load Capacitance




Figure 37. Small Signal Overshoot vs. Load Capacitance

05072-032




Figure 40. Voltage Noise Density

05072-035




Figure 38. 0.1 Hz to 10 Hz Noise

05072-033




Figure 41. Voltage Noise Density

05072-036




Figure 39. 0.1 Hz to 10 Hz Noise

05072-034




Figure 42. Total Harmonic Distortion + Noise vs. Frequency

05072-037





Figure 43. Channel Separation

OUTLINE DIMENSIONS




COMPLIANT TO JEDEC STANDARDS MO-203-AA

Figure 44. 5-Lead Thin Shrink Small Outline Transistor Package [SC70]
(KS-5)

Dimensions shown in millimeters

072809-A



COMPLIANT TO JEDEC STANDARDS MS-012-AA

CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.Figure 45. 8-Lead Standard Small Outline Package [SOIC_N]
(R-8)

Dimensions shown in millimeters and (inches)

012407-A





Figure 46. 8-Lead Mini Small Outline Package [MSOP]
(RM-8)

Dimensions shown in millimeters



CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 47. 14-Lead Standard Small Outline Package [SOIC_N]
(R-14)

Dimensions shown in millimeters and (inches)




Figure 48. 16-Lead Lead Frame Chip Scale Package [LFCSP_VQ]
3 mm × 3 mm Body, Very Thin Quad (CP-16-3)

Dimensions shown in millimeters

ORDERING GUIDE

Model ¹	Temperature Range	Package Description	Package Option	Branding
AD8641AKSZ-R2	–40°C to +125°C	5-Lead SC70	KS-5	A07
AD8641AKSZ-REEL7	–40°C to +125°C	5-Lead SC70	KS-5	A07
AD8641AKSZ-REEL	–40°C to +125°C	5-Lead SC70	KS-5	A07
AD8641ARZ	–40°C to +125°C	8-lead SOIC_N	R-8	
AD8641ARZ-REEL7	–40°C to +125°C	8-lead SOIC_N	R-8	
AD8641ARZ-REEL	–40°C to +125°C	8-lead SOIC_N	R-8	
AD8642ARMZ	–40°C to +125°C	8-lead MSOP	RM-8	A0A
AD8642ARMZ-REEL	–40°C to +125°C	8-lead MSOP	RM-8	A0A
AD8642ARZ	–40°C to +125°C	8-lead SOIC_N	R-8	
AD8642ARZ-REEL7	–40°C to +125°C	8-lead SOIC_N	R-8	
AD8642ARZ-REEL	–40°C to +125°C	8-lead SOIC_N	R-8	
AD8643ARZ	–40°C to +125°C	14-lead SOIC_N	R-14	
AD8643ARZ-REEL7	–40°C to +125°C	14-lead SOIC_N	R-14	
AD8643ARZ-REEL	–40°C to +125°C	14-lead SOIC_N	R-14	
AD8643ACPZ-R2	–40°C to +125°C	16-Lead LFCSP_VQ	CP-16-3	AUA
AD8643ACPZ-REEL7	–40°C to +125°C	16-Lead LFCSP_VQ	CP-16-3	AUA
AD8643ACPZ-REEL	–40°C to +125°C	16-Lead LFCSP_VQ	CP-16-3	AUA

¹ Z = RoHS Compliant Part.

NOTES