



# Avalanche Diode

## Preliminary data

$V_{RSM}$	$V_{(BR)min}$	$V_{RRM}$	Type
V	V	V	
1300	1300	1200	DSA 1-12D
1700	1750	1600	DSA 1-16D
1900	1950	1800	DSA 1-18D



A = Anode, C = Cathode

Symbol	Conditions	Maximum Ratings	
$I_{FRMS}$	$T_{VJ} = T_{VJM}$	7	A
$I_{FAVM}$	$T_{amb} = 45^{\circ}C$ ; $R_{thJA} = 38 K/W$ ; 180° sine	2.3	A
	$T_{amb} = 45^{\circ}C$ ; $R_{thJA} = 80 K/W$ ; 180° sine	1.3	A
$P_{RSM}$	$T_{VJM}$ , $t_p = 10 \mu s$	1.6	kW
$I_{FSM}$	$T_{VJ} = 45^{\circ}C$ ; $t = 10 ms$ (50 Hz), sine	110	A
	$t = 8.3 ms$ (60 Hz), sine	118	
	$T_{VJ} = 150^{\circ}C$ ; $t = 10 ms$ (50 Hz), sine	100	A
	$t = 8.3 ms$ (60 Hz), sine	104	
$I^2t$	$T_{VJ} = 45^{\circ}C$ ; $t = 10 ms$ (50 Hz), sine	60	A <sup>2</sup> s
	$t = 8.3 ms$ (60 Hz), sine	58	
	$T_{VJ} = 150^{\circ}C$ ; $t = 10 ms$ (50 Hz), sine	50	A <sup>2</sup> s
	$t = 8.3 ms$ (60 Hz), sine	45	
$T_{VJ}$		-40...+150	°C
$T_{VJM}$		150	°C
$T_{stg}$		-40...+150	°C
Weight	typical	0.8	g

## Features

- Plastic standard package
- Planar passivated chips

## Applications

- Low power rectifiers
- Field supply for DC motors
- Power supplies
- High voltage rectifiers

## Advantages

- Space and weight savings
- Simple PCB mounting
- Improved temperature & power cycling
- Reduced protection circuits

Symbol	Conditions	Characteristic Values		
		typ.	max.	
$I_R$	$V_R = V_{RRM}$ $T_{VJ} = T_{VJM}$		0.7	mA
$V_F$	$I_F = 7 A$ $T_{VJ} = 25^{\circ}C$		1.34	V
$V_{T0}$	For power-loss calculations only		0.8	V
$r_T$	$T_{VJ} = T_{VJM}$		67	mΩ
$R_{thJA}$	Forced air cooling with 1.5 m/s, $T_{amb} = 45^{\circ}C$ Soldered on to PC board, $T_{amb} = 45^{\circ}C$		38 80	K/W K/W
$d_s$	Creepage distance on surface		8.5	mm
$d_A$	Strike distance through air		6.7	mm
$a$	Max. allowable acceleration		100	m/s <sup>2</sup>

Data according to IEC 60747

## Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

IXYS reserves the right to change limits, test conditions and dimensions.

Dimensions in mm (1 mm = 0.0394")

