

ELECTRICAL SPECIFICATIONS (T _J = 25 °C unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX. UNITS
Cathode to anode breakdown voltage	V _{BR}	I _R = 100 µA		600	-	- V
Maximum forward voltage	V _{FM}	I _F = 25 A	See fig. 1	-	1.3	1.7
		I _F = 50 A		-	1.5	2.0
		I _F = 25 A, T _J = 125 °C		-	1.3	1.7
Maximum reverse leakage current	I _{RM}	V _R = V _R rated	See fig. 2	-	1.5	20
		T _J = 125 °C, V _R = 0.8 x V _R rated		-	600	2000
Junction capacitance	C _T	V _R = 200 V	See fig. 3	-	55	100 pF
Series inductance	L _S	Measured lead to lead 5 mm from package body		-	12	- nH

DYNAMIC RECOVERY CHARACTERISTICS (T _J = 25 °C unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX. UNITS
Reverse recovery time See fig. 5, 10	t _{rr}	I _F = 1.0 A, dI _F /dt = 200 A/µs, V _R = 30 V		-	23	-
	t _{rr1}	T _J = 25 °C	I _F = 25 A dI _F /dt = 200 A/µs V _R = 200 V	-	50	75 ns
	t _{rr2}	T _J = 125 °C		-	105	160
Peak recovery current See fig. 6, 10	I _{RRM1}	T _J = 25 °C		-	4.5	10 A
	I _{RRM2}	T _J = 125 °C		-	8.0	15
Reverse recovery charge See fig. 7, 10	Q _{rr1}	T _J = 25 °C		-	112	375 nC
	Q _{rr2}	T _J = 125 °C		-	420	1200
Peak rate of fall of recovery current during t _b See fig. 8, 10	dI _(rec) /dt1	T _J = 25 °C		-	250	- A/µs
	dI _(rec) /dt2	T _J = 125 °C		-	160	-

THERMAL - MECHANICAL SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX. UNITS
Lead temperature	T _{lead}	0.063" from case (1.6 mm) for 10 s		-	-	300 °C
Thermal resistance, junction to case	R _{thJC}			-	-	0.83
Thermal resistance, junction to ambient	R _{thJA}	Typical socket mount		-	-	40 K/W
Thermal resistance, case to heatsink	R _{thCS}	Mounting surface, flat, smooth and greased		-	0.25	-
Weight				-	6.0	- g
				-	0.21	- oz.
Mounting torque				6.0 (5.0)	-	12 (10) kgf · cm (lbf · in)
Marking device		Case style TO-247AC modified (JEDEC)		HFA25PB60		




Fig. 1 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current




Fig. 2 - Typical Reverse Current vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage








Fig. 4 - Maximum Thermal Impedance Z_{thJC} Characteristics

Fig. 5 - Typical Reverse Recovery Time vs. di_F/dt Fig. 7 - Typical Stored Charge vs. di_F/dt Fig. 6 - Typical Recovery Current vs. di_F/dt Fig. 8 - Typical $di_{(rec)}M/dt$ vs. di_F/dt

HEXFRED®
Ultrafast Soft Recovery Diode, 25 A

Vishay High Power Products




Fig. 9 - Reverse Recovery Parameter Test Circuit




Fig. 10 - Reverse Recovery Waveform and Definitions

ORDERING INFORMATION TABLE

Device code	HF	A	25	PB	60	PbF
	1	2	3	4	5	6

- | | | |
|---|---|--|
| 1 | - | HEXFRED® family |
| 2 | - | Process designator: A = Electron irradiated
B = Platinum diffused |
| 3 | - | Current rating (25 = 25 A) |
| 4 | - | Package outline (PB = TO-247, 2 pins) |
| 5 | - | Voltage rating (60 = 600 V) |
| 6 | - | • None = Standard production
• PbF = Lead (Pb)-free |

LINKS TO RELATED DOCUMENTS	
Dimensions	http://www.vishay.com/doc?95253
Part marking information	http://www.vishay.com/doc?95255



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.