

#### Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
Faranteter		Conditions	min	typ	max	J OHIL
Reverse Voltage	VR	I <sub>R</sub> =1mA	600			V
Forward Voltage	VF	I <sub>F</sub> =10A		1.1	1.3	V
Reverse Current	IR	V <sub>R</sub> =600V			100	μΑ
Reverse Recovery Time	t <sub>rr</sub> 1	I <sub>F</sub> =10A, di / dt=100A/μs		100	150	ns
everse Recovery Time	t <sub>rr</sub> 2	IF=0.5A, IR=1A		60		ns
Thermal Resistance Rth(j-c) Junction		Junction -Case : Smoothed DC			4.9	°C / W

# **Ordering Information**

Device Package		Shipping	memo	
UD1006FR-H TO-220F-2FS		50pcs./magazine	Pb Free and Halogen Free	






#### Magazine Specification

UD1006FR-H

### 1. Packing Format


Package Name	Magazine Name	Maximum Number of devices contained (pcs)			Packing format		
I a o n a g o Mamo	I gong 80 Mamo Maganino Mamo		Inner box	Outer box	Inner BOX	Outer BOX	
TO-220F-2FS	TO-220F	50	1, 000	4,000	SPD-0V0001 20 magazines contained Dimensions:mm (external) 568×150×55	SPT-081029 4 inner boxes contained Dimensions:mm (external) 590×225×178	


### 



Tolerance=±0.3mm
Thickness=0.7±0.2mm
Length =532.5±2mm
Material =PVC (Antistatic treatment)

# 3. Storage method to magazine






The LEAD FREE \* description shows that the surface treatment of the terminal is lead free.

Label		JEITA Phase			
LEAD FREE	3	JEITA Phase 3A			

# **Outline Drawing**

UD1006FR-H



#### **UD1006FR**

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa