

LD-P (ALDP)


2. Specifications

Characteristics	Item		Specifications
Contact	Arrangement		1 Form A
	Contact resistance (Initial)		Max. 100 mΩ (By voltage drop 6 V DC 1A)
	Contact material		AgNi type
Rating	Nominal switching capacity (resistive load)		5A 277V AC
	Max. switching power (resistive load)		1,385VA
	Max. switching voltage		277V AC
	Max. switching current		5A
	Min. switching capacity (reference value)*1		100mA 5V DC
Electrical characteristics	Insulation resistance (Initial)		Min. 1,000MΩ (at 500V DC) Measurement at same location as “Breakdown voltage” section.
	Breakdown voltage (Initial)	Between open contacts	750 Vrms for 1 min. (Detection current: 10 mA)
		Between contact and coil	4,000 Vrms for 1 min. (Detection current: 10 mA)
	Surge breakdown voltage*2 (Between contact and coil)		10,000 V (initial)
	Temperature rise		Max. 30°C 86°F (By resistive method, nominal coil voltage applied to the coil; contact carrying current: 5A, at 85°C 185°F)
	Operate time (at nominal voltage) (at 20°C 68°F)		Max. 10 ms (excluding contact bounce time.)
	Release time (at nominal voltage) (at 20°C 68°F)		Max. 10 ms (excluding contact bounce time) (With diode)
Mechanical characteristics	Shock resistance	Functional	Min. 300 m/s ² (Half-wave pulse of sine wave: 11 ms; detection time: 10μs.)
		Destructive	Min. 1,000 m/s ² (Half-wave pulse of sine wave: 6 ms.)
	Vibration resistance	Functional	10 to 55 Hz at double amplitude of 1.5 mm (Detection time: 10μs.)
		Destructive	10 to 55 Hz at double amplitude of 1.5 mm
Expected life	Mechanical (at 180 cpm)		Min. 5×10 ⁶
	Electrical (at 20 cpm)		Min. 2×10 ⁵ (5A 125V AC at rated load), Min. 10 ⁵ (5A 250V AC at rated load)
Conditions	Conditions for operation, transport and storage*3		Ambient temperature: -40°C to +85°C -40°F to +185°F; Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature)
	Max. operating speed (at nominal switching capacity)		20 cpm
Unit weight			Approx. 4 g .14 oz


Notes:
*1 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.
*2 Wave is standard shock voltage of ±1.2×50μs according to JEC-212-1981
*3 The upper limit of the ambient temperature is the maximum temperature that can satisfy the coil temperature rise value. Refer to "6. Usage, Storage and Transport Conditions" in [AMBIENT ENVIRONMENT](#) section in [Relay Technical Information](#).

REFERENCE DATA

1. Max. switching power




2. Life curve




3. Coil temperature rise


Sample: ALDP112, 6 pcs.
Point measured: inside the coil
Contact current: 0 A, 5 A




4-(1). Operate time
Sample: ALDP112, 30 pcs.



4-(2). Release time (without diode)
Sample: ALDP112, 30 pcs.




4-(3). Release time (with diode)
Sample: ALDP112, 30 pcs.




5. Electrical life test
 (5A 250V AC Resistive load)
 Sample: ALDP112, 6 pcs.
 Operation frequency: 20 times/min.
 (ON:OFF = 1.5s:1.5s)


Circuit:



Change of pick-up and drop-out voltage




Change of contact resistance




DIMENSIONS (mm inch)

Download [CAD Data](#) from our Web site.

[CAD Data](#)




PC board pattern (Bottom view)



Tolerance: $\pm 0.1 \pm .004$

Schematic (Bottom view)



Dimension:

Max. 1mm .039 inch:

1 to 3mm .039 to .118 inch:

Min. 3mm .118 inch:

General tolerance

$\pm 0.1 \pm .004$

$\pm 0.2 \pm .008$

$\pm 0.3 \pm .012$

SAFETY STANDARDS

Certification authority	
UL, C-UL	5A 277V AC 70°C 5A 30V DC
VDE	5A 250V AC $\cos\phi = 1.0$ 70°C 5A 30V DC 0ms

NOTES

■ Usage, transport and storage conditions

1) Temperature:

-40 to +85°C -40 to +185°F


2) Humidity: 5 to 85% RH

(Avoid freezing and condensation.)

The humidity range varies with the temperature. Use within the range indicated in the graph below.

3) Atmospheric pressure: 86 to 106 kPa

Temperature and humidity range for usage, transport, and storage



4) Condensation

Condensation forms when there is a sudden change in temperature under high temperature and high humidity conditions. Condensation will cause deterioration of the relay insulation.

5) Freezing

Condensation or other moisture may freeze on the relay when the temperatures is lower than 0°C 32°F.

This causes problems such as sticking of movable parts or operational time lags.

6) Low temperature, low humidity environments

The plastic becomes brittle if the relay is exposed to a low temperature, low humidity environment for long periods of time.

■ Solder and cleaning conditions

1) Please obey the following conditions when soldering automatically.

(1) Preheating: Within 120°C 248°F

(solder surface terminal portion) and within 120 seconds

(2) Soldering iron: 260°C±5°C

500°F±41°F (solder temperature) and within 6 seconds (soldering time)

2) Do not use ultrasonic cleaning.

This will adversely affect the relay characteristics. Also, it is recommended that alcoholic solvents be used.

■ Certification

1) This relay is UL and C-UL certified.

UL and C-UL standards:

5 A 277 V AC 70°C

5 A 30 V DC

2) This relay is certified by VDE.

VDE standards:

5 A 250 V AC $\cos\phi = 1.0$ 70°C

5 A 30 V DC 0ms

3) UL, C-UL and VDE certified ratings are displayed on the packaging box.

(On the relay, only the certification marks are shown and not the certified ratings.

Please refer to the product specification diagrams to see what is stamped.)

■ Part number display

The "W" at the end of the part number only appears on the inner and outer packaging. It does not appear on the relay itself.

■ Others

1) To ensure good operation, please keep the voltage on the coil ends to $\pm 5\%$ (at 20°C 68°F) of the rated coil operation voltage. Also, please be aware that the pick-up voltage and drop-out voltage may change depending on the temperature and conditions of use.

2) Keep the ripple rate of the nominal coil voltage below 5%.

3) The cycle lifetime is defined under the standard test condition specified in the JIS C 5442 standard (temperature 15 to 35°C 59 to 95°F, humidity 25 to 75%R.H.). Check this with the real device

as it is affected by coil driving circuit, load type, activation frequency, activation phase, ambient conditions and other factors.

Also, be especially careful of loads such as those listed below.

(1) When used for AC load-operating and the operating phase is synchronous.

Rocking and fusing can easily occur due to contact shifting.

(2) Highly frequent load-operating

When highly frequent opening and closing of the relay is performed with a load that causes arcs at the contacts,

nitrogen and oxygen in the air is fused by the arc energy and HNO_3 is formed. This can corrode metal materials.

Three countermeasures for these are listed here.

- Incorporate an arc-extinguishing circuit.
- Lower the operating frequency
- Lower the ambient humidity

4) Minimum switching capacity is a guideline as to the lowest possible level at which it will be possible for a low level load to allow switching. This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.

5) Heat, smoke, and even a fire may occur if the relay is used in conditions outside of the allowable ranges for the coil ratings, contact ratings, operating cycle lifetime, and other specifications. Therefore, do not use the relay if these ratings are exceeded.

6) If the relay has been dropped, the appearance and characteristics should always be checked before use.

7) Incorrect wiring may cause unexpected events or the generation of heat or flames.

8) Creepage distance and clearances between contact and coil: Min. 6 mm

For Cautions for Use, see [Relay Technical Information](#).