

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units	
STATIC PARAMETERS							
BV_{CES}	Collector-Emitter Breakdown Voltage	$I_C=1\text{mA}$, $V_{GE}=0\text{V}$, $T_J=25^\circ\text{C}$	600	-	-	V	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$V_{GE}=15\text{V}$, $I_C=30\text{A}$	$T_J=25^\circ\text{C}$	-	1.6	2.1	V
			$T_J=125^\circ\text{C}$	-	1.82	-	
			$T_J=150^\circ\text{C}$	-	1.88	-	
V_F	Diode Forward Voltage	$V_{GE}=0\text{V}$, $I_C=30\text{A}$	$T_J=25^\circ\text{C}$	-	1.34	1.85	V
			$T_J=125^\circ\text{C}$	-	1.31	-	
			$T_J=150^\circ\text{C}$	-	1.3	-	
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$V_{CE}=5\text{V}$, $I_C=1\text{mA}$	-	5.7	-	V	
I_{CES}	Zero Gate Voltage Collector Current	$V_{CE}=600\text{V}$, $V_{GE}=0\text{V}$	$T_J=25^\circ\text{C}$	-	-	10	μA
			$T_J=125^\circ\text{C}$	-	-	600	
			$T_J=150^\circ\text{C}$	-	-	3000	
I_{GES}	Gate-Emitter leakage current	$V_{CE}=0\text{V}$, $V_{GE}=\pm 20\text{V}$	-	-	± 100	nA	
g_{FS}	Forward Transconductance	$V_{CE}=20\text{V}$, $I_C=30\text{A}$	-	17	-	S	
DYNAMIC PARAMETERS							
C_{ies}	Input Capacitance	$V_{GE}=0\text{V}$, $V_{CE}=25\text{V}$, $f=1\text{MHz}$	-	1893	-	pF	
C_{oes}	Output Capacitance		-	240	-	pF	
C_{res}	Reverse Transfer Capacitance		-	7	-	pF	
Q_g	Total Gate Charge	$V_{GE}=15\text{V}$, $V_{CE}=480\text{V}$, $I_C=30\text{A}$	-	47	-	nC	
Q_{ge}	Gate to Emitter Charge		-	17.8	-	nC	
Q_{gc}	Gate to Collector Charge		-	14.2	-	nC	
$I_{C(SC)}$	Short circuit collector current, Max. 1000 short circuits, Delay between short circuits $\geq 1.0\text{s}$	$V_{GE}=15\text{V}$, $V_{CE}=400\text{V}$, $R_G=25\Omega$	-	128	-	A	
R_g	Gate resistance	$V_{GE}=0\text{V}$, $V_{CE}=0\text{V}$, $f=1\text{MHz}$	-	1.36	-	Ω	
SWITCHING PARAMETERS, (Load Inductive, $T_J=25^\circ\text{C}$)							
$t_{D(on)}$	Turn-On DelayTime	$T_J=25^\circ\text{C}$ $V_{GE}=15\text{V}$, $V_{CE}=400\text{V}$, $I_C=30\text{A}$, $R_G=10\Omega$, Parasitic Inductance=150nH	-	26	-	ns	
t_r	Turn-On Rise Time		-	40	-	ns	
$t_{D(off)}$	Turn-Off Delay Time		-	71	-	ns	
t_f	Turn-Off Fall Time		-	10	-	ns	
E_{on}	Turn-On Energy		-	1.18	-	mJ	
E_{off}	Turn-Off Energy		-	0.2	-	mJ	
E_{total}	Total Switching Energy		-	1.38	-	mJ	
t_{rr}	Diode Reverse Recovery Time		-	137	-	ns	
Q_{rr}	Diode Reverse Recovery Charge	$T_J=150^\circ\text{C}$ $I_F=30\text{A}$, $dI/dt=200\text{A}/\mu\text{s}$, $V_{CE}=400\text{V}$	-	0.8	-	μC	
I_{rm}	Diode Peak Reverse Recovery Current		-	9.5	-	A	
SWITCHING PARAMETERS, (Load Inductive, $T_J=150^\circ\text{C}$)							
$t_{D(on)}$	Turn-On DelayTime	$T_J=150^\circ\text{C}$ $V_{GE}=15\text{V}$, $V_{CE}=400\text{V}$, $I_C=30\text{A}$, $R_G=10\Omega$, Parasitic Inductance=150nH	-	24	-	ns	
t_r	Turn-On Rise Time		-	41	-	ns	
$t_{D(off)}$	Turn-Off Delay Time		-	89	-	ns	
t_f	Turn-Off Fall Time		-	12	-	ns	
E_{on}	Turn-On Energy		-	1.48	-	mJ	
E_{off}	Turn-Off Energy		-	0.43	-	mJ	
E_{total}	Total Switching Energy		-	1.9	-	mJ	
t_{rr}	Diode Reverse Recovery Time		$T_J=150^\circ\text{C}$ $I_F=30\text{A}$, $dI/dt=200\text{A}/\mu\text{s}$, $V_{CE}=400\text{V}$	-	208	-	ns
Q_{rr}	Diode Reverse Recovery Charge	-		1.68	-	μC	
I_{rm}	Diode Peak Reverse Recovery Current	-		14.4	-	A	

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: Output Characteristic
($T_j = 25^\circ\text{C}$)




Fig 2: Output Characteristic
($T_j = 150^\circ\text{C}$)




Fig 3: Transfer Characteristic




Fig 4: Diode Characteristic




Fig 5: Collector-Emitter Saturation Voltage vs. Junction Temperature













Fig 6: V_{GE} vs. Short Circuit Time
($V_{CE} = 400V, T_c = 25^\circ\text{C}$)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 16: Switching Loss vs. I_C
($T_J=150^\circ\text{C}$, $V_{GE}=15\text{V}$, $V_{CE}=400\text{V}$, $R_g=10\Omega$)




Figure 17: Switching Loss vs. R_g
($T_J=150^\circ\text{C}$, $V_{GE}=15\text{V}$, $V_{CE}=400\text{V}$, $I_C=30\text{A}$)




Figure 18: Switching Loss vs. T_J
($V_{GE}=15\text{V}$, $V_{CE}=400\text{V}$, $I_C=30\text{A}$, $R_g=10\Omega$)




Figure 19: Switching Loss vs. V_{CE}
($T_J=150^\circ\text{C}$, $V_{GE}=15\text{V}$, $I_C=30\text{A}$, $R_g=10\Omega$)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 20: Diode Reverse Leakage Current vs. Junction Temperature




Fig 21: Diode Forward Voltage vs. Junction Temperature




Fig 22: Diode Reverse Recovery Charge and Peak Current vs. Conduction Current
($V_{GE}=15V, V_{CE}=400V, di/dt=200A/\mu s$)




Fig 23: Diode Reverse Recovery Time and Softness Factor vs. Conduction Current
($V_{GE}=15V, V_{CE}=400V, di/dt=200A/\mu s$)




Fig 24: Diode Reverse Recovery Charge and Peak Current vs. di/dt
($V_{GE}=15V, V_{CE}=400V, I_F=30A$)




Fig 25: Diode Reverse Recovery Time and Softness Factor vs. di/dt
($V_{GE}=15V, V_{CE}=400V, I_F=30A$)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 26: Normalized Maximum Transient Thermal Impedance for IGBT









Figure 27: Normalized Maximum Transient Thermal Impedance for Diode

Gate Charge Test Circuit & Waveform



Inductive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

