



Dimensions - mm

Drawing Not to Scale



- Ratings above 6.3A have a 0.8mm diameter lead
- With TR2 packaging code, lead wire length is 19.05mm

Time-Current Curves



| Packaging Code | |
|-----------------------|---|
| Product Number Prefix | Description |
| BK- | 100 fuses packed into a cardboard carton |
| BK1- | 1000 fuses packed into a poly bag |
| TR2- | 1500 Axial lead fuses packed into tape on a reel (19.05mm lead wire length) |

| Option Code | |
|-----------------------|---|
| Product Number Suffix | Description |
| -V | Axial leads - copper tinned wire with nickel plated brass overcaps (place before amp rating; e.g., GMC-V-2) |

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/electronics

© 2018 Eaton
All Rights Reserved
Printed in USA
Publication No. 4395 BU-SB11757
February 2018