


| Schottky   |                                              |                                                                    |                                | Ratings                        |      |      |               |
|------------|----------------------------------------------|--------------------------------------------------------------------|--------------------------------|--------------------------------|------|------|---------------|
| Symbol     | Definition                                   | Conditions                                                         |                                | min.                           | typ. | max. | Unit          |
| $V_{RSM}$  | max. non-repetitive reverse blocking voltage | $T_{VJ} = 25^{\circ}\text{C}$                                      |                                |                                |      | 150  | V             |
| $V_{RRM}$  | max. repetitive reverse blocking voltage     | $T_{VJ} = 25^{\circ}\text{C}$                                      |                                |                                |      | 150  | V             |
| $I_R$      | reverse current, drain current               | $V_R = 150\text{ V}$                                               | $T_{VJ} = 25^{\circ}\text{C}$  |                                |      | 200  | $\mu\text{A}$ |
|            |                                              | $V_R = 150\text{ V}$                                               | $T_{VJ} = 125^{\circ}\text{C}$ |                                |      | 2    | mA            |
| $V_F$      | forward voltage drop                         | $I_F = 10\text{ A}$                                                | $T_{VJ} = 25^{\circ}\text{C}$  |                                |      | 0.87 | V             |
|            |                                              | $I_F = 20\text{ A}$                                                |                                |                                |      | 0.98 | V             |
|            |                                              | $I_F = 10\text{ A}$                                                | $T_{VJ} = 125^{\circ}\text{C}$ |                                |      | 0.73 | V             |
|            |                                              | $I_F = 20\text{ A}$                                                |                                |                                |      | 0.85 | V             |
| $I_{FAV}$  | average forward current                      | $T_C = 155^{\circ}\text{C}$<br>rectangular $d = 0.5$               | $T_{VJ} = 175^{\circ}\text{C}$ |                                |      | 10   | A             |
| $V_{F0}$   | threshold voltage                            | } for power loss calculation only                                  |                                | $T_{VJ} = 175^{\circ}\text{C}$ |      | 0.54 | V             |
| $r_F$      | slope resistance                             |                                                                    |                                |                                |      | 11.4 | m $\Omega$    |
| $R_{thJC}$ | thermal resistance junction to case          |                                                                    |                                |                                |      | 2.4  | K/W           |
| $R_{thCH}$ | thermal resistance case to heatsink          |                                                                    |                                |                                | 0.5  |      | K/W           |
| $P_{tot}$  | total power dissipation                      | $T_C = 25^{\circ}\text{C}$                                         |                                |                                |      | 65   | W             |
| $I_{FSM}$  | max. forward surge current                   | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}; V_R = 0\text{ V}$ | $T_{VJ} = 45^{\circ}\text{C}$  |                                |      | 220  | A             |
| $C_J$      | junction capacitance                         | $V_R = 24\text{ V}$ $f = 1\text{ MHz}$                             | $T_{VJ} = 25^{\circ}\text{C}$  |                                | 53   |      | pF            |

| Package TO-220 |                              |                            | Ratings |      |      |      |
|----------------|------------------------------|----------------------------|---------|------|------|------|
| Symbol         | Definition                   | Conditions                 | min.    | typ. | max. | Unit |
| $I_{RMS}$      | RMS current                  | per terminal <sup>1)</sup> |         |      | 35   | A    |
| $T_{VJ}$       | virtual junction temperature |                            | -55     |      | 175  | °C   |
| $T_{op}$       | operation temperature        |                            | -55     |      | 150  | °C   |
| $T_{stg}$      | storage temperature          |                            | -55     |      | 150  | °C   |
| Weight         |                              |                            |         | 2    |      | g    |
| $M_D$          | mounting torque              |                            | 0.4     |      | 0.6  | Nm   |
| $F_C$          | mounting force with clip     |                            | 20      |      | 60   | N    |

### Product Marking



### Part description

D = Diode  
 S = Schottky Diode  
 A = low VF  
 20 = Current Rating [A]  
 C = Common Cathode  
 150 = Reverse Voltage [V]  
 PB = TO-220AB (3)


| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|-----------------|--------------------|---------------|----------|----------|
| Standard | DSA20C150PB     | DSA20C150PB        | Tube          | 50       | 503913   |


| Similar Part | Package        | Voltage class |
|--------------|----------------|---------------|
| DSA20C150PN  | TO-220ABFP (3) | 150           |

### Equivalent Circuits for Simulation


\* on die level

$T_{VJ} = 175^{\circ}\text{C}$

|                                                                                     |                    |                 |    |
|-------------------------------------------------------------------------------------|--------------------|-----------------|----|
|  |                    | <b>Schottky</b> |    |
| $V_{0 \max}$                                                                        | threshold voltage  | 0.54            | V  |
| $R_{0 \max}$                                                                        | slope resistance * | 8.2             | mΩ |

**Outlines TO-220**


| Dim. | Millimeter |       | Inches |       |
|------|------------|-------|--------|-------|
|      | Min.       | Max.  | Min.   | Max.  |
| A    | 4.32       | 4.82  | 0.170  | 0.190 |
| A1   | 1.14       | 1.39  | 0.045  | 0.055 |
| A2   | 2.29       | 2.79  | 0.090  | 0.110 |
| b    | 0.64       | 1.01  | 0.025  | 0.040 |
| b2   | 1.15       | 1.65  | 0.045  | 0.065 |
| C    | 0.35       | 0.56  | 0.014  | 0.022 |
| D    | 14.73      | 16.00 | 0.580  | 0.630 |
| E    | 9.91       | 10.66 | 0.390  | 0.420 |
| e    | 2.54       | BSC   | 0.100  | BSC   |
| H1   | 5.85       | 6.85  | 0.230  | 0.270 |
| L    | 12.70      | 13.97 | 0.500  | 0.550 |
| L1   | 2.79       | 5.84  | 0.110  | 0.230 |
| ØP   | 3.54       | 4.08  | 0.139  | 0.161 |
| Q    | 2.54       | 3.18  | 0.100  | 0.125 |




**Schottky**


Fig. 1 Maximum forward voltage drop characteristics




Fig. 2 Typ. reverse current  $I_R$  vs. reverse voltage  $V_R$




Fig. 3 Typ. junction capacitance  $C_T$  versus reverse voltage  $V_R$




Fig. 4 Avg: forward current  $I_{F(AV)}$  vs. case temperature  $T_C$




Fig. 5 Forward power loss characteristics




Fig. 6 Transient thermal impedance junction to case