

PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM7SZ14	SC70-5	-40°C to +125°C	SGM7SZ14XC5G/TR	SF7XX	Tape and Reel, 3000
	SOT-23-5	-40°C to +125°C	SGM7SZ14XN5G/TR	SF8XX	Tape and Reel, 3000

MARKING INFORMATION

NOTE: XX = Date Code.

YYY X X
 └──┬──┬──
 Date Code - Month
 Date Code - Year
 Serial Number

Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS

Supply Voltage Range, V_{CC} -0.5V to 6V
 DC Input Voltage Range, V_{IN} -0.5V to 6V
 DC Output Voltage Range, V_{OUT} -0.5V to 6V
 DC Input Diode Current, I_{IK} ($V_{IN} < -0.5V$) -50mA
 DC Output Diode Current, I_{OK} ($V_{OUT} < -0.5V$)..... -50mA
 DC Output Current, I_{OUT} $\pm 50mA$
 DC V_{CC} or Ground Current, I_{CC} or I_{GND} $\pm 50mA$
 Junction Temperature..... +150°C
 Storage Temperature Range..... -65°C to +150°C
 Lead Temperature (Soldering, 10s)..... +260°C
 ESD Susceptibility
 HBM..... 8000V
 MM..... 400V

RECOMMENDED OPERATING CONDITIONS

Operating Temperature Range..... -40°C to +125°C

OVERSTRESS CAUTION

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.


ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATIONS



PIN DESCRIPTION

PIN	NAME	FUNCTION
1	NC	No Connection.
2	A	Input. Unused input must be held high or low. It may not float.
3	GND	Ground.
4	Y	Output.
5	V _{CC}	Power Supply.

ELECTRICAL CHARACTERISTICS

(Full = -40°C to +125°C, typical values are at $T_A = +25^\circ\text{C}$, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	V_{CC} (V)	MIN	TYP	MAX	UNITS
General							
Power Supply Range	V_{CC}			1.65		5.50	V
Supply Voltage Data Retention				1.50		5.50	
Input Voltage	V_{IN}			0.00		5.50	V
Output Voltage	V_{OUT}			0.00		V_{CC}	V
DC Performance							
Positive Threshold Voltage	V_P		1.65	0.70	0.96	1.20	V
			1.80	0.75	1.04	1.30	
			2.30	1.00	1.30	1.55	
			3.00	1.35	1.65	1.95	
			4.50	2.05	2.40	2.70	
			5.50	2.60	2.92	3.25	
Negative Threshold Voltage	V_N		1.65	0.35	0.53	0.70	V
			1.80	0.40	0.57	0.75	
			2.30	0.60	0.77	0.95	
			3.00	0.85	1.04	1.20	
			4.50	1.35	1.56	1.75	
			5.50	1.65	1.90	2.10	
Hysteresis Voltage	V_H		1.65	0.10	0.43	0.70	V
			1.80	0.14	0.46	0.75	
			2.30	0.18	0.52	0.80	
			3.00	0.22	0.60	0.95	
			4.50	0.37	0.83	1.25	
			5.50	0.60	1.02	1.40	
High-Level Output Voltage	V_{OH}	$V_{IN} = V_{IL}$	$I_{OH} = -100\mu\text{A}$	1.65	1.62	1.65	V
				1.80	1.77	1.80	
				2.30	2.27	2.30	
				3.00	2.97	3.00	
				4.50	4.47	4.50	
			$I_{OH} = -4\text{mA}$ $I_{OH} = -8\text{mA}$ $I_{OH} = -16\text{mA}$ $I_{OH} = -24\text{mA}$ $I_{OH} = -32\text{mA}$	1.65	1.46	1.55	
				2.30	2.01	2.18	
				3.00	2.49	2.81	
				3.00	2.30	2.70	
				4.50	3.98	4.20	
Low-Level Output Voltage	V_{OL}	$V_{IN} = V_{IH}$	$I_{OL} = 100\mu\text{A}$	1.65		0.00	V
				1.80		0.00	
				2.30		0.00	
				3.00		0.00	
				4.50		0.00	
			$I_{OL} = 4\text{mA}$ $I_{OL} = 8\text{mA}$ $I_{OL} = 16\text{mA}$ $I_{OL} = 24\text{mA}$ $I_{OL} = 32\text{mA}$	1.65		0.06	
				2.30		0.09	
				3.00		0.16	
				3.00		0.24	
				4.50		0.29	
						0.12	
						0.18	
						0.33	
						0.51	
						0.58	
Input Leakage Current	I_{IN}	$V_{IN} = 5.5\text{V}, \text{GND}$	0 to 5.5		± 0.10	± 5	μA
Power-Off Leakage Current	I_{OFF}	V_{IN} or $V_{OUT} = 5.5\text{V}$	0		0.10	5	μA
Quiescent Supply Current	I_{CC}	$V_{IN} = 5.5\text{V}, \text{GND}$	1.65 to 5.5		0.10	10	μA


ELECTRICAL CHARACTERISTICS (continued)(Full = -40°C to +125°C, typical values are at T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
AC Performance						
Propagation Delay	t _{PHL} , t _{PLH}	V _{CC} = 1.65V		9.3		ns
		V _{CC} = 1.80V		7.6		
		V _{CC} = 2.50V ± 0.20V		4.7		
		V _{CC} = 3.30V ± 0.30V		3.6		
		V _{CC} = 5.00V ± 0.50V		2.7		
		V _{CC} = 3.30V ± 0.30V		4.2		
		V _{CC} = 5.00V ± 0.50V		3.2		
Input Capacitance	C _{IN}	V _{CC} = 0V		4.0		pF
Power Dissipation Capacitance ⁽²⁾	C _{PD}	V _{CC} = 3.30V		17.0		pF
		V _{CC} = 5.00V		19.0		

NOTES:

1. Unused input must be held high or low. It may not float.
2. C_{PD} is defined as the value of the internal equivalent capacitance which is derived from dynamic operating current consumption (I_{CCD}) at no output loading and operating at 50% duty cycle (see Figure 3). C_{PD} is related to dynamic operating current I_{CCD} by the expression: I_{CCD} = (C_{PD}) (V_{CC}) (f_{IN}) + (I_{CC,Static}).

TEST CIRCUITS



CL includes load and stray capacitance;
Input PRR = 1.0MHz; *t*_w = 500ns.

Figure 1. AC Test Circuit





Figure 2. AC Waveforms



Input = AC Waveform; *t*_r = *t*_f = 1.8ns;
PRR = 10MHz; Duty Cycle = 50%.

Figure 3. *I*_{CCD} Test Circuit



REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.



FEBRUARY 2021 – REV.A to REV.A.1	Page
Changed operating temperature range	All
Changes from Original (OCTOBER 2013) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

SOT-23-5





RECOMMENDED LAND PATTERN (Unit: mm)





Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950 BSC		0.037 BSC	
e1	1.900 BSC		0.075 BSC	
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

PACKAGE OUTLINE DIMENSIONS

SC70-5



RECOMMENDED LAND PATTERN (Unit: mm)




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.65 TYP		0.026 TYP	
e1	1.300 BSC		0.051 BSC	
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SOT-23-5	7"	9.5	3.20	3.20	1.40	4.0	4.0	2.0	8.0	Q3
SC70-5	7"	9.5	2.25	2.55	1.20	4.0	4.0	2.0	8.0	Q3

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

DD0002