


Ordering Information



| Device | Package Code | Packaging | 13" Tape and Reel | |
|----------------|--------------|-----------|-------------------|--------------------|
| | | | Quantity | Part Number Suffix |
| 74AHC126S14-13 | S14 | SO-14 | 2500/Tape & Reel | -13 |
| 74AHC126T14-13 | T14 | TSSOP-14 | 2500/Tape & Reel | -13 |


Pin Descriptions

| Pin Number | Pin Name | Function |
|------------|-----------------|---------------------------------|
| 1 | 1OE | Data Enable Input (Active High) |
| 2 | 1A | Data Input |
| 3 | 1Y | Data Output |
| 4 | 2OE | Data Enable Input (Active High) |
| 5 | 2A | Data Input |
| 6 | 2Y | Data Output |
| 7 | GND | Ground |
| 8 | 3Y | Data Output |
| 9 | 3A | Data Input |
| 10 | 3OE | Data Enable Input (Active High) |
| 11 | 4Y | Data Output |
| 12 | 4A | Data Input |
| 13 | 4OE | Data Enable Input (Active High) |
| 14 | V _{CC} | Supply Voltage |

Function Table

| Inputs | | Output |
|--------|---|--------|
| OE | A | Y |
| H | H | H |
| H | L | L |
| L | X | Z |

Logic Diagram



Absolute Maximum Ratings (Note 4) ($T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Symbol | Description | Rating | Unit |
|-----------|--|--------------|------------------|
| ESD HBM | Human Body Model ESD Protection | 2 | kV |
| ESD CDM | Charged Device Model ESD Protection | 1 | kV |
| ESD MM | Machine Model ESD Protection | 200 | V |
| V_{CC} | Supply Voltage Range | -0.5 to +7.0 | V |
| V_I | Input Voltage Range | -0.5 to +7.0 | V |
| I_{IK} | Input Clamp Current $V_I < -0.5\text{V}$ | -20 | mA |
| I_{OK} | Output Clamp Current $V_O < -0.5\text{V}$ | -20 | mA |
| I_{OK} | Output Clamp Current $V_O > V_{CC} + 0.5\text{V}$ | 25 | mA |
| I_O | Continuous Output Current $-0.5\text{V} < V_O < V_{CC} + 0.5\text{V}$ | ± 25 | mA |
| I_{CC} | Continuous Current Through V_{CC} | 75 | mA |
| I_{GND} | Continuous Current Through GND | -75 | mA |
| T_J | Operating Junction Temperature | -40 to +150 | $^\circ\text{C}$ |
| T_{STG} | Storage Temperature | -65 to +150 | $^\circ\text{C}$ |
| P_{TOT} | Total Power Dissipation | 500 | mW |

Note: 4. Stresses beyond the absolute maximum may result in immediate failure or reduced reliability. These are stress values and device operation should be within recommend values.

Recommended Operating Conditions (Note 5) ($T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Symbol | Parameter | Conditions | Min | Max | Unit |
|---------------------|------------------------------------|--|-----|----------|------------------|
| V_{CC} | Supply Voltage | — | 2.0 | 5.5 | V |
| V_I | Input Voltage | — | 0 | 5.5 | V |
| V_O | Output Voltage | — | 0 | V_{CC} | V |
| $\Delta t/\Delta V$ | Input Transition Rise or Fall Rate | $V_{CC} = 3.0\text{V to } 3.6\text{V}$ | — | 100 | ns/V |
| | | $V_{CC} = 4.5\text{V to } 5.5\text{V}$ | — | 20 | |
| T_A | Operating Free-Air Temperature | — | -40 | +125 | $^\circ\text{C}$ |

Note: 5. Unused inputs should be held at V_{CC} or Ground.

Electrical Characteristics

| Symbol | Parameter | Test Conditions | V _{CC} | T _A = -40°C to +85°C | | T _A = -40°C to +125°C | | Unit |
|-----------------|---------------------------|--|-----------------|---------------------------------|------|----------------------------------|------|------|
| | | | | Min | Max | Min | Max | |
| V _{IH} | High-Level Input Voltage | — | 2.0V | 1.5 | — | 1.5 | — | V |
| | | — | 3.0V | 2.1 | — | 2.1 | — | |
| | | — | 5.5V | 3.85 | — | 3.85 | — | |
| V _{IL} | Low-Level Input Voltage | — | 2.0V | — | 0.5 | — | 0.5 | V |
| | | — | 3.0V | — | 0.9 | — | 0.9 | |
| | | — | 5.5V | — | 1.65 | — | 1.65 | |
| V _{OH} | High-Level Output Voltage | I _{OH} = -50μA | 2.0V | 1.9 | — | 1.9 | — | V |
| | | I _{OH} = -50μA | 3.0V | 2.9 | — | 2.9 | — | |
| | | I _{OH} = -50μA | 4.5V | 4.4 | — | 4.4 | — | |
| | | I _{OH} = -4mA | 3.0V | 2.48 | — | 2.40 | — | |
| | | I _{OH} = -8mA | 4.5V | 3.80 | — | 3.70 | — | |
| V _{OL} | Low-Level Output Voltage | I _{OL} = 50μA | 2.0V | — | 0.1 | — | 0.1 | V |
| | | I _{OL} = 50μA | 3.0V | — | 0.1 | — | 0.1 | |
| | | I _{OL} = 50μA | 4.5V | — | 0.1 | — | 0.1 | |
| | | I _{OL} = 4mA | 3.0V | — | 0.44 | — | 0.55 | |
| | | I _{OL} = 8mA | 4.5V | — | 0.44 | — | 0.55 | |
| I _{OZ} | Z State Leakage Current | V _O = 0 to 5.5V V _I = GND or 5.5V | 5.5V | — | ±2.5 | — | ±10 | μA |
| I _I | Input Current | V _I = GND to 5.5V | 3.6V | — | ±1 | — | ±2 | μA |
| I _{CC} | Supply Current | V _I = GND or V _{CC} , I _O = 0 | 3.6V | — | 20 | — | 40 | μA |


Operating Characteristics

| Parameter | | Test Conditions | V _{CC} = 2.0V | V _{CC} = 3.3V | V _{CC} = 5V | Unit |
|-----------------|--|---|------------------------|------------------------|----------------------|------|
| | | | Typ | Typ | Typ | |
| C _{pd} | Power Dissipation Capacitance per Gate | f = 1MHz | 10.1 | 13.1 | 15 | pF |
| C _i | Input Capacitance | V _I = V _{CC} or GND | 4.0 | 4.0 | 4.0 | pF |

Switching Characteristics

| Symbol | Parameter | Test Conditions | V _{CC} | T _A = +25°C | | | -40°C to +85°C | | -40°C to +125°C | | Unit |
|------------------|--|------------------------------------|-----------------|------------------------|-----|------|----------------|------|-----------------|------|------|
| | | | | Min | Typ | Max | Min | Max | Min | Max | |
| t _{PD} | Propagation Delay A _N to Y _N | Figure 1 C _L = 15pF | 3.0V to 3.6V | 0.5 | 4.4 | 8.0 | 0.5 | 9.5 | 0.5 | 11.5 | ns |
| | | | 4.5V to 5.5V | 0.5 | 3.0 | 5.5 | 0.5 | 6.5 | 0.5 | 7.0 | |
| | | Figure 1 C _L = 50pF | 3.0V to 3.6V | 0.5 | 6.2 | 11.5 | 0.5 | 13.0 | 0.5 | 14.5 | |
| | | | 4.5V to 5.5V | 0.5 | 4.3 | 7.5 | 0.5 | 8.5 | 0.5 | 9.5 | |
| t _{EN} | Enable Time OE _N to Y _N | Figure 1 C _L = 15 pF | 3.0V to 3.6V | 0.5 | 4.7 | 8.0 | 0.5 | 9.5 | 0.5 | 11.5 | ns |
| | | | 4.5V to 5.5V | 0.5 | 3.3 | 5.1 | 0.5 | 6.0 | 0.5 | 7.5 | |
| | | Figure 1 C _L = 50pF | 3.0V to 3.6V | 0.5 | 6.8 | 11.5 | 0.5 | 13.0 | 0.5 | 14.5 | |
| | | | 4.5V to 5.5V | 0.5 | 4.7 | 7.1 | 0.5 | 8.0 | 0.5 | 9.0 | |
| t _{DIS} | Disable Time OE _N to Y _N | Figure 1 C _L = 15 pF | 3.0V to 3.6V | 0.5 | 6.7 | 9.7 | 0.5 | 11.5 | 0.5 | 12.5 | ns |
| | | | 4.5V to 5.5V | 0.5 | 4.8 | 6.8 | 0.5 | 8.0 | 0.5 | 8.5 | |
| | | Figure 1 C _L = 50pF | 3.0V to 3.6V | 0.5 | 9.6 | 13.2 | 0.5 | 15.0 | 0.5 | 16.5 | |
| | | | 4.5V to 5.5V | 0.5 | 6.8 | 8.8 | 0.5 | 10.0 | 0.5 | 11.0 | |

Parameter Measurement Information




| TEST | S1 |
|-------------------|------------|
| t_{PLH}/t_{PHL} | Open |
| t_{PLZ}/t_{PZL} | V_{load} |
| t_{PHZ}/t_{PZH} | GND |


| V_{CC} | Inputs | | V_M | V_{LOAD} | C_L | R_L | V_{Δ} |
|-----------------|----------|------------|------------|------------|----------|-------------|--------------|
| | V_I | t_r/t_f | | | | | |
| $3.3V \pm 0.3V$ | 3 V | $\leq 3ns$ | $V_{CC}/2$ | V_{CC} | 15,50 pF | 1K Ω | 0.3 V |
| $5V \pm 0.5V$ | V_{CC} | $\leq 3ns$ | $V_{CC}/2$ | V_{CC} | 15,50 pF | 1K Ω | 0.3 V |



Voltage Waveform Pulse Duration



Voltage Waveform Propagation Delay Times
Inverting and Non Inverting Outputs




Voltage Waveform Enable and Disable Times
Low and High Level Enabling

Figure 1. Load Circuit and Voltage Waveforms

- Notes:
- A. Includes test lead and test apparatus capacitance.
 - B. All pulses are supplied at pulse repetition rate ≤ 1 MHz.
 - C. Inputs are measured separately one transition per measurement.
 - D. t_{PLZ} and t_{PHZ} are the same as t_{dis} .
 - E. t_{PZL} and t_{PZH} are the same as t_{EN0} .
 - F. t_{PLH} and t_{PHL} are the same as t_{PD} .

Marking Information

(1) SO-14, TSSOP-14




| Part Number | Package |
|-------------|----------|
| 74AHC126S14 | SO-14 |
| 74AHC126T14 | TSSOP-14 |

Package Outline Dimensions (All dimensions in mm.)


Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SO-14



| SO-14 | | |
|----------------------|----------|------|
| Dim | Min | Max |
| A | 1.47 | 1.73 |
| A1 | 0.10 | 0.25 |
| A2 | 1.45 Typ | |
| B | 0.33 | 0.51 |
| D | 8.53 | 8.74 |
| E | 3.80 | 3.99 |
| e | 1.27 Typ | |
| H | 5.80 | 6.20 |
| L | 0.38 | 1.27 |
| θ | 0° | 8° |
| All Dimensions in mm | | |

TSSOP-14




| TSSOP-14 | | |
|----------------------|----------|------|
| Dim | Min | Max |
| a1 | 7° (4X) | |
| a2 | 0° | 8° |
| A | 4.9 | 5.10 |
| B | 4.30 | 4.50 |
| C | — | 1.2 |
| D | 0.8 | 1.05 |
| F | 1.00 Typ | |
| F1 | 0.45 | 0.75 |
| G | 0.65 Typ | |
| K | 0.19 | 0.30 |
| L | 6.40 Typ | |
| All Dimensions in mm | | |

Suggested Pad Layout


Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SO-14



| Dimensions | Value (in mm) |
|------------|---------------|
| X | 0.60 |
| Y | 1.50 |
| C1 | 5.4 |
| C2 | 1.27 |

TSSOP-14



| Dimensions | Value (in mm) |
|------------|---------------|
| X | 0.45 |
| Y | 1.45 |
| C1 | 5.9 |
| C2 | 0.65 |

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2019, Diodes Incorporated

www.diodes.com