

PCS3P6100A




Figure 1. Block Diagram

Table 1. PIN DESCRIPTION

Pin#	Pin Name	Type	Description
1	CLKIN	Input	External Reference Input frequency.
2	VSS	Power	Ground to entire chip.
3	ModOUT	Output	Modulated Frequency Output.
4	SS1%	Input	Spread Deviation Selection Pin -1. Refer to <i>Spread Deviation Selection Table</i> for details. Has an Internal pull-up resistor.
5	SS2%	Input	Spread Deviation Selection Pin -2. Refer to <i>Spread Deviation Selection Table</i> for details. Has an Internal pull-up resistor.
6	VDD	Power	Power to entire chip.

Table 2. SPREAD DEVIATION SELECTION TABLE

SS2%	SS1%	Frequency Deviation
L	L	±1.50%
L	H	±1.25%
H	L	±0.75%
H	H	±1.00%

Table 3. MODRATE TABLE

ModRate	20 MHz – 40 MHz	40 MHz – 130 MHz
	Fin / 336	Fin / 840

Table 4. ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Rating	Unit
V _{DD} , V _{IN}	Voltage on any pin with respect to Ground	-0.5 to +4.6	V
T _{STG}	Storage temperature	-65 to +125	°C
T _s	Max. Soldering Temperature (10 sec)	260	°C
T _J	Junction Temperature	150	°C
T _{DV}	Static Discharge Voltage (As per JEDEC STD22- A114-B)	2	KV

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

PCS3P6100A

Table 5. OPERATING CONDITIONS FOR 2.5 V AND 3.3 V SUPPLY VOLTAGE

Parameter	Description	Min	Max	Unit
V _{DD(2.5)}	Supply Voltage	2.375	2.625	V
V _{DD(3.3)}		3.0	3.6	
T _A	Operating Temperature (Ambient Temperature)	-40	+85	°C
C _L	Load Capacitance		15	pF

Table 6. DC ELECTRICAL CHARACTERISTICS FOR 2.5 V SUPPLY

Symbol	Parameter	Min	Typ	Max	Unit
V _{IL}	Input low voltage	V _{SS} - 0.3		0.7	V
V _{IH}	Input high voltage	1.7		V _{DD} + 0.3	V
I _{IL}	Input low current			-35	μA
I _{IH}	Input high current			35	μA
V _{OL}	Output low voltage (V _{DD} = 2.5 V, I _{OL} = 8 mA)			0.6	V
V _{OH}	Output high voltage (V _{DD} = 2.5 V, I _{OH} = -8 mA)	1.8			V
I _{DD}	Static supply current (Note 1)			4	mA
I _{CC}	Dynamic supply current (2.5 V and no load)		11		mA
V _{DD}	Operating voltage	2.375	2.5	2.625	V
t _{ON}	Power-up time (first locked cycle after power-up)			5	mS
C _{IN}	Input Capacitance		5		pF
Z _{OUT}	Output Impedance		40		Ω

1. CLKIN pin is pulled low.

Table 7. AC ELECTRICAL CHARACTERISTICS FOR 2.5 V SUPPLY

Symbol	Parameter	Min	Typ	Max	Unit
CLKIN	Input frequency	30		130	MHz
ModOUT	Output frequency	30		130	MHz
t _{LH} (Note 2)	Output rise time (measured from 0.7 V to 1.7 V)		2.2		nS
t _{HL} (Note 2)	Output fall time (measured from 1.7 V to 0.7 V)		1.2		nS
t _{JC}	Jitter (Cycle-to-cycle)		±250		pS
t _D	Output duty cycle	40	50	60	%

2. t_{LH} and t_{HL} are measured into a capacitive load of 15 pF.

PCS3P6100A

Table 8. DC ELECTRICAL CHARACTERISTICS FOR 3.3 V SUPPLY

Symbol	Parameter	Min	Typ	Max	Unit
V _{IL}	Input low voltage	VSS – 0.3		0.8	V
V _{IH}	Input high voltage	2.0		VDD + 0.3	V
I _{IL}	Input low current			–35	μA
I _{IH}	Input high current			35	μA
V _{OL}	Output low voltage (VDD = 3.3 V, I _{OL} = 8 mA)			0.4	V
V _{OH}	Output high voltage (VDD = 3.3 V, I _{OH} = –8 mA)	2.5			V
I _{DD}	Static supply current (Note 3)			4.5	mA
I _{CC}	Dynamic supply current (3.3 V and no load)		14		mA
V _{DD}	Operating voltage	3.0	3.3	3.6	V
t _{ON}	Power-up time (first locked cycle after power-up)			5	mS
C _{IN}	Input Capacitance		5		pF
Z _{OUT}	Output Impedance		40		Ω

3. CLKIN pin is pulled low.

Table 9. AC ELECTRICAL CHARACTERISTICS FOR 3.3 V SUPPLY

Symbol	Parameter	Min	Typ	Max	Unit
CLKIN	Input frequency	20		130	MHz
ModOUT	Output frequency	20		130	MHz
t _{LH} (Note 4)	Output rise time (measured from 0.8 V to 2.0 V)		1.5		nS
t _{HL} (Note 4)	Output fall time (measured at 2.0 V to 0.8 V)		1.1		nS
t _{JC}	Jitter (Cycle-to-cycle)		±225		pS
t _D	Output duty cycle	45	50	55	%

4. t_{LH} and t_{HL} are measured into a capacitive load of 15 pF.

DEVIATION CHARTS




Figure 2. Deviation vs. Output Frequency
(35 MHz to 130 MHz) at 25°C for VDD = 2.5 V




Figure 3. Deviation vs. Output Frequency
(20 MHz to 29 MHz) at 25°C for VDD = 3.3 V




Figure 4. Deviation vs. Output Frequency
(40 MHz to 130 MHz) at 25°C for VDD = 3.3 V

NOTE: Transition band is 30 MHz to 34 MHz for VDD = 2.5 V at 25°C. Deviation in this band is 2.64% ± 3%.
Transition band is 30 MHz to 39 MHz for VDD = 3.3 V at 25°C. Deviation in this band is 1.67% ± 45%.

DEVIATION CHARTS




Figure 5. Deviation vs. Output Frequency (35 MHz to 130 MHz) across Temperature for $V_{DD} = 2.5\text{ V} \pm 5\%$




Figure 6. Deviation vs. Output Frequency (20 MHz to 29 MHz) across Temperature for $V_{DD} = 3.3\text{ V} \pm 0.3\text{ V}$





Figure 7. Deviation vs. Output Frequency (40 MHz to 130 MHz) across Temperature for $V_{DD} = 3.3\text{ V} \pm 0.3\text{ V}$

NOTE: Transition band is 30 MHz to 34 MHz for $V_{DD} = 2.5\text{ V} \pm 5\%$, across -40°C to $+85^{\circ}\text{C}$. Deviation in this band is $1.8\% \pm 53\%$.
Transition band is 30 MHz to 39 MHz for $V_{DD} = 3.3\text{ V} \pm 0.3\text{ V}$, across -40°C to $+85^{\circ}\text{C}$. Deviation in this band is $1.67\% \pm 60\%$.

PCS3P6100A


PACKAGE DIMENSIONS

TSOT-23, 6 LEAD
CASE 419AF-01
ISSUE O




TOP VIEW

SYMBOL	MIN	NOM	MAX
A			1.00
A1	0.01	0.05	0.10
A2	0.80	0.87	0.90
b	0.30		0.45
c	0.12	0.15	0.20
D	2.90 BSC		
E	2.80 BSC		
E1	1.60 BSC		
e	0.95 TYP		
L	0.30	0.40	0.50
L1	0.60 REF		
L2	0.25 BSC		
θ	0°		8°



SIDE VIEW



END VIEW

Notes:


- (1) All dimensions are in millimeters. Angles in degrees.
- (2) Complies with JEDEC MO-193.

PCS3P6100A

Table 10. ORDERING INFORMATION

Part Number	Marking	Package Type	Temperature
PCS3I6100AG-06JR	AB2	6L-TSOT 23 (6L-TSOT 26), TAPE & REEL, Green	-40°C to +85°C

NOTE: A "microdot" placed at the end of last row of marking or just below the last row toward the center of package indicates Pb-free.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative

PCS3P6100A/D