

This document was generated on 05/16/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>679105700</u>		\sim
Status:	Active - Custom		AT a
Description: 0	$0.80mm$ (.310") Pitch, 5.75mm (.226") Height, PCI Express* Mini Card, 52 Circuit, Right Angle, SMT, $0.25\mu m$ (10 μ ") Gold (Au) Plating, Tape on Reel, Lead Free		Xelou
Documents:			
3D Model		Test Summary TS-67910-002 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	**************************************
Product Specification PS	<u>-67910-002 (PDF)</u>	, ,	Serie
General			image - Reference only
Product Family		Edge Card Connectors	
Series		67910	EU RoHS China RoHS
Component Type		Edgecard to PCB	ELV and RoHS
Product Name		Mini PCI Express*	Compliant
Floduct Name		Milli POLEXPIESS	REACH SVHC
Physical			Contains SVHC: No
(p)ower-(s)ignal Configuration		52s - 0p	Low-Halogen Status
Circuits (Loaded)		52s - op 52	Low-Halogen
Circuits (maximum)		52	Need more information on product
		52 50	environmental compliance?
Durability (mating cycles max)			chunonmental compliance i
Entry Angle		90° Angle (Side Entry)	Email productcompliance@molex.com
Keying to Mating Part		Yes	For a multiple part number RoHS Certificate
Material - Plating Mating		Gold	Compliance, <u>click here</u>
Material - Plating Termination		Tin	
PCB Locator		Yes	Please visit the <u>Contact Us</u> section for any
PCB Retention		Yes	non-product compliance questions.
PCB Thickness - Recom	mended	1.00mm (.039"), 1.20mm (.047")	
Packaging Type		Embossed Tape on Reel	
Pitch - Mating Interface		0.80mm (.031")	
Pitch - Termination Interface		0.80mm (.031")	Search Parts in this Series
Temperature Range - Operating		-40°C to +80°C	67910Series
Termination Interface: Style		Surface Mount	
Electrical			Mates With
Current - Maximum per Contact		1.1A	PCI Express Mini Card
Voltage - Maximum		50V	
Solder Process Dat	а		Use With 48099-5701 Latch with Pick and Place
Duration at Max. Process Temperature (seconds)		10	Cover, <u>48099-5702</u> Latch without Pick and
Lead-free Process Capability		Reflow Capable (SMT only)	Place Cover
Max. Cycles at Max. Process Temperature		2	
Process Temperature ma		260	
Material Info			
Reference - Drawin	g Numbers		
Product Specification	-	PS-67910-002	
Sales Drawing		SD-67910-004	
Test Summary		TS-67910-002	

* Mini PCI is a trademark of PCI-SIG® and * PCI Express is a registered trademark of PCI-SIG®

This document was generated on 05/16/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION