



Pin Assignments

(Top View)



DFN2015-6

(Top View)




DFN3020-6

Notes: 3. NC is "No Connection" which is recommended to be tied to ground.


Pin Descriptions

Pin Name	P/I/O	Description
Vdd	P/I	Power Supply Input
GND	P/I	Ground
Output	O	Output Pin
NC	NC	No Connected

Block Diagram



Typical Circuit



Notes: 4. C is for power stabilization and to strengthen the noise immunity, the recommended capacitance is 10nF~100nF.
R_L is the pull-up resistor, the recommended resistance is 10KΩ~100KΩ.

Absolute Maximum Ratings (at T_A= 25°C)

Symbol	Characteristics	Values	Unit
V _{dd}	Supply voltage	7	V
B	Magnetic flux density	Unlimited	
T _{ST}	Storage Temperature Range	-65 to +150	°C
P _D	Package Power Dissipation	230	mW
T _J	Maximum Junction Temperature	150	°C


Recommended Operating Conditions

Symbol	Parameter	Conditions	Rating	Unit
V _{dd}	Supply Voltage	Operating	2.5~5.5	V
T _A	Operating Temperature Range	Operating	-40 to +85	°C

Electrical Characteristics ($T_A = +25^\circ\text{C}$, $V_{dd} = 3\text{V}$; unless otherwise specified)

Symbol	Characteristic	Conditions	Min	Typ.	Max	Unit
V_{out}	Output On Voltage	$I_{out}=1\text{mA}$	—	0.1	0.3	V
I_{off}	Output Leakage Current	$V_{out}=5.5\text{V}$, Output off	—	<0.1	1	μA
$I_{dd(en)}$	Supply Current	Chip enable, $T_A = 25^\circ\text{C}$, $V_{dd} = 3\text{V}$	—	3	6	mA
$I_{dd(en)}$		Chip enable, $T_A = -40\sim 85^\circ\text{C}$, $V_{dd} = 2.5\sim 5.5\text{V}$	—	3	10	mA
$I_{dd(dis)}$		Chip disable, $T_A = 25^\circ\text{C}$, $V_{dd} = 3\text{V}$	—	5	10	μA
$I_{dd(dis)}$		Chip disable, $T_A = -40\sim 85^\circ\text{C}$, $V_{dd} = 2.5\sim 5.5\text{V}$	—	5	18	μA
$I_{dd(ave)}$		Average supply current, $T_A = 25^\circ\text{C}$, $V_{dd} = 3\text{V}$	—	8	16	μA
$I_{dd(ave)}$		Average supply current, $T_A = -40\sim 85^\circ\text{C}$, $V_{dd} = 2.5\sim 5.5\text{V}$	—	8	28	μA
F_c	Chopping Frequency	For design information only	—	300	—	KHz
T_{wake}	Awake Time	(Note 5)	—	75	150	μs
T_{period}	Period	(Note 5)	—	75	150	ms
D.C.	Duty Cycle		—	0.1	—	%

Notes: 5. When power is initially on, the operating V_{dd} (2.5V to 5.5V) must be applied to be guaranteed for the output sampling. The output state is valid after the second operating phase (typical 150ms).




Magnetic Characteristics ($T_A=25^\circ\text{C}$, $V_{DD}=3\text{V}$, Note 6, 7)

(1mT=10 Gauss)


Symbol	Characteristic	Min	Typ.	Max	Unit
Bops(south pole to brand side)	Operate Point	-	28	55	Gauss
Bopn(north pole to brand side)		-55	-28	-	
Brps(south pole to brand side)	Release Point	10	20	-	
Brpn(north pole to brand side)		-	-20	-10	
Bhy($ B_{opx} - B_{rpx} $)	Hysteresis	5	8	-	

Notes: 6. Typical data is at $T_A = 25^\circ\text{C}$, $V_{DD} = 3\text{V}$, and for design information only.
7. Operating point and release point will vary with supply voltage and operating temperature.



Performance Characteristics


T_A ($^\circ\text{C}$)	25	50	60	70	80	85	90	100	110	120	130	140	150
PD (mW)	230	184	166	147	129	120	110	92	74	55	37	18	0



Marking Information

(1) DFN2015-6

(Top View)




Pin 1 indicator
XX : Identification Code
Y : Year : 0~9
W : Week : A~Z : 1~26 week;
a~z : 27~52 week; z represents
52 and 53 week
X : A~Z : Green

Part Number	Package	Identification Code
AH1822	DFN2015-6	K7

(2) DFN3020-6

(Top View)




Pin 1 indicator
XX : Identification Code
Y : Year : 0~9
W : Week : A~Z : 1~26 week;
a~z : 27~52 week; z represents
52 and 53 week
X : A~Z : Green


Part Number	Package	Identification Code
AH1822	DFN3020-6	K8

Package Information (All Dimensions in mm)

(1) Package type: DFN2015-6




(2) Package type: DFN3020-6





Taping Orientation

(1) DFN2015-6



(2) DFN3020-6



Notes: 8. The taping orientation of the other package type can be found on our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.