





om Arrow.com.


A	2.00	[.079]	+ 0.20	[.008]
B	1.25	[.049]	+ 0.20	[.008]
C	0.90	[.035]	+ 0.20	[.008]
D	0.51	[.020]	+ 0.25	[.010]



LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.763
([.030] to this dimension.)



RECOMMENDED SOLDERING CONDITIONS

ELECTRICAL CHARACTERISTICS:			
Z @ 100MHz (Ω)		DCR (Ω)	Rated Current
Nominal	2000		
Minimum	1500		
Maximum	2500	0.500	300 mA

NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL, PAPER TAPE.
2. TERMINATION FINISH IS 100% TIN.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
4. OPERATING TEMP. RANGE: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$ (INCLUDING SELF-HEATING)

[illegible]

This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.

Laird

FREQUENCY

Z R

AGILENT E4991A RF Impedance/Material Analyzer
HP 16194A Test Fixture. TEST REF. 3228

2002/95/EC

FREQUENCY (MHZ)

 α x^{-1}

PROJECT/PART NUMBER:	HZ0805C202R-10
DATE:	04/03/04
CAD #	HZ0805C202R-10-D

NTS	SHEET:	2 of 2
PART TYPE:	CO-FIRE	TMB
DRAWN BY		