

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

## ABSOLUTE MAXIMUM RATINGS

V<sub>DD</sub> to GND .....-0.3V to +6V  
 IN, OUT, COM, OS, CLK,  $\overline{\text{SHDN}}$  .....-0.3V to (V<sub>DD</sub> + 0.3V)  
 OUT Short-Circuit Duration .....1s  
 Continuous Power Dissipation (T<sub>A</sub> = +70°C)  
   8-Pin  $\mu\text{MAX}$  (derate 4.1mW/°C above +70°C) .....330mW  
   8-Pin PDIP (derate 6.90mW/°C above +70°C) .....552mW

### Operating Temperature Ranges

MAX742 \_C\_A .....0°C to +70°C  
 MAX742 \_E\_A .....-40°C to +85°C  
 Storage Temperature Range .....-65°C to +160°C  
 Lead Temperature (soldering, 10s) .....+300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## ELECTRICAL CHARACTERISTICS—MAX7426

(V<sub>DD</sub> = +5V, filter output measured at OUT, 10k $\Omega$  || 50pF load to GND at OUT,  $\overline{\text{SHDN}}$  = V<sub>DD</sub>, OS = COM, 0.1 $\mu\text{F}$  from COM to GND, f<sub>CLK</sub> = 100kHz, T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.)

| PARAMETER                                       | SYMBOL                           | CONDITIONS  | MIN                      | TYP                    | MAX                      | UNITS  |
|---|----------------------------------|---|--------------------------|------------------------|--------------------------|--------|
| FILTER  |                                  |   |                          |                        |                          |        |
| Corner-Frequency Range                          | f <sub>C</sub>                   | (Note 1)  | 0.001 to 9               |                        |                          | kHz    |
| Clock-to-Corner Ratio                           | f <sub>CLK</sub> /f <sub>C</sub> |   | 100:1                    |                        |                          |        |
| Clock-to-Corner Tempco                          |                                  |   | 10                       |                        |                          | ppm/°C |
| Output Voltage Range                            |                                  |   | 0.25                     | V <sub>DD</sub> - 0.25 |                          | V      |
| Output Offset Voltage                           | V <sub>OFFSET</sub>              | V <sub>IN</sub> = V <sub>COM</sub> = V <sub>DD</sub> / 2                        | ±4                       |                        | ±25                      | mV     |
| DC Insertion Gain with Output Offset Removed    |                                  | V <sub>COM</sub> = V <sub>DD</sub> / 2 (Note 2)                                 | 0                        | 0.2                    | 0.4                      | dB     |
| Total Harmonic Distortion plus Noise            | THD+N                            | f <sub>IN</sub> = 200Hz, V <sub>IN</sub> = 4Vp-p, measurement bandwidth = 22kHz | -81                      |                        |                          | dB     |
| Offset Voltage Gain                             | A <sub>OS</sub>                  | OS to OUT   | +1                       |                        |                          | V/V    |
| COM Voltage Range                               | V <sub>COM</sub>                 | Input, COM externally driven  | $\frac{V_{DD}}{2} - 0.5$ | $\frac{V_{DD}}{2}$     | $\frac{V_{DD}}{2} + 0.5$ | V      |
|   |                                  | Output, COM internally driven   | $\frac{V_{DD}}{2} - 0.2$ | $\frac{V_{DD}}{2}$     | $\frac{V_{DD}}{2} + 0.2$ |        |
| Input Voltage Range at OS                       | V <sub>OS</sub>                  | Measured with respect to COM  | ±0.1                     |                        |                          | V      |
| Input Resistance at COM                         | R <sub>COM</sub>                 |   | 90                       | 130                    |                          | kΩ     |
| Clock Feedthrough                               |                                  | T <sub>A</sub> = +25°C  | 5                        |                        |                          | mVp-p  |
| Resistive Output Load Drive                     | R <sub>L</sub>                   |   | 10                       | 1                      |                          | kΩ     |
| Maximum Capacitive Load at OUT                  | C <sub>L</sub>                   |   | 50                       | 500                    |                          | pF     |
| Input Leakage Current at COM                    |                                  | $\overline{\text{SHDN}}$ = GND, V <sub>COM</sub> = 0 to V <sub>DD</sub>         | ±0.2                     |                        | ±10                      | μA     |
| Input Leakage Current at OS                     |                                  | V <sub>OS</sub> = 0 to V <sub>DD</sub>  | ±0.2                     |                        | ±10                      | μA     |
| CLOCK   |                                  |   |                          |                        |                          |        |
| Internal Oscillator Frequency                   | f <sub>OSC</sub>                 | C <sub>OSC</sub> = 1000pF (Note 3)  | 13.5                     | 17.5                   | 21.5                     | kHz    |
| Clock Output Current (internal oscillator mode) | I <sub>CLK</sub>                 |   | ±8                       |                        | ±12.5                    | μA     |
| Clock Input High                                | V <sub>IH</sub>                  |   | 4.5                      |                        |                          | V      |
| Clock Input Low                                 | V <sub>IL</sub>                  |   | 0.5                      |                        |                          | V      |

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

MAX7426/MAX7427

## ELECTRICAL CHARACTERISTICS—MAX7426 (continued)

( $V_{DD} = +5V$ , filter output measured at OUT,  $10k\Omega$  ||  $50pF$  load to GND at OUT,  $\overline{SHDN} = V_{DD}$ , OS = COM,  $0.1\mu F$  from COM to GND,  $f_{CLK} = 100kHz$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                               | SYMBOL                | CONDITIONS                            | MIN | TYP       | MAX      | UNITS   |
|---|-----------------------|---------------------------------------|-----|-----------|----------|---------|
| <b>POWER REQUIREMENTS</b>               |                       |                                       |     |           |          |         |
| Supply Voltage                          | $V_{DD}$              |                                       | 4.5 |           | 5.5      | V       |
| Supply Current                          | $I_{DD}$              | Operating mode, no load               |     | 0.8       | 1.0      | mA      |
| Shutdown Current                        | $I_{\overline{SHDN}}$ | $\overline{SHDN} = GND$               |     | 0.2       | 1        | $\mu A$ |
| Power-Supply Rejection Ratio            | PSRR                  | Measured at DC                        |     | 70        |          | dB      |
| <b>SHUTDOWN</b>                         |                       |                                       |     |           |          |         |
| $\overline{SHDN}$ Input High            | $V_{SDH}$             |                                       | 4.5 |           |          | V       |
| $\overline{SHDN}$ Input Low             | $V_{SDL}$             |                                       |     |           | 0.5      | V       |
| $\overline{SHDN}$ Input Leakage Current |                       | $V_{\overline{SHDN}} = 0$ to $V_{DD}$ |     | $\pm 0.2$ | $\pm 10$ | $\mu A$ |

## ELECTRICAL CHARACTERISTICS—MAX7427

( $V_{DD} = +3V$ , filter output measured at OUT pin,  $10k\Omega$  ||  $50pF$  load to GND at OUT,  $\overline{SHDN} = V_{DD}$ , OS = COM,  $0.1\mu F$  from COM to GND,  $f_{CLK} = 100kHz$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                                    | SYMBOL        | CONDITIONS   | MIN                      | TYP                | MAX                      | UNITS           |
|--|---------------|--|--------------------------|--------------------|--------------------------|-----------------|
| <b>FILTER CHARACTERISTICS</b>                |               |  |                          |                    |                          |                 |
| Corner-Frequency Range                       | $f_C$         | (Note 1)   |                          | 0.001 to 12        |                          | kHz             |
| Clock-to-Corner Ratio                        | $f_{CLK}/f_C$ |  |                          | 100:1              |                          |                 |
| Clock-to-Corner Tempco                       |               |  |                          | 10                 |                          | ppm/ $^\circ C$ |
| Output Voltage Range                         |               |  | 0.25                     |                    | $V_{DD} - 0.25$          | V               |
| Output Offset Voltage                        | $V_{OFFSET}$  | $V_{IN} = V_{COM} = V_{DD} / 2$  |                          | $\pm 4$            | $\pm 25$                 | mV              |
| DC Insertion Gain with Output Offset Removed |               | $V_{COM} = V_{DD} / 2$ (Note 2)  | 0                        | 0.2                | 0.4                      | dB              |
| Total Harmonic Distortion plus Noise         | THD+N         | $f_{IN} = 200Hz$ , $V_{IN} = 2.5V_{p-p}$ , measurement bandwidth = 22kHz |                          | -79                |                          | dB              |
| Offset Voltage Gain                          | $A_{OS}$      | OS to OUT  |                          | +1                 |                          | V/V             |
| COM Voltage Range                            | $V_{COM}$     |  | $\frac{V_{DD}}{2} - 0.1$ | $\frac{V_{DD}}{2}$ | $\frac{V_{DD}}{2} + 0.1$ | V               |
| Input Voltage Range at OS                    | $V_{OS}$      | Measured with respect to COM   |                          | $\pm 0.1$          |                          | V               |
| Input Resistance at COM                      | $R_{COM}$     |  | 90                       | 130                |                          | $k\Omega$       |
| Clock Feedthrough                            |               | $T_A = +25^\circ C$  |                          | 3                  |                          | mVp-p           |
| Resistance Output Load Drive                 | $R_L$         |  | 10                       | 1                  |                          | $k\Omega$       |
| Maximum Capacitive Load at OUT               | $C_L$         |  | 50                       | 500                |                          | pF              |
| Input Leakage Current at COM                 |               | $\overline{SHDN} = GND$ , $V_{COM} = 0$ to $V_{DD}$                      |                          | $\pm 0.2$          | $\pm 10$                 | $\mu A$         |
| Input Leakage Current at OS                  |               | $V_{OS} = 0$ to $V_{DD}$   |                          | $\pm 0.2$          | $\pm 10$                 | $\mu A$         |

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

## ELECTRICAL CHARACTERISTICS—MAX7427 (continued)

( $V_{DD} = +3V$ , filter output measured at OUT pin,  $10k\Omega$  ||  $50pF$  load to GND at OUT,  $\overline{SHDN} = V_{DD}$ , OS = COM,  $0.1\mu F$  from COM to GND,  $f_{CLK} = 100kHz$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                                       | SYMBOL                | CONDITIONS                            | MIN  | TYP       | MAX        | UNITS   |
|---|-----------------------|---------------------------------------|------|-----------|------------|---------|
| <b>CLOCK</b>                                    |                       |                                       |      |           |            |         |
| Internal Oscillator Frequency                   | $f_{OSC}$             | $C_{OSC} = 1000pF$ (Note 3)           | 13.5 | 17.5      | 21.5       | kHz     |
| Clock Output Current (internal oscillator mode) | $I_{CLK}$             | $V_{CLK} = 0$ or $3V$                 |      | $\pm 7.5$ | $\pm 12.5$ | $\mu A$ |
| Clock Input High                                | $V_{IH}$              |                                       | 2.5  |           |            | V       |
| Clock Input Low                                 | $V_{IL}$              |                                       |      |           | 0.5        | V       |
| <b>POWER REQUIREMENTS</b>                       |                       |                                       |      |           |            |         |
| Supply Voltage                                  | $V_{DD}$              |                                       | 2.7  |           | 3.6        | V       |
| Supply Current                                  | $I_{DD}$              | Operating mode, no load               |      | 0.75      | 1.0        | mA      |
| Shutdown Current                                | $I_{\overline{SHDN}}$ | $\overline{SHDN} = GND$               |      | 0.2       | 1          | $\mu A$ |
| Power-Supply Rejection Ratio                    | PSRR                  | Measured at DC                        |      | 70        |            | dB      |
| <b>SHUTDOWN</b>                                 |                       |                                       |      |           |            |         |
| $\overline{SHDN}$ Input High                    | $V_{SDH}$             |                                       | 2.5  |           |            | V       |
| $\overline{SHDN}$ Input Low                     | $V_{SDL}$             |                                       |      |           | 0.5        | V       |
| $\overline{SHDN}$ Input Leakage Current         |                       | $V_{\overline{SHDN}} = 0$ to $V_{DD}$ |      | $\pm 0.2$ | $\pm 10$   | $\mu A$ |

## ELLIPTIC FILTER CHARACTERISTICS ( $r = 1.25$ )

( $V_{DD} = +5V$  for MAX7426,  $V_{DD} = +3V$  for MAX7427, filter output measured at OUT,  $10k\Omega$  ||  $50pF$  load to GND at OUT,  $\overline{SHDN} = V_{DD}$ ,  $V_{COM} = V_{OS} = V_{DD} / 2$ ,  $f_{CLK} = 100kHz$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .) (Note 3)

| PARAMETER  | CONDITIONS         | MIN  | TYP   | MAX | UNITS |
|--|--------------------|------|-------|-----|-------|
| Insertion Gain with DC Gain Error Removed (Note 4) | $f_{IN} = 0.38f_C$ | -0.4 | -0.2  | 0.4 | dB    |
|  | $f_{IN} = 0.68f_C$ | -0.4 | 0.2   | 0.4 |       |
|  | $f_{IN} = 0.87f_C$ | -0.4 | -0.2  | 0.4 |       |
|  | $f_{IN} = 0.97f_C$ | -0.4 | 0.2   | 0.4 |       |
|  | $f_{IN} = f_C$     | -0.7 | -0.2  | 0.2 |       |
|  | $f_{IN} = 1.25f_C$ |      | -38.5 | -34 |       |
|  | $f_{IN} = 1.43f_C$ |      | -37.2 | -35 |       |
|  | $f_{IN} = 3.25f_C$ |      | -37.2 | -35 |       |

**Note 1:** The maximum  $f_C$  is defined as the clock frequency  $f_{CLK} = 100 \times f_C$  at which the peak SINAD drops to 68dB with a sinusoidal input at  $0.2f_C$ .

**Note 2:** DC insertion gain is defined as  $\Delta V_{OUT} / \Delta V_{IN}$ .

**Note 3:**  $f_{OSC} (kHz) \approx 17.5 \times 10^3 / C_{OSC}$  ( $C_{OSC}$  in pF).






**Note 4:** The input frequencies,  $f_{IN}$ , are selected at the peaks and troughs of the ideal elliptic frequency responses.

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

## Typical Operating Characteristics

( $V_{DD} = +5V$  for MAX7426,  $V_{DD} = +3V$  for MAX7427,  $f_{CLK} = 100kHz$ ,  $\overline{SHDN} = V_{DD}$ ,  $V_{COM} = V_{OS} = V_{DD} / 2$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)

MAX7426/MAX7427



# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

## Typical Operating Characteristics (continued)

(V<sub>DD</sub> = +5V for MAX7426, V<sub>DD</sub> = +3V for MAX7427, f<sub>CLK</sub> = 100kHz,  $\overline{\text{SHDN}}$  = V<sub>DD</sub>, V<sub>COM</sub> = V<sub>OS</sub> = V<sub>DD</sub> / 2, T<sub>A</sub> = +25°C, unless otherwise noted.)





Table 1. THD + Noise Test Conditions







| LABEL | f <sub>IN</sub><br>(Hz) | f <sub>C</sub><br>(kHz) | f <sub>CLK</sub><br>(kHz) | MEASUREMENT<br>BANDWIDTH (kHz) |
|-------|-------------------------|-------------------------|---------------------------|--------------------------------|
| A     | 200                     | 1                       | 100                       | 22                             |
| B     | 1k                      | 5                       | 500                       | 80                             |

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor

## Typical Operating Characteristics (continued)

( $V_{DD} = +5V$  for MAX7426,  $V_{DD} = +3V$  for MAX7427,  $f_{CLK} = 100kHz$ ,  $\overline{SHDN} = V_{DD}$ ,  $V_{COM} = V_{OS} = V_{DD} / 2$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)

MAX7426/MAX7427



# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

## Pin Description

| PIN | NAME            | FUNCTION  |
|-----|-----------------|---|
| 1   | COM             | Common Input Pin. Biased internally at midsupply. Bypass externally to GND with a 0.1µF capacitor. To override internal biasing, drive with an external supply.                             |
| 2   | IN              | Filter Input  |
| 3   | GND             | Ground  |
| 4   | V <sub>DD</sub> | Positive Supply Input, +5V for MAX7426 or +3V for MAX7427   |
| 5   | OUT             | Filter Output   |
| 6   | OS              | Offset Adjust Input. To adjust output offset, bias OS with a resistive voltage-divider between an external supply and ground. Connect OS to COM if no offset adjustment is needed.          |
| 7   | SHDN            | Shutdown Input. Drive low to enable shutdown mode; drive high or connect to V <sub>DD</sub> for normal operation.   |
| 8   | CLK             | Clock Input. Connect an external capacitor (C <sub>OSC</sub> ) from CLK to GND to set the internal oscillator frequency. To override the internal oscillator, connect to an external clock. |

## Detailed Description

The MAX7426/MAX7427 family of 5th-order, elliptic, lowpass filters provides sharp rolloff with good stopband rejection. All parts operate with a 100:1 clock-to-corner frequency ratio.

Most SCFs are designed with biquadratic sections. Each section implements two pole-zero pairs, and the sections can be cascaded to produce higher-order filters. The advantage to this approach is ease of design. However, this type of design is highly sensitive to component variations if any section's Q is high. The MAX7426/MAX7427 use an alternative approach, which is to emulate a passive network using switched-capacitor integrators with summing and scaling. The passive network may be synthesized using CAD programs or may be found in many filter books. Figure 1 shows a basic 5th-order ladder elliptic filter structure.

A switched-capacitor filter that emulates a passive ladder filter retains many of the same advantages. The component sensitivity of a passive ladder filter is low when compared to a cascaded biquadratic design, because each component affects the entire filter shape rather than a single pole-zero pair. In other words, a




Figure 1. 5th-Order Ladder Elliptic Filter Network

mismatched component in a biquadratic design has a concentrated error on its respective poles, while the same mismatch in a ladder filter design spreads its error over all poles.

### Elliptic Characteristics

Lowpass elliptic filters such as the MAX7426/MAX7427 provide the steepest possible rolloff with frequency of the four most common filter types (Butterworth, Bessel, Chebyshev, and elliptic). The high Q value of the poles near the passband edge combined with the stopband zeros allow for the sharp attenuation characteristic of elliptic filters, making these devices ideal for anti-aliasing and post-DAC filtering in single-supply systems (see the *Anti-Aliasing and Post-DAC Filtering* section).

In the frequency domain (Figure 2), the first transmission zero causes the filter's amplitude to drop to a minimum level. Beyond this zero, the response rises as the frequency increases until the next transmission zero. The stopband begins at the stopband frequency,  $f_s$ . At frequencies above  $f_s$ , the filter's gain does not exceed the gain at  $f_s$ . The corner frequency,  $f_c$ , is defined as the point where the filter output attenuation falls just below the passband ripple. The transition ratio ( $r$ ) is defined as the ratio of the stopband frequency to the corner frequency:

$$r = f_s / f_c$$

The MAX7426/MAX7427 have a transition ratio of 1.25 and typically 37dB of stopband rejection.

### Clock Signal

#### External Clock

These SCFs are designed for use with external clocks that have a 40% to 60% duty cycle. When using an external clock, drive the CLK pin with a CMOS gate

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

MAX7426/MAX7427




Figure 2. Elliptic Filter Response

powered from 0 to  $V_{DD}$ . Varying the rate of the external clock adjusts the corner frequency of the filter:

$$f_C = \frac{f_{CLK}}{100}$$

## Internal Clock

When using the internal oscillator, the capacitance ( $C_{OSC}$ ) on CLK determines the oscillator frequency:

$$f_{OSC}(kHz) = \frac{17.5 \times 10^3}{C_{OSC}(pF)}$$

Since  $C_{OSC}$  is in the low picofarads, minimize the stray capacitance at CLK so that it does not affect the internal oscillator frequency. Varying the rate of the internal oscillator adjusts the filter's corner frequency by a 100:1 clock-to-corner frequency ratio. For example, an internal oscillator frequency of 100kHz produces a nominal corner frequency of 1kHz.

## Input Impedance vs. Clock Frequencies

The MAX7426/MAX7427's input impedance is effectively that of a switched-capacitor resistor (see the following equation), and is inversely proportional to frequency. The input impedance values determined by the equation represent the average input impedance, since the input current is not continuous. As a rule, use a driver with an output resistance less than 10% of the filter's input impedance.




Figure 3. Offset Adjustment Circuit

Estimate the input impedance of the filter by using the following formula:

$$Z_{IN} = \frac{1}{f_{CLK} \times C_{IN}}$$

where  $f_{CLK}$  = clock frequency and  $C_{IN}$  = 1pF.

## Low-Power Shutdown Mode

The MAX7426/MAX7427 have a shutdown mode that is activated by driving  $\overline{SHDN}$  low. In shutdown mode, the filter supply current reduces to 0.2µA, and the output of the filter becomes high impedance. For normal operation, drive  $\overline{SHDN}$  high or connect to  $V_{DD}$ .

## Applications Information

### Offset (OS) and Common-Mode (COM) Input Adjustment

COM sets the common-mode input voltage and is biased at midsupply with an internal resistor-divider. If the application does not require offset adjustment, connect OS to COM. For applications where offset adjustment is required, apply an external bias voltage through a resistor-divider network to OS, as shown in Figure 3. For applications that require DC level shifting, adjust OS with respect to COM. (**Note:** Do not leave OS unconnected.) The output voltage is represented by these equations:

$$V_{OUT} = (V_{IN} - V_{COM}) + V_{OS}$$

$$V_{COM} = \frac{V_{DD}}{2} \text{ (typical)}$$

where  $(V_{IN} - V_{COM})$  is lowpass filtered by the SCF and OS is added at the output stage. See the *Electrical*



# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters




Figure 4. Dual-Supply Operation

Characteristics table for the input voltage range of COM and OS. Changing the voltage on COM or OS significantly from midsupply reduces the dynamic range.

## Power Supplies

The MAX7426 operates from a single +5V supply, and the MAX7427 operates from a single +3V supply. Bypass  $V_{DD}$  to GND with a  $0.1\mu\text{F}$  capacitor. If dual supplies are required, connect COM to the system ground and GND to the negative supply. Figure 4 shows an example of dual-supply operation. Single-supply and dual-supply performance are equivalent.

For either single-supply or dual-supply operation, drive CLK and SHDN from GND ( $V_-$  in dual-supply operation) to  $V_{DD}$ . Use the MAX7427 for  $\pm 2.5$ , and use the MAX7426 for  $\pm 1.5$ . For  $\pm 5$ V dual-supply applications, refer to the MAX291/MAX292/MAX295/MAX296 and MAX293/MAX294/MAX297 data sheets.

## Input Signal Amplitude Range

The optimal input signal range is determined by observing the voltage level at which the signal-to-noise plus distortion (SINAD) ratio is maximized for a given corner frequency. The *Typical Operating Characteristics* show the THD + Noise response as the input signal's peak-to-peak amplitude is varied.

## Anti-Aliasing and Post-DAC Filtering

When using the MAX7426/MAX7427 for anti-aliasing or post-DAC filtering, synchronize the DAC (or ADC) and the filter clocks. If the clocks are not synchronized, beat frequencies may alias into the desired passband.

## Harmonic Distortion

Harmonic distortion arises from nonlinearities within the filter. These nonlinearities generate harmonics when a pure sine wave is applied to the filter input. Table 2 lists typical harmonic distortion values with a  $10\text{k}\Omega$  load at  $T_A = +25^\circ\text{C}$ .

## Chip Information

TRANSISTOR COUNT: 1457  
PROCESS: BiCMOS

Table 2. Typical Harmonic Distortion


| FILTER  | $f_{\text{CLK}}$<br>(kHz) | $f_{\text{IN}}$<br>(Hz) | $V_{\text{IN}}$<br>(Vp-p) | TYPICAL HARMONIC DISTORTION (dB) |     |     |     |
|---------|---------------------------|-------------------------|---------------------------|----------------------------------|-----|-----|-----|
|         |                           |                         |                           | 2nd                              | 3rd | 4th | 5th |
| MAX7426 | 500                       | 1k                      | 4                         | -71                              | -73 | -90 | -82 |
|         | 100                       | 200                     |                           | -88                              | -86 | -92 | -88 |
| MAX7427 | 500                       | 1k                      | 2                         | -87                              | -86 | -90 | -90 |
|         | 100                       | 200                     |                           | -90                              | -87 | -90 | -90 |

# 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters


## Package Information

MAX7426/MAX7427


8LUMAXD.EPS




TOP VIEW



BOTTOM VIEW



FRONT VIEW



SIDE VIEW

|    | INCHES |       | MILLIMETERS |       | JEDEC  |       |      |      |
|----|--------|-------|-------------|-------|--------|-------|------|------|
|    | MIN    | MAX   | MIN         | MAX   | MIN    | MAX   | MIN  | MAX  |
| A  | 0.037  | 0.043 | 0.94        | 1.10  | ---    | 0.043 | ---  | 1.10 |
| A1 | 0.002  | 0.006 | 0.05        | 0.15  | 0.002  | 0.006 | 0.05 | 0.15 |
| B  | 0.010  | 0.014 | 0.25        | 0.36  | 0.010  | 0.016 | 0.25 | 0.40 |
| C  | 0.005  | 0.007 | 0.13        | 0.18  | 0.005  | 0.009 | 0.13 | 0.23 |
| D  | 0.116  | 0.120 | 2.95        | 3.05  | 0.114  | 0.122 | 2.9  | 3.1  |
| e  | 0.0256 | BSC   | 0.65        | BSC   | 0.0256 | BSC   | 0.64 | BSC  |
| E  | 0.116  | 0.120 | 2.95        | 3.05  | 0.114  | 0.122 | 2.9  | 3.1  |
| H  | 0.188  | 0.198 | 4.78        | 5.03  | 0.193  | BSC   | 4.9  | BSC  |
| L  | 0.016  | 0.026 | 0.41        | 0.66  | 0.016  | 0.027 | 0.40 | 0.70 |
| α  | 0°     | 6°    | 0°          | 6°    | 0°     | 6°    | 0°   | 6°   |
| *X | 0.087  | 0.099 | 2.210       | 2.515 |        |       |      |      |
| *Y | 0.062  | 0.074 | 1.575       | 1.880 |        |       |      |      |

\* EXPOSED PAD  
(Note 5)


### NOTES:

1. D & E DO NOT INCLUDE MOLD FLASH.
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .15 MM (.006").
3. CONTROLLING DIMENSION: MILLIMETERS.
4. MEETS JEDEC MO-187.
5. DIMENSIONS X & Y APPLY TO EXPOSED PAD (EP) VERSIONS ONLY. SEE INDIVIDUAL PRODUCT DATASHEET TO DETERMINE IF A PRODUCT USES EXPOSED PAD PACKAGE.
6. EXPOSED PAD FLUSH WITH BOTTOM OF PACKAGE WITHIN .002".

|   |                      |     |     |
|---|----------------------|-----|-----|
| <b>MAXIM</b>                            |                      |     |     |
| PROPRIETARY INFORMATION                 |                      |     |     |
| TITLE:                                  |                      |     |     |
| PACKAGE OUTLINE, 8L uMAX WITH EP OPTION |                      |     |     |
| APPROVAL                                | DOCUMENT CONTROL NO. | REV |     |
|   | 21-0036              | H   | 1/1 |

## 5th-Order, Lowpass, Elliptic, Switched-Capacitor Filters

### Package Information (continued)



*Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.*

12 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 2000 Maxim Integrated Products

Printed USA

**MAXIM** is a registered trademark of Maxim Integrated Products.