1 Absolute maximum ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{CEO}	Collector-emitter voltage (I _B = 0)	80	V
V _{EBO}	Emitter-base voltage (I _C = 0)	5	V
I _C	Collector current	10	Α
I _{CM}	Collector peak current	20	Α
P _{TOT}	Total dissipation at T _{case} = 25 °C	50	W
TSTG	Storage temperature	-55 to 150	°C
TJ	Max. operating junction temperature	150	°C

Table 3. Thermal data

Symbol	Parameter	Value	Unit
R _{thJC}	Thermal resistance junction-case max	2.5	°C/W
R _{thJA}	Thermal resistance junction-ambient max	62.5	°C/W

577

2/11 DocID022716 Rev 2

2 Electrical characteristics

 T_{case} = 25 °C; unless otherwise specified.

Table 4. Electrical characteristics

Symbol	Parameter	Test con	Min.	Тур.	Max.	Unit	
V _{CEO(sus)} ⁽¹⁾	Collector-emitter sustaining voltage (I _B = 0)	I _C = 30 mA		80	-		V
I _{CES}	Collector cut-off current (V _{BE} = 0)	V _{CE} = 80 V			-	10	μΑ
I _{EBO}	Emitter cut-off current (I _C = 0)	V _{EB} = 5 V			-	50	μΑ
V _{CE(sat)} ⁽¹⁾	Collector-emitter saturation voltage	I _C = 8 A	I _B = 0.4 A		1	1	V
V _{BE(sat)} ⁽¹⁾	Base-emitter saturation voltage	I _C = 8 A	$I_B = 0.8 A$		1	1.5	V
h _{FE} ⁽¹⁾	DC current gain	I _C = 2 A	$V_{CE} = 1 V$	60	-		
		I _C = 4 A	$V_{CE} = 1 V$	40	-		

^{1.} Pulse test: pulse duration \leq 300 μ s, duty cycle \leq 2 %.



Electrical characteristics MJB44H11T4

2.1 Electrical characteristics (curves)

Figure 2. Safe operating area

Ic (A)

| Continue | Pulse | P

Figure 3. Derating curve






Figure 4. DC current gain

Figure 5. Collector-emitter saturation voltage





5//

4/11 DocID022716 Rev 2

3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK[®] packages, depending on their level of environmental compliance. ECOPACK[®] specifications, grade definitions and product status are available at: www.st.com. ECOPACK[®] is an ST trademark.




Figure 6. D²PAK (TO-263) drawing

Table 5. D²PAK (TO-263) mechanical data

Dim.	mm					
	Min.	Тур.	Max.			
А	4.40		4.60			
A1	0.03		0.23			
b	0.70		0.93			
b2	1.14		1.70			
С	0.45		0.60			
c2	1.23		1.36			
D	8.95		9.35			
D1	7.50					
E	10		10.40			
E1	8.50					
е		2.54				
e1	4.88		5.28			
Н	15		15.85			
J1	2.49		2.69			
L	2.29		2.79			
L1	1.27		1.40			
L2	1.30		1.75			
R		0.4				
V2	0°		8°			

12.20 Figure 7. D²PAK footprint^(a)

16.90

12.20

19.75

Footprint

Footprint

Footprint


a. All dimension are in millimeters



DocID022716 Rev 2

4 Packaging mechanical data

Figure 8. Tape



57/

8/11 DocID022716 Rev 2

REEL DIMENSIONS 40mm min. Access hole At slot location В D С Tape slot in core for tape start 25 mm min. width G measured at hub Full radius AM08851v2

Figure 9. Reel

Table 6. D²PAK (TO-263) tape and reel mechanical data

Таре				Reel		
Dim	mm		Dim.	mm		
Dilli.	Dim. Min.	Max.	Dilli.	Min.	Max.	
A0	10.5	10.7	Α		330	
В0	15.7	15.9	В	1.5		
D	1.5	1.6	С	12.8	13.2	
D1	1.59	1.61	D	20.2		
Е	1.65	1.85	G	24.4	26.4	
F	11.4	11.6	N	100		
K0	4.8	5.0	Т		30.4	
P0	3.9	4.1				
P1	11.9	12.1		Base qty 1000		
P2	1.9	2.1	Bulk qty 1000		1000	
R	50					
Т	0.25	0.35				
W	23.7	24.3				



Revision history MJB44H11T4

5 Revision history

Table 7. Document revision history

Date	Revision	Changes
23-Jan-2012	1	Initial release.
12-May-2014	2	Updated Section 3: Package mechanical data. Added Section 4: Packaging mechanical data.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

ST PRODUCTS ARE NOT DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER'S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR "AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL" INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2014 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com



DocID022716 Rev 2