

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Application Specification

Z-PACK 2mm HM Interconnection System For Board-To-Board Connections

PDF

English

Product Specification

Z-Pack 2 Mm HM CONNECTORS

PDF

English

Product Environmental Compliance

TE Material Declaration

MD_5352332-1_12122015019_dmtec

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- PCB Mounting Orientation Vertical
- Connector & Contact Terminates To Printed Circuit Board
- Make First / Break Last Yes
- Shielded Yes
- Connector Style Plug
- Connector Type Connector Assembly

Configuration Features

- Rows Loaded A, B, C, D, E, F, Z
- Number of Rows 5+2
- Number of Positions 154
- Number of Signal Contacts 110

Signal Characteristics

- Data Rate (Gb/s) ≤1
- Crosstalk Version Standard

Body Features

Shield Type Ground Return Shielding

Contact Features

Contact Configuration Signal
Grounding Contact Without
CompactPCI Designation P1
Contact Mating Area Plating Thickness (µm) 1.27
Feedthrough Post Length (mm) 3.7
Contact Base Material Phosphor Bronze
Contact Style Short Tail
Contact Type Pin

Termination Features

Interface Type 2mm HM
Termination End Plating Material Tin over Nickel

Mechanical Attachment

Front Mating Level Level 1
Mating Alignment Type Multi-Purpose Center

Housing Features

Centerline (Pitch) (mm) 2
Housing Color Gray
Housing Material Polyester - GF

Dimensions

Module Length (mm) 50

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Method Tube
Packaging Quantity 11

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF