

■ Coil Data

Standard Non-latching Type (G6E-134P(-ST)-US, G6E-134C(-ST)-US)

| Rated voltage (VDC) | Rated current (mA) | Coil resistance (Ω) | Coil inductance (ref. value) (H) | | Pick-up voltage | Dropout voltage | Maximum voltage | Power consumption (mW) |
|---------------------|--------------------|------------------------------|----------------------------------|-------------|-----------------|-----------------|-----------------|------------------------|
| | | | Armature OFF | Armature ON | | | | |
| 3 | 66.70 | 45 | 0.08 | 0.06 | 70% max. | 10% min. | 190% at 23°C | Approx. 200 |
| 5 | 40 | 125 | 0.18 | 0.17 | | | | |
| 6 | 33.30 | 180 | 0.31 | 0.24 | | | | |
| 9 | 22.20 | 405 | 0.62 | 0.50 | | | | |
| 12 | 16.70 | 720 | 1.20 | 0.99 | | | | |
| 24 | 8.30 | 2,880 | 4.70 | 3.90 | | | | |
| 48 | 8.30 | 5,760 | 5.35 | 5.12 | | | 170% at 23°C | Approx. 400 |

Low-sensitivity Non-latching Type (G6E-134PL(-ST)-US)

| Rated voltage (VDC) | Rated current (mA) | Coil resistance (Ω) | Coil inductance (ref. value) (H) | | Pick-up voltage | Dropout voltage | Maximum voltage | Power consumption (mW) |
|---------------------|--------------------|------------------------------|----------------------------------|-------------|-----------------|-----------------|-----------------|------------------------|
| | | | Armature OFF | Armature ON | | | | |
| 3 | 133 | 22.50 | 0.03 | 0.03 | 70% max. | 10% min. | 190% at 23°C | Approx. 400 |
| 5 | 79.40 | 63 | 0.08 | 0.07 | | | | |
| 6 | 66.60 | 90 | 0.12 | 0.10 | | | | |
| 9 | 44.30 | 203 | 0.21 | 0.19 | | | | |
| 12 | 33.30 | 360 | 0.45 | 0.42 | | | | |
| 24 | 16.70 | 1,440 | 1.77 | 1.65 | | | | |

Standard Single Coil Latching Type (G6EU-134P(-ST)-US, G6EU-134C(-ST)-US)

| Rated voltage (VDC) | Rated current (mA) | Coil resistance (Ω) | Coil inductance (ref. value) (H) | | Set pick-up voltage | Reset pick-up voltage | Maximum voltage | Power consumption (mW) |
|---------------------|--------------------|------------------------------|----------------------------------|-------------|---------------------|-----------------------|-------------------|------------------------|
| | | | Armature OFF | Armature ON | | | | |
| 3 | 66.70 | 45 | 0.05 | 0.04 | 70% max. | 70% min. | 190% max. at 23°C | Approx. 200 |
| 5 | 40 | 125 | 0.13 | 0.12 | | | | |
| 6 | 33.30 | 180 | 0.19 | 0.17 | | | | |
| 9 | 22.20 | 405 | 0.45 | 0.40 | | | | |
| 12 | 16.70 | 720 | 0.84 | 0.79 | | | | |
| 24 | 8.30 | 2,880 | 3.56 | 3.10 | | | | |

Standard Dual Coil Latching Type (G6EK-134P(-ST)-US, G6EK-134C(-ST)-US)

| Rated voltage (VDC) | Rated current (mA) | Coil resistance (Ω) | Coil inductance (ref. value) (H) | | Set pick-up voltage | Reset pick-up voltage | Maximum voltage | Power consumption (mW) |
|---------------------|--------------------|------------------------------|----------------------------------|-------------|---------------------|-----------------------|-------------------|------------------------|
| | | | Armature OFF | Armature ON | | | | |
| 3 | 66.70 | 45 | 0.05 | 0.04 | 70% max. | 70% min. | 190% max. at 23°C | Approx. 200 |
| 5 | 40 | 125 | 0.09 | 0.08 | | | | |
| 6 | 33.30 | 180 | 0.12 | 0.11 | | | | |
| 7 | 22.20 | 405 | 0.25 | 0.22 | | | | |
| 12 | 16.70 | 720 | 0.44 | 0.41 | | | | |
| 24 | 8.30 | 2,880 | 1.66 | 1.62 | | | | |

- Note:** 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of $\pm 10\%$.
 2. Operating characteristics are measured at a coil temperature of 23°C.
 3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

Low-sensitivity Dual Coil Latching Type (G6EK-134PL(-ST)-US)

| Rated voltage (VDC) | Rated current (mA) | Coil resistance (Ω) | Coil inductance (ref. value) (H) | | Set pick-up voltage | Reset pick-up voltage | Maximum voltage | Power consumption (mW) |
|---------------------|--------------------|------------------------------|----------------------------------|-------------|---------------------|-----------------------|-------------------|------------------------|
| | | | Armature OFF | Armature ON | | | | |
| 3 | 133 | 22.50 | 0.02 | 0.01 | 70% max. | 70% min. | 170% max. at 23°C | Approx. 400 |
| 5 | 79.40 | 63 | 0.04 | 0.03 | | | | |
| 6 | 66.60 | 90 | 0.06 | 0.04 | | | | |
| 9 | 44.30 | 203 | 0.12 | 0.09 | | | | |
| 12 | 33.30 | 360 | 0.21 | 0.15 | | | | |
| 24 | 16.70 | 1,440 | 0.80 | 0.58 | | | | |

Note: 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of $\pm 10\%$.

2. Operating characteristics are measured at a coil temperature of 23°C.

3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

Characteristics

| | | |
|--|------------------------|--|
| Contact resistance (See note 1) | | 50 m Ω max. |
| Operate time (set) time (See note 2) | | 5 ms max. (mean value approx. 2.90 ms, 48 VDC type, approx. 2.40 ms) |
| Release time (reset) time (See note 2) | | 5 ms max. (mean value approx. 1.30 ms) |
| Min. set/reset signal width | | Latching type: 15 ms min. (at 23°C) |
| Operating frequency (max.) | Mechanical | 36,000 operations/hour |
| | Electrical | 1,800 operations/hour (under rated load) |
| Insulation resistance (See note 3) | | 1,000 M Ω min. (at 500 VDC) |
| Dielectric strength | | 1,500 VAC, 50/60 Hz for 1 minute between coil contacts |
| | | 1,000 VAC, 50/60 Hz for 1 minute between contacts of same pole |
| Surge withstand voltage | | 1,500 V (10 x 160 μ s) (conforms to FCC Part 68) |
| | | 2,500 V (2 x 10 μ s) (Telcordia Requirement) |
| Vibration | Mechanical durability | 10 to 55 Hz; 5 mm double amplitude |
| | Malfunction durability | 10 to 55 Hz; 3.3 mm double amplitude |
| Shock | Mechanical durability | 1,000 m/s ² , approx. 100G |
| | Malfunction durability | 300 m/s ² , approx. 30G |
| Ambient temperature | | -40°C to 70°C with no icing |
| Humidity | | 5% to 85% RH |
| Service life | Mechanical | 100 million operations min. (at 36,000 operations/hour) |
| | Electrical | 100,000 operations min (0.4A at 125 VAC resistive; 0.2A at 125VAC inductive) 500,000 operations min. (2A at 30 VDC resistive; 1A at 30VDC inductive) 200,000 operations min. (3A at 30 VDC resistive) See "Characteristic Data" |
| Weight | | Approx. 2.7 g |

Note: 1. The contact resistance was measured with 1A at 5VDC with a fall-of-potential method.


2. Values in parentheses are typical values unless otherwise stated.

3. The insulation resistance was measured with a 500-VDC megohmmeter applied to the same parts as those for checking the dielectric strength


4. The above values are initial values.

Characteristic Data


Maximum Switching Capacity



Electrical Service Life





Ambient Temperature vs. Maximum Coil Voltage





Note: The maximum coil voltage refers to the maximum value in a varying range of operating power voltage, not a continuous voltage.

Dimensions


Note: 1. All units are in millimeters unless otherwise indicated.
2. Orientation marks are indicated as follows:  

Standard coil



G6E-134P(L)-(ST)-US




**Terminal Arrangement/
Internal Connections
(Bottom View)**



G6E-134C(-ST)-US





**Mounting Holes
(Bottom View)**
Tolerance: ± 0.1




Single coil latching


G6EU-134P(L)-(ST)-US





**Terminal Arrangement/
Internal Connections
(Bottom View)**



**Mounting Holes
(Bottom View)**
Tolerance: ± 0.1





G6EU-134C(-ST)-US




Dual coil latching

G6EK-134P(L)(-ST)-US



*Average value
** 0.64mm for "-ST" models



Terminal Arrangement/ Internal Connections (Bottom View)




Mounting Holes (Bottom View)

Tolerance: ± 0.1

G6EK-134C(-ST)-US



*Average value
** 0.64mm for "-ST" models



■ Approvals

UL Recognized (File No. E41515) / CSA Certified (File No. LR31928) - - Ambient Temp. = 40°C

| Contact form | Coil ratings | Contact ratings | Number of test operations |
|--------------|--------------|--|---------------------------|
| SPDT | 3 to 48 VDC | 0.2 A at 250 VAC (General Use) 0.6 A at 125 VAC (General Use) 2 A at 30 VDC (Resistive) 0.6 A at 125 VDC (Resistive, Ag contact only) | 6,000 |

Note: 1. The rated values approved by each of the safety standards (e.g., UL, CSA, TUV) may be different from the performance characteristics individually defined in this catalog.

2. In the interest of product improvement, specifications are subject to change.

Precautions

■ Precautions for Correct Use


Long-term Continuously ON Contacts

Using the Relay in a circuit where the Relay will be ON continuously for long periods (without switching) can lead to unstable contacts because the heat generated by the coil itself will affect the insulation, causing a film to develop on the contact surfaces. We recommend using a latching relay (magnetic-holding relay) in this kind of circuit. If a single-side stable model must be used in this kind of circuit, we recommend using a fail-safe circuit design that provides protection against contact failure or coil burnout.

Installation


Do not reverse the polarity of the coil (+, -).

Provide sufficient space between Relays when mounting two or more on the same PCB, as shown in the following diagram.



Wiring

Refer to the following diagram when wiring to switch a DC load. The difference in polarity applied to the contacts will affect the endurance of the Relay due to the amount of contact movement. To extend the endurance characteristics beyond the performance ratings, wire the common (pin 7) terminal to the positive (+) side.



Ultrasonic Cleaning

Do not use ultrasonic cleaning on standard relay models. Doing so may result in resonance, coil burnout, and contact adhesion within the Relay.

Relay Handling


When washing the product after soldering the Relay to a PCB, use a water-based solvent or alcohol-based solvent, and keep the solvent temperature to less than 40°C. Do not put the Relay in a cold cleaning bath immediately after soldering.

■ Hints on Correct Use


Single-winding type (G6EU)

Example of low-power consumption driver circuit

1. This is an example of a driver circuit that allows Model G6E to function as a normal relay with a normal switching pulse input.
2. The relay is set by an abrupt current charged to capacity C. This current flows in the relay via diode D₁ and C and out via diode D₂.
3. The relay is reset by the discharge current of C flowing in the relay via transistor TR and C.



- Note:**
1. Give adequate consideration to the circuit constant when actually using this circuit, confirming the set and reset status of the relay.
 2. OMRON owns the patent on this circuit. Consult OMRON when using this circuit.



All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON[®]

**OMRON ELECTRONIC
COMPONENTS LLC**

55 E. Commerce Drive, Suite B
Schaumburg, IL 60173

847-882-2288

OMRON ON-LINE

Global - <http://www.omron.com>

USA - <http://www.components.omron.com>

Cat. No. X301-E-1b

09/11

Specifications subject to change without notice

Printed in USA

Low Signal Relay **G6E**