

TABLE 1. ELECTRICAL TESTS:

TEST	Symbol	CONDITIONS -55 °C ≤ T _A ≤ +125°C V ⁺ =+5.0V Unless otherwise specified	Group A Subgroup	Device type	Limits Min	Limits Max	Units
SWITCH							
Minimum Supply Voltage	I _{CC}	R _L =∞ Boost and OSC, no connection	1	All		200	μA
Minimum Supply Voltage	V+Min	R _L =10kΩ	1,2,3	All	1.5		V
Maximum Supply Voltage	V+Max	R _L =10kΩ	1,2,3	All		9.0	V
Output Resistance	R _{OUT}	I _L =20mA, f _{OSC} =5.0kHz	1 2,3	All		100 150	Ω
		I _L =3.0mA, f _{OSC} =1.0kHz, V ⁺ =2V	1,2,3			400	
Oscillator Frequency NOTE 2	f _{OSC}	C _{OSC} =1.0pF, V ⁺ =5.0V	4,5,6	All	5.0		kHz
		C _{OSC} =1.0pF, V ⁺ =5.0V	4,5,6	All	1.0		
Power Efficiency	P _{EFF}	R _L =5kΩ, f _{OSC} =5kHz	1	All	95		%
Voltage Conversion Efficiency	V _C EFF	R _L =∞	1	All	97		%
Oscillator Sink Current	I _{SINK}	V _{OSC} =V+, BOOST=0V	1,2,3	All	0.1	3.0	μA
		V _{OSC} =V+, BOOST=V+	1,2,3	All	1.0	20	
Oscillator Source Current	I _{SOURCE}	V _{OSC} =0V, BOOST=0V	1,2,3	All	0.1	3.0	μA
		V _{OSC} =0V, BOOST=V+	1,2,3	All	1.0	20	

NOTE 2: f_{OSC} is tested with C_{OSC}=100pF to minimize the effects of test fixture capacitance loading. The 1.0pF frequency is correlated to this 100pF test point and is intended to simulate the capacitance at the OSC pin when the device is plugged into a test socket and no external capacitor is used.

Package	ORDERING INFORMATION:	SMD Number
8 pin Cerdip	MAX1044MJA/883B	5962-3870701MPA
8 pin Can	MAX1044MTV/883B	5962-3870701MGC

TERMINAL CONNECTIONS:

	J8	TO99
1	BOOST	BOOST
2	CAP+	CAP+
3	GND	GND
4	CAP-	CAP-
5	VOUT	VOUT
6	LV	LV
7	OSC	OSC
8	V+	V+

-----	Electrical Characteristics of MAX1044/883B for /883B and SMD 5962-3870701	19-0193 Page 3 of 5	Rev. C 5
-------	--	------------------------	-------------

QUALITY ASSURANCE

Sampling and inspection procedures shall be in accordance with MIL-Prf-38535, Appendix A as specified in Mil-Std-883.

Screening shall be in accordance with Method 5004 of Mil-Std-883. Burn-in test Method 1015:

1. Test Condition, A, B, C, or D.
2. TA = +125°C minimum.
3. Interim and final electrical test requirements shall be specified in Table 2.

Quality conformance inspection shall be in accordance with Method 5005 of Mil-Std-883, including Groups A, B, C, and D inspection.

Group A inspection:

1. Tests as specified in Table 2.
2. Selected subgroups in Table 1, Method 5005 of Mil-Std-883 shall be omitted.

Group C and D inspections:

- a. End-point electrical parameters shall be specified in Table 1.
- b. Steady-state life test, Method 1005 of Mil-Std-883:
 1. Test condition A, B, C, D.
 2. TA = +125°C, minimum.
 3. Test duration, 1000 hours, except as permitted by Method 1005 of Mil-Std-883.

TABLE 2. ELECTRICAL TEST REQUIREMENTS

Mil-Std-883 Test Requirements	Subgroups per Method 5005, Table 1
Interim Electric Parameters Method 5004	1
Final Electrical Parameters Method 5005	1*, 2, 3, 4, 5, 6
Group A Test Requirements Method 5005	1, 2, 3, 4, 5, 6
Group C and D End-Point Electrical Parameters Method 5005	1

* PDA applies to Subgroup 1 only.