

## Dynamic Characteristics

VRF152(MP)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$C_{iss}$	Input Capacitance	$V_{GS} = 0V$		383		pF
$C_{oss}$	Output Capacitance	$V_{DS} = 50V$		215		
$C_{rss}$	Reverse Transfer Capacitance	$f = 1MHz$		20		

## Functional Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
$G_{PS}$	$f_1 = 30MHz, f_2 = 30.001MHz, V_{DD} = 50V, I_{DQ} = 250mA, P_{out} = 150W_{PEP}^1$	18	22		dB
$G_{PS}$	$f = 175MHz, V_{DD} = 50V, I_{DQ} = 250mA, P_{out} = 150W$		14		
$\eta_D$	$f_1 = 30MHz, f_2 = 30.001MHz, V_{DD} = 50V, I_{DQ} = 250mA, P_{out} = 150W_{PEP}^1$		50		%
IMD <sub>(d3)</sub>	$f_1 = 30MHz, f_2 = 30.001MHz, V_{DD} = 50V, I_{DQ} = 250mA, P_{out} = 150W_{PEP}^1$		-30		dBc
$\psi$	$f = 30MHz, V_{DD} = 50V, I_{DQ} = 250mA, P_{out} = 150W$ CW 70:1 VSWR - All Phase Angles, 0.2mSec X 20% Duty Factor	No Degradation in Output Power			

1. To MIL-STD-1311 Version A, test method 2204B, Two Tone, Reference Each Tone

Microsemi reserves the right to change, without notice, the specifications and information contained herein.

## Typical Performance Curves




FIGURE 1, Output Characteristics




FIGURE 2, Transfer Characteristics




FIGURE 3, Capacitance vs Drain-to-Source Voltage




FIGURE 4, Forward Safe Operating Area









Figure 5. Maximum Effective Transient Thermal Impedance Junction-to-Case vs Pulse Duration

Figure 6. Gain and Efficiency vs  $P_{out}$ Figure 7.  $P_{OUT}$  versus  $P_{IN}$ Figure 8. Gain and Efficiency vs  $P_{out}$ Figure 9.  $P_{OUT}$  versus  $P_{IN}$


## 30 MHz test Circuit



C1,2,8,9 - ARCO 463 20-180pF  
 C3,7 - 120 pF ATC 100B  
 C4,11-13 - 0.1uF 100V SMT  
 C5 - 1 uF 15WV tant  
 C6, C15 - 47pF ATC 100B  
 C10 - 150pF ATC 100B  
 C14 - 15uF 100V Elect  
 W1 W2 - printed line 0.23"x 0.7"

L1 - 4t #20 ga .25"d x .16"L ~120nH  
 L2 - 5t #14 ga .312" dia x .45" ~135nH  
 L3 -7 turns #16 ga 5/16" ID tight. ~250nH  
 R1 R2 - 2.2k ohm 1/4W  
 R3 - 22 ohm 1W SMT  
 R4 - 2.2 ohm 2W  
 RFC1 Fair-Rite 2961666631 (VK200-4B)  
 PCB = FR-4 fiberglass-epoxy er = 4.6

## 175 MHz test Circuit



C1 C2 C8 - ARCO 463  
 C3 C7 - 25 pF ATC 100B  
 C4 C10 C12 - 0.1uF 100V SMT  
 C5 - 1 uF 15WV tant  
 C6 - 250 pF ATC 100B  
 C9 - ARCO 462  
 C11 - 15uF 100V Elect


L1 - 3/4" #18 ga into Hairpin  
 L2 - printed line 0.2"W x 0.5" L  
 L3 - 1" #16 ga into Hairpin  
 L4 -2 turns #16 ga. 5/16" ID  
 R1 R2 - 150 ohm 1W  
 R3 - 470 ohm 3W, Panasonic ECG  
 RFC1 Fair-Rite 2961666631 (VK200-4B)

Adding MP at the end of P/N specifies a matched pair where  $V_{GS(TH)}$  is matched between the two parts.  $V_{TH}$  values are marked on the devices per the following table.

Code	Vth Range	Code 2	Vth Range
A	2.900 - 2.975	M	3.650 - 3.725
B	2.975 - 3.050	N	3.725 - 3.800
C	3.050 - 3.125	P	3.800 - 3.875
D	3.125 - 3.200	R	3.875 - 3.950
E	3.200 - 3.275	S	3.950 - 4.025
F	3.275 - 3.350	T	4.025 - 4.100
G	3.350 - 3.425	W	4.100 - 4.175
H	3.425 - 3.500	X	4.175 - 4.250
J	3.500 - 3.575	Y	4.250 - 4.325
K	3.575 - 3.650	Z	4.325 - 4.400

$V_{TH}$  values are based on Microsemi measurements at datasheet conditions with an accuracy of 1.0%.

**.5" SOE Package Outline**  
**All Dimensions are  $\pm .005$**



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.096	0.990	24.39	25.14
B	0.465	0.510	11.82	12.95
C	0.229	0.275	5.82	6.98
D	0.216	0.235	5.49	5.96
E	0.084	0.110	2.14	2.79
H	0.144	0.178	3.66	4.52
J	0.003	0.007	0.08	0.17
K	0.435		11.0	
M	45° NOM		45° NOM	
Q	0.115	0.130	2.93	3.30
R	0.246	0.255	6.25	6.47
U	0.720	0.730	18.29	18.54

**Disclaimer:**

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>