This browser does not have Java enabled.

My Cart | My Part Lists | Sign In/Register   English (Change)

Have a Question? Chat with a Product Information Specialist

What can we help you find?

Products | Industries | Resources | About TE | My Account | Innovation | Support Center

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details

5569380-1 Product Details

Share   Print   Email

5569380-1

TE Internal Number: 5569380-1

✔ Active

📄 View 3D PDF

PCB Mounted Jacks - Single Port, Multi-port and Stacked

🌿 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:
- Connector
- Preloaded
- Stacked Port Configuration
- 2 x 1 Jack Configuration
- Jack Type = RJ45

View all Features

Add to My Part List   Request Sample   Find Similar Products   Buy Product

Quick Links
- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- STACKED MODULAR JACK ASSEMBLY, 2 X 1 PORT, 8 POSITIO... (PDF, English)

Catalog Pages/Data Sheets:
- None Available

Product Specifications:
- High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English)

Application Specifications:
- Modular Jacks (PDF, English)

Instruction Sheets:
- None Available

CAD Files: (CAD Format & Compression Information)
- 2D Drawing (DXF, Version A1)
- 3D Model (IGES, Version A1)
- 3D Model (STEP, Version A1)

Additional Information:
- Product Line Information

Related Products:
- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Side Entry (Right Angle)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 5
- LED = Without
- Grounding Options = PCB Ground
- Panel Stops = Without
- Keyed = No
- Profile = Low
- Color = Black
- Shield Material = .010 [0.25] Copper Alloy

Mechanical Attachment:
- Panel Mount Retention = Without

Electrical Characteristics:
- Shielded = Yes

Termination Features:
- Solder Tail Contact Plating = Tin over Nickel
- Grounding Clips = Without

Dimensions:
- PCB Tail Length (mm [in]) = 3.56 [0.140]
- PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]

Body Features:
- Inverted Jack Face = No
- Shield Plating = Tin over Copper
- Grounding Tab Plating = Tin over Copper

Contact Features:
- Contact Plating, Mating Area, Material = Gold (50)
- Contact Base Material = Phosphor Bronze
- PCB ACTION PIN Grounds = Without

Housing Features:
- Housing Material = PCT GF
- Housing Color = Black
- UL Flammability Rating = UL 94V-0

Configuration Features:
- Preloaded = Yes
- Port Configuration = Stacked
- Jack Configuration = 2 x 1
- Number of Positions = 8
- Number of Contacts Loaded = 8
- Number of PCB Ground Tabs = 6
- Number of Terminals Per Port = 8

Industry Standards:
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Product Availability:
- Region = Asia, North America

Other:
- Brand = AMP