

Documentation & Additional Information		
Product Drawings: Product Drawings: <u>RECEPTACLE ASSEMBLY, RIGHT ANGLE, STACKED, 1</u> <u>HOLE, USB</u> (PDF, English)	Additional Information: ? Product Line Information	
Catalog Pages/Data Sheets: ? None Available	Related Products: ? <u>Tooling</u>	
Product Specifications: [?] None Available		
Application Specifications: ? None Available		
Instruction Sheets: ² None Available		
CAD Files: ? None Available		
Lis	t all Documents	
Product Features (Please use the Product Drawing for all design activity)		
Product Type Features:	Housing Related Features:	

Product Type Features:	Housing Related Features:	
? Gender = Receptacle	? Housing Color = Black	
? Number of Ports = 2	? Housing Material = Thermoplastic	
PCB Mount Style = Thru Hole	? Housing Flammability Rating = UL 94V	-0

PCB Thickness (mm [in]) = 1.57 [0.062]		
 Electrical Characteristics: Panel Ground Type = Spring Finger Termination Related Features: Termination (Solder) Post Length (mm [in]) = 2.84 [0.112] 	 Industry Standards: <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C RoHS/ELV Compliance History = Always was RoHS compliant 	
 Body Related Features: Series = A Mount Orientation = Right Angle Panel Ground = With Shell Plating = Tin over Copper Contact Related Features: Contact Mating Area Plating Material = Gold Flash over Palladium Nickel or Gold (30) over Nickel Contact Material = Copper Alloy 	Conditions for Usage: • USB Type = Standard Packaging Related Features: • Panel Ground Location = Middle • Packaging Method _ = Box Other: • Brand = AMP	
Provide Website Feedback Contact Customer Support Home Customer Support Site Map Privacy Policy Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved		

Downloaded from Arrow.com.