







Catalog #	DC Sparkover Voltage Tolerance (%)	V _{Nom Spark} (V)	Max Impulse Breakdown @ 100V/μs (V)	Max Impulse Breakdown @ 1kV/μs (V)	Capacitance (C ₀) (pF)	Impulse Discharge Current @ 8/20μs (kA)	AC Discharge Current (A)	Electrodes	Failsafe	Product Specification	Stock	Samples	Compare
GTCA25-401M-R02	±20%	400	<=900	<=1000	<1	2.5	2.5	2	Without		Check	Order	<input type="checkbox"/>
GTCA25-501M-R02	±20%	500	<=1100	<=1200	<1	2.5	2.5	2	Without		Check		<input type="checkbox"/>
GTCA25-601L-R05	±15%	600	<=950	<=1100	<1	5	5	2	Without		Check		<input type="checkbox"/>
GTCA25-750M-R02	±20%	75	<=450	<=550	<1	2.5	2.5	2	Without		Check		<input type="checkbox"/>
GTCA25-900M-R02	±20%	90	<=450	<=550	<1	2.5	2.5	2	Without		Check	Order	<input type="checkbox"/>
GTCA25-900M-R05	±20%	90	<=450	<=550	<1	5	5	2	Without		Check		<input type="checkbox"/>

Connect with Littelfuse



[Mobile Site](#)

About Littelfuse

- [About Littelfuse](#)
- [Conflict Free Statement](#)
- [History](#)
- [Investor Relations](#)
- [Legal](#)
- [Press Room](#)
- [Privacy Statement](#)
- [Supply Chain Transparency](#)
- [Website Feedback](#)

Explore Littelfuse

- [Capabilities Brochures](#)
- [Careers](#)
- [Check Distributor Stock](#)
- [Competitor Cross Reference](#)
- [Industries](#)
- [Order Samples](#)
- [Products](#)
- [Services](#)

Technical Resources

- [Application Designs](#)
- [Education](#)
- [FAQs](#)
- [iDesign™](#)
- [Littelfuse University](#)
- [Product Catalogs](#)
- [Quality Documents](#)
- [Technical Documents](#)