

Low-Voltage, SPST, CMOS Analog Switches

ABSOLUTE MAXIMUM RATINGS

(Voltages Referenced to GND)

V+-0.3V to +13V
Voltage into Any Terminal (Note 1)-0.3V to (V+ + 0.3V) or
±10mA (whichever occurs first)

Continuous Current into Any Terminal±10mA

Peak Current, NO or COM

(pulsed at 1ms, 10% duty cycle)±20mA

ESD per Method 3015.7>2000V

Continuous Power Dissipation (T_A = +70°C)

5-Pin SC70-5 (derate 2.5mW/°C above +70°C)200mW

5-Pin SOT23-5 (derate 7.1mW/°C above +70°C)571mW

8-Pin SO (derate 5.88mW/°C above +70°C)471mW

8-Pin Plastic DIP (derate 9.09mW/°C above +70°C)727mW

8-Pin Cerdip (derate 8.00mW/°C above +70°C)640mW

Operating Temperature Ranges

MAX4501C_/MAX4502C_0°C to +70°C

MAX4501E_/MAX4502E_-40°C to +85°C

MAX4501MJA/MAX4502MJA-55°C to +125°C

Storage Temperature Range-65°C to +150°C

Lead Temperature (soldering, 10s)+300°C

Note 1: Voltages exceeding V+ or GND on any signal terminal are clamped by internal diodes. Limit forward-diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—+5V Supply

(V+ = +4.5V to +5.5V, V_{INH} = 2.4V, V_{INL} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS			MIN	TYP	MAX	UNITS
ANALOG SWITCH								
Analog Signal Range	V _{COM} , V _{NO} , V _{NC}				0		V+	V
COM to NO or NC On-Resistance	R _{ON}	V _{COM} = 3.5V, I _{COM} = 1mA	T _A = +25°C		90		250	Ω
			T _A = T _{MIN} to T _{MAX}				350	
NO or NC Off-Leakage Current (Notes 3, 4)	I _{NO} (OFF), I _{NC} (OFF)	V+ = 5.5V, V _{COM} = 1V, V _{NO} or V _{NC} = 4.5V	T _A = +25°C		-1	0.01	1	nA
			T _A = T _{MIN} to T _{MAX}	C, E	-10		10	
				M	-100		100	
COM Off-Leakage Current (Notes 3, 4)	I _{COM} (OFF)	V+ = 5.5V, V _{COM} = 1V, V _{NO} or V _{NC} = 4.5V	T _A = +25°C		-1	0.01	1	nA
			T _A = T _{MIN} to T _{MAX}	C, E	-10		10	
				M	-100		100	
COM On-Leakage Current (Notes 3, 4)	I _{COM} (ON)	V+ = 5.5V, V _{COM} = 1V, 4.5V	T _A = +25°C		-2	0.01	2	nA
			T _A = T _{MIN} to T _{MAX}	C, E	-20		20	
				M	-200		200	
DIGITAL I/O								
Input Logic High	V _{INH}				2.4		V+	V
Input Logic Low	V _{INL}				0		0.8	V
Input Current Logic High or Low	I _{INH} , I _{INL}	V _{IN} = V+, 0			-1	0.03	1	μA
SWITCH DYNAMIC CHARACTERISTICS								
Turn-On Time	t _{ON}	V _{NO} = V _{NC} = 1.5V, V _{IN} = 3V, R _L = 1kΩ, C _L = 35pF, Figure 1	T _A = +25°C		16		75	ns
			T _A = T _{MIN} to T _{MAX}				150	
Turn-Off Time	t _{OFF}	V _{NO} = V _{NC} = 1.5V, V _{IN} = 3V, R _L = 1kΩ, C _L = 35pF, Figure 1	T _A = +25°C		10		50	ns
			T _A = T _{MIN} to T _{MAX}				150	

Low-Voltage, SPST, CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—+5V Supply (continued)

(V₊ = +4.5V to +5.5V, V_{INH} = 2.4V, V_{INL} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
SWITCH DYNAMIC CHARACTERISTICS (continued)						
Charge Injection (Note 5)	Q	C _L = 1nF, V _{NO} = 0, R _S = 0Ω, T _A = +25°C, Figure 2		1	10	pC
Off-Isolation	V _{ISO}	R _L = 50Ω, C _L = 15pF, V _{NO} = 1V _{RMS} , f = 100kHz, T _A = +25°C, Figure 3		< -100		dB
NO or NC Off-Capacitance	C _{NO(OFF)} , C _{NC(OFF)}	f = 1MHz, Figure 4		3		pF
COM Off-Capacitance	C _{COM(OFF)}	f = 1MHz, Figure 4		3		pF
COM On-Capacitance	C _{COM(ON)}	f = 1MHz, Figure 4		8		pF
POWER SUPPLY						
V ₊ Supply Current	I ₊	V _{IN} = 0 or V ₊	T _A = +25°C	-1	1	μA
			T _A = T _{MIN} to T _{MAX}	-10	10	

ELECTRICAL CHARACTERISTICS—+12V Supply

(V₊ = +11.4V to +12.6V, V_{INH} = 5.0V, V_{INL} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS			MIN	TYP	MAX	UNITS
ANALOG SWITCH								
Analog Signal Range	V _{COM} , V _{NO} , V _{NC}				0		V+	V
COM to NO or NC On-Resistance	R _{ON}	V _{COM} = 10V, I _{COM} = 1mA	T _A = +25°C		40		160	Ω
			T _A = T _{MIN} to T _{MAX}			200		
NO or NC Off-Leakage Current (Notes 3, 4)	I _{NO} (OFF), I _{NC} (OFF)	V _{COM} = 10V, V _{NO} or V _{NC} = 1V, V+ = +12.6V	T _A = +25°C		-5		5	nA
			T _A = T _{MIN} to T _{MAX}	C, E	-50		50	
				M	-500		500	
COM Off-Leakage Current (Notes 3, 4)	I _{COM} (OFF)	V _{COM} = 10V, V _{NO} or V _{NC} = 1V, V+ = +12.6V	T _A = +25°C		-5		5	nA
			T _A = T _{MIN} to T _{MAX}	C, E	-50		50	
				M	-500		500	
COM On-Leakage Current (Notes 3, 4)	I _{COM} (ON)	V _{COM} = 10V, V+ = +12.6V	T _A = +25°C		-10		10	nA
			T _A = T _{MIN} to T _{MAX}	C, E	-100		100	
				M	-1000		1000	
DIGITAL I/O								
Input Logic High	V _{INH}				5.0		V+	V
Input Logic Low	V _{INL}				0		0.8	V
Input Current Logic High or Low	I _{INH} , I _{INL}	V _{IN} = 0 or V+			-1	0.03	1	μA
POWER SUPPLY								
V+ Supply Current	I+	I _N = 0 or V+	T _A = +25°C		-1		1	μA
			T _A = T _{MIN} to T _{MAX}		-10		10	

Low-Voltage, SPST, CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—+3V Supply

($V_+ = +3.0V$ to $+3.6V$, $V_{INH} = 2.4V$, $V_{INL} = 0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
ANALOG SWITCH							
Analog Signal Range	V _{COM} , V _{NO} , V _{NC}			0		V+	V
COM to NO or NC On-Resistance	R _{ON}	V _{COM} = 1.5V, I _{COM} = 0.1mA	T _A = +25°C	175	600		Ω
			T _A = T _{MIN} to T _{MAX}		800		
DIGITAL I/O							
Input Logic High	V _{INH}			2.4		V+	V
Input Logic Low	V _{INL}			0		0.8	V
Input Current Logic High or Low	I _{INH} , I _{INL}	V _{IN} = 0 or V+		-1.00	0.03	1.00	μA
SWITCH DYNAMIC CHARACTERISTICS							
Turn-On Time (Note 5)	t _{ON}	V _{NO} = V _{NC} = 1.5V, V _{IN} = 3V, R _L = 1kΩ, Figure 1	T _A = +25°C	45	300		ns
			T _A = T _{MIN} to T _{MAX}		500		
Turn-Off Time (Note 5)	t _{OFF}	V _{NO} = V _{NC} = 1.5V, V _{IN} = 3V, R _L = 1kΩ, Figure 1	T _A = +25°C	10	125		ns
			T _A = T _{MIN} to T _{MAX}		175		
Charge Injection (Note 5)	Q	C _L = 1nF, T _A = +25°C, Figure 2		0.5		10	pC
POWER SUPPLY							
V+ Supply Current	I+	I _N = 0 or V+	T _A = +25°C	-1		1	μA
			T _A = T _{MIN} to T _{MAX}	-10		10	

Note 2: Algebraic convention is used in this data sheet; the most negative value is shown in the minimum column.

Note 3: Leakage parameters are 100% tested at maximum-rated hot operating temperature, and are guaranteed by correlation at $+25^\circ C$.

Note 4: SOT and SC70 packaged parts are 100% tested at $+25^\circ C$. Limits at maximum and minimum rated temperature are guaranteed by design and correlation limits at $+25^\circ C$.









Note 5: Guaranteed, not production tested.

Low-Voltage, SPST, CMOS Analog Switches

Typical Operating Characteristics

($V_+ = +5V$, $GND = 0$, $T_A = +25^\circ C$, unless otherwise noted.)

MAX4501/MAX4502



Low-Voltage, SPST, CMOS Analog Switches

Pin Description

PIN				NAME	FUNCTION
MAX4501		MAX4502			
SO/DIP	SC70-5/SOT23-5	SO/DIP	SC70-5/SOT23-5		
1	1	1	1	COM	Analog Switch Common Terminal
2, 3, 5	—	2, 3, 5	—	N.C.	No Connection. Not internally connected.
4	5	4	5	V+	Positive Supply-Voltage Input (analog and digital)
6	4	6	4	IN	Digital Control Input
7	3	7	3	GND	Ground
8	2	—	—	NO	Analog Switch (normally open)
—	—	8	2	NC	Analog Switch (normally closed)

Note: NO, NC, and COM pins are identical and interchangeable. Any may be considered as an input or an output; signals pass equally well in both directions.

Applications Information

Power-Supply Considerations

The MAX4501/MAX4502 are constructed like most CMOS analog switches, except they have only two supply pins: V+ and GND. V+ and GND drive the internal CMOS switches and set the analog voltage limits of the switch. Reverse ESD-protection diodes are internally connected between each analog signal pin and both V+ and GND. One of these diodes conducts if any analog signal exceeds V+ or GND. During normal operation, these and other reverse-biased ESD diodes leak, forming the only current drawn from V+ or GND.

Virtually all the analog leakage current comes from the ESD diodes. Although the ESD diodes on a given signal pin are identical and therefore fairly well balanced, they are reverse biased differently. Each is biased by either V+ or GND and the analog signal. This means their leakages will vary as the signal varies. The *difference* in the two diode leakages to the V+ and GND pins constitutes the analog signal-path leakage current. All analog leakage current flows between each pin and one of the supply terminals, not to the other switch terminal. This is why both sides of a given switch can show leakage currents of the same or opposite polarity.

There is no connection between the analog-signal paths and V+ or GND.

V+ and GND also power the internal logic and logic-level translators, and set the input logic limits. The logic-level translators convert the logic levels to switched V+ and GND signals to drive the analog sig-

nal gates. This drive signal is the only connection between the logic supplies (and signals) and the analog supplies. COM, NO, and NC pins have ESD-protection diodes to V+ and GND.

The logic-level thresholds are CMOS/TTL compatible when V+ is +5V. As V+ rises, the threshold increases slightly. When V+ reaches +12V, the logic-level threshold is about 3V—above the TTL guaranteed high-level minimum of 2.8V, but still compatible with CMOS outputs.

Do not connect the MAX4501/MAX4502's V+ pin to +3V and then connect the logic-level pins to TTL logic-level signals. TTL levels can exceed +3V and violate the absolute maximum ratings, damaging the part and/or external circuits.

High-Frequency Performance

In 50Ω systems, signal response is reasonably flat up to 250MHz (see *Typical Operating Characteristics*). Above 20MHz, the on-response has several minor peaks that are highly layout dependent. The problem is not in turning the switch on; it's in turning it off. The off-state switch acts like a capacitor and passes higher frequencies with less attenuation. At 10MHz, off-isolation is about -60dB in 50Ω systems, decreasing approximately 20dB per decade as frequency increases. Higher circuit impedances also cause off-isolation to decrease. Adjacent channel attenuation is about 3dB above that of a bare IC socket, and is due entirely to capacitive coupling.

Low-Voltage, SPST, CMOS Analog Switches

Test Circuits/Timing Diagrams

MAX4501/MAX4502




Figure 1. Switching Times




Figure 2. Charge Injection

Low-Voltage, SPST, CMOS Analog Switches

Test Circuits/Timing Diagrams (continued)




Figure 3. Off-Isolation and On-Loss





Figure 4. NO, NC, and COM Capacitance

Chip Topography



Ordering Information (continued)

PART	TEMP. RANGE	PIN-PACKAGE	TOP MARK
MAX4502CUK-T	0°C to +70°C	5 SOT23-5	AAAB
MAX4502CSA	0°C to +70°C	8 SO	—
MAX4502CPA	0°C to +70°C	8 Plastic DIP	—
MAX4502C/D	0°C to +70°C	Dice*	—
MAX4502EXK-T	-40°C to +85°C	5 SC70-5	AAF
MAX4502EUK-T	-40°C to +85°C	5 SOT23-5	AAAB
MAX4502ESA	-40°C to +85°C	8 SO	—
MAX4502EPA	-40°C to +85°C	8 Plastic DIP	—
MAX4502MJA	-55°C to +125°C	8 CERDIP**	—

*Contact factory for dice specifications.

**Contact factory for availability.

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

8 Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600

© 1999 Maxim Integrated Products

Printed USA

MAXIM is a registered trademark of Maxim Integrated Products.