


# CPH3145/CPH3245

## ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 2)

| Parameter                               | Symbol               | Conditions                                        | Value   |           |           | Unit |
|-----------------------------------------|----------------------|---------------------------------------------------|---------|-----------|-----------|------|
|                                         |                      |                                                   | min     | typ       | max       |      |
| Collector Cutoff Current                | ICBO                 | V <sub>CB</sub> =(-)40V, I <sub>E</sub> =0A       |         |           | (-)1      | μA   |
| Emitter Cutoff Current                  | IEBO                 | V <sub>EB</sub> =(-)4V, I <sub>C</sub> =0A        |         |           | (-)1      | μA   |
| DC Current Gain                         | h <sub>FE</sub>      | V <sub>CE</sub> =(-)2V, I <sub>C</sub> =(-)100mA  | 200     |           | 560       |      |
| Gain-Bandwidth Product                  | f <sub>T</sub>       | V <sub>CE</sub> =(-)10V, I <sub>C</sub> =(-)300mA |         | 420       |           | MHz  |
| Output Capacitance                      | C <sub>ob</sub>      | V <sub>CB</sub> =(-)10V, f=1MHz                   |         | (16)8     |           | pF   |
| Collector to Emitter Saturation Voltage | V <sub>CE(sat)</sub> | I <sub>C</sub> =(-)1A, I <sub>B</sub> =(-)50mA    |         | (-165)130 | (-330)260 | mV   |
| Base to Emitter Saturation Voltage      | V <sub>BE(sat)</sub> |                                                   |         | (-)0.9    | (-)1.2    | V    |
| Collector to Base Breakdown Voltage     | V <sub>(BR)CBO</sub> | I <sub>C</sub> =(-)10μA, I <sub>E</sub> =0A       | (-50)80 |           |           | V    |
| Collector to Emitter Breakdown Voltage  | V <sub>(BR)CES</sub> | I <sub>C</sub> =(-)100μA, R <sub>BE</sub> =0Ω     | (-50)80 |           |           | V    |
| Collector to Emitter Breakdown Voltage  | V <sub>(BR)CEO</sub> | I <sub>C</sub> =(-)1mA, R <sub>BE</sub> =∞        | (-)50   |           |           | V    |
| Emitter to Base Breakdown Voltage       | V <sub>(BR)EBO</sub> | I <sub>E</sub> =(-)10μA, I <sub>C</sub> =0A       | (-)6    |           |           | V    |
| Turn-ON Time                            | t <sub>on</sub>      | See specified Test Circuit                        |         | (35)35    |           | ns   |
| Storage Time                            | t <sub>stg</sub>     |                                                   |         | (200)330  |           | ns   |
| Fall Time                               | t <sub>f</sub>       |                                                   |         | (24)40    |           | ns   |


Note 2 : Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## Switching Time Test Circuit





$$I_C = -10I_{B1} = 10I_{B2} = -0.7A$$

CPH3145











$$I_C = 10I_{B1} = -10I_{B2} = 0.7A$$









CPH3245



# CPH3145/CPH3245



# CPH3145/CPH3245




# CPH3145/CPH3245

## PACKAGE DIMENSIONS


unit : mm

CPH3  
CASE 318BA  
ISSUE 0



- 1 : Base
- 2 : Emitter
- 3 : Collector

## Recommended Soldering Footprint



## ORDERING INFORMATION

| Device       | Marking | Package                                    | Shipping (Qty / Packing) |
|--------------|---------|--------------------------------------------|--------------------------|
| CPH3145-TL-E | BE      | CPH3<br>SC-59, SOT-23, TO-236<br>(Pb-Free) | 3,000 / Tape & Reel      |
| CPH3245-TL-E | DQ      |                                            |                          |

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D. [http://www.onsemi.com/pub\\_link/Collateral/BRD8011-D.PDF](http://www.onsemi.com/pub_link/Collateral/BRD8011-D.PDF)

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.