

## Product specifications

| Part number | OCL (uH) minimum<br>(1-2) & (4-3) | I rms. Amperes<br>Max* | DCR (Ω) typ @<br>20°C (1-2) | DCR (Ω) typ @<br>20°C (4-3) | Leakage<br>Inductance (uH)<br>typ | Interwinding<br>Capacitance (pF) typ |
|-------------|-----------------------------------|------------------------|-----------------------------|-----------------------------|-----------------------------------|--------------------------------------|
| CMS1-1-R    | 4.5                               | 7.00                   | 0.0027                      | 0.0027                      | 0.05                              | 2.0                                  |
| CMS1-2-R    | 8                                 | 5.70                   | 0.0040                      | 0.0040                      | 0.09                              | 2.1                                  |
| CMS1-3-R    | 12.6                              | 4.10                   | 0.077                       | 0.077                       | 0.14                              | 2.2                                  |
| CMS1-4-R    | 18                                | 3.80                   | 0.0089                      | 0.0089                      | 0.20                              | 2.3                                  |
| CMS1-5-R    | 25                                | 3.60                   | 0.0100                      | 0.0100                      | 0.28                              | 2.4                                  |
| CMS1-6-R    | 32.8                              | 3.10                   | 0.0138                      | 0.0138                      | 0.36                              | 2.5                                  |
| CMS1-7-R    | 41.5                              | 2.60                   | 0.019                       | 0.019                       | 0.45                              | 2.6                                  |
| CMS1-8-R    | 51.2                              | 2.20                   | 0.026                       | 0.026                       | 0.056                             | 2.7                                  |
| CMS1-9-R    | 62                                | 1.90                   | 0.035                       | 0.035                       | 0.68                              | 2.7                                  |
| CMS1-10-R   | 73.7                              | 1.65                   | 0.048                       | 0.048                       | 0.81                              | 2.8                                  |
| CMS1-11-R   | 100                               | 1.35                   | 0.070                       | 0.070                       | 1.10                              | 3.9                                  |
| CMS1-12-R   | 131                               | 1.15                   | 0.100                       | 0.100                       | 1.45                              | 3.0                                  |
| CMS1-13-R   | 166                               | 1.00                   | 0.138                       | 0.138                       | 1.83                              | 3.1                                  |
| CMS1-14-R   | 205                               | 0.85                   | 0.186                       | 0.186                       | 2.25                              | 3.2                                  |
| CMS2-0-R    | 14                                | 6.00                   | 0.004                       | 0.004                       | 0.13                              | 1.7                                  |
| CMS2-1-R    | 25                                | 5.35                   | 0.005                       | 0.005                       | 0.22                              | 2.0                                  |
| CMS2-2-R    | 40                                | 4.40                   | 0.008                       | 0.008                       | 0.34                              | 2.3                                  |
| CMS2-3-R    | 57                                | 3.60                   | 0.012                       | 0.012                       | 0.47                              | 2.5                                  |
| CMS2-4-R    | 102                               | 2.80                   | 0.019                       | 0.019                       | 0.80                              | 2.8                                  |
| CMS2-5-R    | 160                               | 2.30                   | 0.029                       | 0.029                       | 1.25                              | 3.1                                  |
| CMS2-6-R    | 230                               | 1.85                   | 0.044                       | 0.044                       | 1.75                              | 3.4                                  |
| CMS2-7-R    | 270                               | 1.60                   | 0.060                       | 0.060                       | 2.00                              | 3.6                                  |
| CMS2-8-R    | 360                               | 1.35                   | 0.084                       | 0.084                       | 2.60                              | 3.9                                  |
| CMS2-9-R    | 460                               | 1.10                   | 0.120                       | 0.120                       | 3.30                              | 4.3                                  |
| CMS2-10-R   | 575                               | 0.94                   | 0.170                       | 0.170                       | 4.00                              | 4.3                                  |
| CMS2-11-R   | 700                               | 0.80                   | 0.230                       | 0.230                       | 5.00                              | 4.6                                  |
| CMS2-12-R   | 915                               | 0.67                   | 0.330                       | 0.330                       | 6.30                              | 4.9                                  |
| CMS2-13-R   | 1070                              | 0.58                   | 0.440                       | 0.440                       | 7.30                              | 5.1                                  |
| CMS2-14-R   | 1340                              | 0.50                   | 0.620                       | 0.620                       | 9.00                              | 5.4                                  |
| CMS3-1-R    | 28                                | 5.70                   | 0.005                       | 0.005                       | 0.31                              | 2.80                                 |
| CMS3-2-R    | 45                                | 5.10                   | 0.006                       | 0.006                       | 0.46                              | 3.05                                 |
| CMS3-3-R    | 64                                | 4.75                   | 0.007                       | 0.007                       | 0.64                              | 3.30                                 |
| CMS3-4-R    | 88                                | 3.95                   | 0.010                       | 0.010                       | 0.85                              | 3.50                                 |
| CMS3-5-R    | 146                               | 3.10                   | 0.017                       | 0.017                       | 1.30                              | 3.70                                 |
| CMS3-6-R    | 217                               | 2.85                   | 0.020                       | 0.020                       | 1.90                              | 3.90                                 |
| CMS3-7-R    | 258                               | 2.45                   | 0.027                       | 0.027                       | 2.20                              | 4.15                                 |
| CMS3-8-R    | 350                               | 2.00                   | 0.040                       | 0.040                       | 3.00                              | 4.40                                 |
| CMS3-9-R    | 400                               | 1.70                   | 0.053                       | 0.053                       | 3.30                              | 4.65                                 |
| CMS3-10-R   | 518                               | 1.45                   | 0.076                       | 0.076                       | 4.20                              | 4.85                                 |
| CMS3-11-R   | 648                               | 1.20                   | 0.107                       | 0.107                       | 5.10                              | 5.10                                 |
| CMS3-12-R   | 790                               | 1.05                   | 0.145                       | 0.145                       | 6.10                              | 5.35                                 |
| CMS3-13-R   | 1030                              | 0.88                   | 0.210                       | 0.210                       | 7.80                              | 5.55                                 |
| CMS3-14-R   | 1310                              | 0.75                   | 0.300                       | 0.300                       | 9.60                              | 5.80                                 |

### Definitions:

OCL = Open Circuit Inductance

DCR = Direct Current Resistance

I<sub>rms</sub> = rms current for approx. a 40°C temperature rise at an ambient temperature of 85°C.

\*Operating Temperature: 160°C Max. Inductance values are sustained up to 160°C.

### Electrical Characteristics:

OCL (1-2) 0.10Vrms, 100kHz, 0.0Adc: (See Chart)

OCL (4-3) 0.10Vrms, 100kHz, 0.0Adc: (See Chart)

DCR (1-2) typ @ 20°C: (See Chart)

DCR (4-3) typ @ 20°C: (See Chart)




Hipot rating: winding to winding: 300Vdc min. for 1 second.

Turns Ratio: (1-2):(4-3) 1:1


Dimensions—mm

CMS1

RECOMMENDED PCB LAYOUT




SCHEMATIC




CMS2


TOP VIEW




FRONT VIEW



RECOMMENDED PCB LAYOUT




SCHEMATIC




CMS3


TOP VIEW




FRONT VIEW



RECOMMENDED PCB LAYOUT



SCHEMATIC



wwlyy = Date code R = Revision level



## Packaging Information

### CMS1

Supplied in tape and reel packaging, 2,000 parts per 13" diameter reel


### CMS2

Supplied in tape and reel packaging, 800 parts per 13" diameter reel






### CMS3

Supplied in tape and reel packaging, 600 parts per 13" diameter reel




## Attenuation Curves




## Impedance Curves


Impedance CMS1-1 & 4




Impedance CMS1 - 7,11, & 14




Impedance CMS2 - 1 & 4




Impedance CMS2 - 7,11, & 14



Impedance CMS3 - 1 & 4



Impedance CMS3 - 7,11, & 14



## Solder reflow profile




Table 1 - Standard SnPb solder ( $T_C$ )

| Package thickness | Volume mm <sup>3</sup> <350 | Volume mm <sup>3</sup> ≥350 |
|-------------------|-----------------------------|-----------------------------|
| <2.5mm)           | 235°C                       | 220°C                       |
| ≥2.5mm            | 220°C                       | 220°C                       |

Table 2 - Lead (Pb) free solder ( $T_C$ )

| Package thickness | Volume mm <sup>3</sup> <350 | Volume mm <sup>3</sup> 350 - 2000 | Volume mm <sup>3</sup> >2000 |
|-------------------|-----------------------------|-----------------------------------|------------------------------|
| <1.6mm            | 260°C                       | 260°C                             | 260°C                        |
| 1.6 – 2.5mm       | 260°C                       | 250°C                             | 245°C                        |
| >2.5mm            | 250°C                       | 245°C                             | 245°C                        |

## Reference J-STD-020

| Profile feature                                                                    | Standard SnPb solder | Lead (Pb) free solder |
|------------------------------------------------------------------------------------|----------------------|-----------------------|
| Preheat and soak                                                                   |                      |                       |
| • Temperature min. ( $T_{smin}$ )                                                  | 100 °C               | 150 °C                |
| • Temperature max. ( $T_{smax}$ )                                                  | 150 °C               | 200 °C                |
| • Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )                                      | 60-120 seconds       | 60-120 seconds        |
| Average ramp up rate $T_{smax}$ to $T_P$                                           | 3 °C/ second Max.    | 3 °C/ second Max.     |
| Liquidous temperature ( $T_L$ )                                                    | 183 °C               | 217 °C                |
| Time at liquidous ( $t_L$ )                                                        | 60-150 seconds       | 60-150 seconds        |
| Peak package body temperature ( $T_P$ )*                                           | Table 1              | Table 2               |
| Time ( $t_p$ )** within 5 °C of the specified classification temperature ( $T_C$ ) | 20 seconds**         | 30 seconds**          |
| Average ramp-down rate ( $T_P$ to $T_{smax}$ )                                     | 6 °C/ second max.    | 6 °C/ second max.     |
| Time 25 °C to peak temperature                                                     | 6 minutes max.       | 8 minutes max.        |

\* Tolerance for peak profile temperature ( $T_P$ ) is defined as a supplier minimum and a user maximum.

\*\* Tolerance for time at peak profile temperature ( $t_p$ ) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
**Electronics Division**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
www.eaton.com/electronics

© 2018 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 4313 PCN18009  
September 2018