



A

PRODUCT NO	DIM"A"	ROW	6	5	4	3	2	1
88945-X03 88945-X03LF	2.90	D	X	-	X	X	X	X
		C	X	-	X	X	X	X
		B	-	-	X	X	-	-
88945-X13 88945-X13LF	3.53	A	X	-	X	X	-	X
		D	X	-	X	X	X	X
		C	X	-	X	X	X	X
88945-X04 88945-X04LF	2.90	B	-	-	X	X	-	-
		D	X	-	X	-	X	-
		C	-	X	-	X	-	X
88945-X14 88945-X14LF	3.53	A	-	X	-	X	-	X
		D	X	-	X	-	X	-
		C	-	X	-	X	-	X

LOAD PATTERN	
X	LOADED
-	NOT LOADED

NOTES:

- CONNECTOR MATERIALS:
HOUSING: LCP, 30% GLASS FILLED,
UL 94-V0 COMPLIANT
TERMINAL: PHOSPHOR BRONZE ALLOY
- PRESS-FIT TAIL PLATING: 0.5-1.5 µm TIN LEAD
- PRODUCT SPECIFICATION:
GS-12-002
- APPLICATION SPECIFICATIONS:
BUS-20-061
GS-20-001
TA-941
- PRODUCT MARKING: (PART NUMBER & LOT CODE).
- INDICATED HOLES ARE UNPLATED.
- DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.
- TOP SURFACE OF PRESS BLOCK MAY EXTEND UP TO 0.4MM HIGHER THAN HOUSING. THIS MAY AFFECT THE TAIL LENGTH BEFORE APPLICATION TO A BOARD.
- THESE PRODUCTS WHERE THE PART NUMBER ENDS IN "LF" MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 240°C FOR 60 SECONDS IN A CONVECTION, INFAIR-RED OR VAPOR PHASE REFLOW OVEN.
- FOR PLATING SPEC, REFER TO DRAWING 10097866.

FOR LEAD FREE PART NUMBERS ADD "LF" SUFFIX. EXAMPLE: 88945-XYTLF.

A

matl code		SEE NOTES		tolerances unless otherwise specified		CUSTOMER COPY		FCI		www.fciconnect.com			
ltr	ecn no	dr	date	linear	.XX ±.10	projection	title	B SERIES R/A SIGNAL RECEPT ASSY 4 ROW, 1 MOD, PF product family METRAL (tm) size dwg no code					
P				angles	.XXX ±.050	MM	1:1						
				dr	S.STONER 10/29/92	engr	R.DOUTRICH 10/29/92					code	213
				chr	S.STONER 10/29/92	appd	S.STONER 10/29/92					sheet	2 of 2
sheet	revision			index	sheet								