


| Schottky   |                                              |                                                                    |                                | Ratings                        |      |      |               |
|------------|----------------------------------------------|--------------------------------------------------------------------|--------------------------------|--------------------------------|------|------|---------------|
| Symbol     | Definition                                   | Conditions                                                         |                                | min.                           | typ. | max. | Unit          |
| $V_{RSM}$  | max. non-repetitive reverse blocking voltage | $T_{VJ} = 25^{\circ}\text{C}$                                      |                                |                                |      | 100  | V             |
| $V_{RRM}$  | max. repetitive reverse blocking voltage     | $T_{VJ} = 25^{\circ}\text{C}$                                      |                                |                                |      | 100  | V             |
| $I_R$      | reverse current, drain current               | $V_R = 100\text{ V}$                                               | $T_{VJ} = 25^{\circ}\text{C}$  |                                |      | 250  | $\mu\text{A}$ |
|            |                                              | $V_R = 100\text{ V}$                                               | $T_{VJ} = 125^{\circ}\text{C}$ |                                |      | 2.5  | mA            |
| $V_F$      | forward voltage drop                         | $I_F = 15\text{ A}$                                                | $T_{VJ} = 25^{\circ}\text{C}$  |                                |      | 0.91 | V             |
|            |                                              | $I_F = 30\text{ A}$                                                |                                |                                |      | 1.06 | V             |
|            |                                              | $I_F = 15\text{ A}$                                                | $T_{VJ} = 125^{\circ}\text{C}$ |                                |      | 0.72 | V             |
|            |                                              | $I_F = 30\text{ A}$                                                |                                |                                |      | 0.90 | V             |
| $I_{FAV}$  | average forward current                      | $T_C = 150^{\circ}\text{C}$<br>rectangular $d = 0.5$               | $T_{VJ} = 175^{\circ}\text{C}$ |                                |      | 15   | A             |
| $V_{F0}$   | threshold voltage                            | } for power loss calculation only                                  |                                | $T_{VJ} = 175^{\circ}\text{C}$ |      | 0.46 | V             |
| $r_F$      | slope resistance                             |                                                                    |                                |                                |      | 11.7 | m $\Omega$    |
| $R_{thJC}$ | thermal resistance junction to case          |                                                                    |                                |                                |      | 1.75 | K/W           |
| $R_{thCH}$ | thermal resistance case to heatsink          |                                                                    |                                |                                | 0.3  |      | K/W           |
| $P_{tot}$  | total power dissipation                      | $T_C = 25^{\circ}\text{C}$                                         |                                |                                |      | 85   | W             |
| $I_{FSM}$  | max. forward surge current                   | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}; V_R = 0\text{ V}$ | $T_{VJ} = 45^{\circ}\text{C}$  |                                |      | 340  | A             |
| $C_J$      | junction capacitance                         | $V_R = 12\text{ V}$ $f = 1\text{ MHz}$                             | $T_{VJ} = 25^{\circ}\text{C}$  |                                | 146  |      | pF            |

| Package TO-247 |                              |                            | Ratings |      |      |      |
|----------------|------------------------------|----------------------------|---------|------|------|------|
| Symbol         | Definition                   | Conditions                 | min.    | typ. | max. | Unit |
| $I_{RMS}$      | RMS current                  | per terminal <sup>1)</sup> |         |      | 50   | A    |
| $T_{VJ}$       | virtual junction temperature |                            | -55     |      | 175  | °C   |
| $T_{op}$       | operation temperature        |                            | -55     |      | 150  | °C   |
| $T_{stg}$      | storage temperature          |                            | -55     |      | 150  | °C   |
| Weight         |                              |                            |         | 6    |      | g    |
| $M_D$          | mounting torque              |                            | 0.8     |      | 1.2  | Nm   |
| $F_C$          | mounting force with clip     |                            | 20      |      | 120  | N    |

### Product Marking



### Part description

D = Diode  
 S = Schottky Diode  
 A = low VF  
 30 = Current Rating [A]  
 C = Common Cathode  
 100 = Reverse Voltage [V]  
 HB = TO-247AD (3)


| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|-----------------|--------------------|---------------|----------|----------|
| Standard | DSA30C100HB     | DSA30C100HB        | Tube          | 30       | 505053   |


| Similar Part | Package        | Voltage class |
|--------------|----------------|---------------|
| DSA30C100QB  | TO-3P (3)      | 100           |
| DSA30C100PB  | TO-220AB (3)   | 100           |
| DSA30C100PN  | TO-220ABFP (3) | 100           |

### Equivalent Circuits for Simulation

\* on die level

 $T_{VJ} = 175^{\circ}\text{C}$ 

|                                                                                     |                    |                 |    |
|-------------------------------------------------------------------------------------|--------------------|-----------------|----|
|  |                    | <b>Schottky</b> |    |
| $V_{0\max}$                                                                         | threshold voltage  | 0.46            | V  |
| $R_{0\max}$                                                                         | slope resistance * | 9.1             | mΩ |

**Outlines TO-247**


| Sym. | Inches |       | Millimeter |       |
|------|--------|-------|------------|-------|
|      | min.   | max.  | min.       | max.  |
| A    | 0.185  | 0.209 | 4.70       | 5.30  |
| A1   | 0.087  | 0.102 | 2.21       | 2.59  |
| A2   | 0.059  | 0.098 | 1.50       | 2.49  |
| D    | 0.819  | 0.845 | 20.79      | 21.45 |
| E    | 0.610  | 0.640 | 15.48      | 16.24 |
| E2   | 0.170  | 0.216 | 4.31       | 5.48  |
| e    | 0.215  | BSC   | 5.46       | BSC   |
| L    | 0.780  | 0.800 | 19.80      | 20.30 |
| L1   | -      | 0.177 | -          | 4.49  |
| Ø P  | 0.140  | 0.144 | 3.55       | 3.65  |
| Q    | 0.212  | 0.244 | 5.38       | 6.19  |
| S    | 0.242  | BSC   | 6.14       | BSC   |
| b    | 0.039  | 0.055 | 0.99       | 1.40  |
| b2   | 0.065  | 0.094 | 1.65       | 2.39  |
| b4   | 0.102  | 0.135 | 2.59       | 3.43  |
| c    | 0.015  | 0.035 | 0.38       | 0.89  |
| D1   | 0.515  | -     | 13.07      | -     |
| D2   | 0.020  | 0.053 | 0.51       | 1.35  |
| E1   | 0.530  | -     | 13.45      | -     |
| Ø P1 | -      | 0.29  | -          | 7.39  |

