# PNP Epitaxial Silicon Darlington Transistor

#### **Features**

- Monolithic Construction with Built-in Base-Emitter Shunt Resistors
- High DC Current Gain:  $h_{FE} = 1000$  at  $V_{CE} = -4$  V,  $I_{C} = -5$  A (Minimum)
- Industrial Use
- Complement to TIP142T

### **ORDERING INFORMATION**

Part Number	Top Mark	Package	Packing Method	
TIP147T	TIP147	TO-220 3L (Single Gauge)	Bulk	
TIP147TTU	TIP147	TO-220 3L (Single Gauge)	Rail	



## ON Semiconductor®


www.onsemi.com



1.Base 2.Collector 3.Emitter

TO-220 MOLDED CASE 340AT

### **EQUIVALENT CIRCUIT**



**Table 1. ABSOLUTE MAXIMUM RATINGS** 

Symbol	Parameter	Value	Unit
$V_{CBO}$	Collector-Base Voltage	-100	V
$V_{CEO}$	Collector–Emitter Voltage	-100	V
$V_{EBO}$	Emitter-Base Voltage	-5	V
I <sub>C</sub>	Collector Current (DC)	-10	Α
I <sub>CP</sub>	Collector Current (Pulse)	<b>–15</b>	Α
Ι <sub>Β</sub>	Base Current (DC)	-0.5	Α
$P_{C}$	Collector Dissipation (T <sub>C</sub> = 25°C)	80	W
$T_J$	Junction Temperature	150	°C
T <sub>STG</sub>	Storage Temperature Range	-65 to 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

**Table 2. ELECTRICAL CHARACTERISTICS** Values are at  $T_C = 25^{\circ}C$  unless otherwise noted.

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
V <sub>CEO(sus)</sub>	Collector–Emitter Sustaining Voltage	$I_C = -30 \text{ mA}, I_B = 0$	-100			V
I <sub>CEO</sub>	Collector Cut-Off Current	$V_{CE} = -50 \text{ V}, I_{B} = 0$			-2	mA
I <sub>CBO</sub>	Collector Cut-Off Current	$V_{CB} = -100 \text{ V}, I_{E} = 0$			-1	mA
I <sub>EBO</sub>	Emitter Cut-Off Current	$V_{EB} = -5 \text{ V}, I_{C} = 0$			-2	mA
h <sub>FE</sub>	DC Current Gain	$V_{CE} = -4 \text{ V}, I_{C} = -5 \text{ A}$	1000			
		$V_{CE} = -4 \text{ V}, I_{C} = -10 \text{ A}$	500			
V <sub>CE(sat)</sub>	Collector–Emitter Saturation Voltage	$I_C = -5 \text{ A}, I_B = -10 \text{ mA}$			-2	V
		$I_C = -10 \text{ A}, I_B = -40 \text{ mA}$			-3	
V <sub>BE(sat)</sub>	Base–Emitter Saturation Voltage	$I_C = -10 \text{ A}, I_B = -40 \text{ mA}$			-3.5	V
V <sub>BE(on)</sub>	Base-Emitter On Voltage	$V_{CE} = -4 \text{ V}, I_{C} = -10 \text{ A}$			-3	V
t <sub>D</sub>	Delay Time	$V_{CC} = -30 \text{ V, } I_{C} = -5 \text{ A,}$ $I_{B1} = -20 \text{ mA,}$ $I_{B2} = 20 \text{ mA,}$ $R_{L} = 6 \Omega$		0.15		μs
t <sub>R</sub>	Rise Time			0.55		μS
t <sub>STG</sub>	Storage Time			2.50		μs
t <sub>F</sub>	Fall Time			2.50		μs

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## **Typical Performance Characteristics**




Figure 1. Static Characteristic




Figure 2. DC Current Gain





Figure 3. Collector–Emitter Voltage and Base–Emitter Saturation Voltage



**Figure 4. Collector Output Capacitance** 




Figure 5. Safe Operating Area




Figure 6. Power Derating

#### **PACKAGE DIMENSIONS**

## TO-220-3LD CASE 340AT **ISSUE O** SUPPLIER "B" PACKAGE SHAPE Ø4.00 10.67 SUPPLIER "A" PACKAGE SHAPE 9.65 E 3.40 2.50 IF PRESENT, SEE NOTE "D" -Æ 16.51 15.42 9.40 8.13 3 [2.46] С 14.04 12.70 2.13 FRONT VIEWS ► "A1" SEE NOTE "F" 8.65 7.59 OPTIONAL 6.69 6.06 CHAMFER - $\odot$ NOTE "I" **BOTTOM VIEW** NOTES: A) REFERENCE JEDEC, TO-220, VARIATION AB B) ALL DIMENSIONS ARE IN MILLIMETERS. C) DIMENSIONS COMMON TO ALL PACKAGE C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ]. D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE) DOES NOT COMPLY JEDEC STANDARD VALUE. F) "A1" DIMENSIONS AS BELOW: SINGLE GAUGE = 0.51 - 0.61 DUAL GAUGE = 1.10 - 1.45 PRESENCE IS SUPPLIER DEPENDENT 3 2

**BACK VIEW** 

H) SUPPLIER DEPENDENT MOLD LOCKING HOLES

IN HEATSINK.

0.60 0.36

SIDE VIEW

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdf/Patent-Marking.pdf">www.onsemi.com/site/pdf/Patent-Marking.pdf</a>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor nakes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intend

#### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:

Europe, Middle East and Africa Technical Suppor Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81-3-5817-1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

♦ TIP147T/D

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdf/Patent-Marking.pdf">www.onsemi.com/site/pdf/Patent-Marking.pdf</a>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hol

### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81–3–5817–1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative