

ZTX690B


NPN SILICON PLANAR MEDIUM POWER
HIGH GAIN TRANSISTOR

ISSUE 1 – MAY 94

ZTX690B

FEATURES

- * 45 Volt V_{CEO}
 - * Gain of 400 at $I_C=1$ Amp
 - * Very low saturation voltage
- APPLICATIONS
- * Darlington replacement
 - * Siren Drivers
 - * Battery powered circuits
 - * Motor drivers



E-Line
TO92 Compatible

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$)


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Transition Frequency	f_T	150			MHz	$I_C=50\text{mA}$, $V_{CE}=5\text{V}$ $f=50\text{MHz}$
Input Capacitance	C_{ibo}		200		pF	$V_{EB}=0.5\text{V}$, $f=1\text{MHz}$
Output Capacitance	C_{obo}		16		pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$
Switching Times	t_{on}	33			ns	$I_C=500\text{mA}$, $I_{B1}=50\text{mA}$ $I_{B2}=50\text{mA}$, $V_{CE}=10\text{V}$
	t_{off}	1300			ns	

*Measured under pulsed conditions. Pulse width=300 μ s. Duty cycle $\leq 2\%$


THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	MAX.	UNIT
Thermal Resistance: Junction to Ambient, Junction to Ambient, Junction to Case	$R_{\theta(j-amb)1}$	175	$^{\circ}\text{C/W}$
	$R_{\theta(j-amb)2}^{\dagger}$	116	$^{\circ}\text{C/W}$
	$R_{\theta(j-case)}$	70	$^{\circ}\text{C/W}$

$\dagger$ Device mounted on P.C.B. with copper equal to 1 sq. Inch minimum.



Derating curve



Maximum transient thermal impedance

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	45	V
Collector-Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	6	A
Continuous Collector Current	I_C	2	A
Practical Power Dissipation*	P_{totp}	1.5	W
Power Dissipation at $T_{amb}=25^{\circ}\text{C}$ derate above 25°C	P_{tot}	1	W
	T_j, T_{sg}	5.7	$\text{mW}/^{\circ}\text{C}$
Operating and Storage Temperature Range		-55 to +200	$^{\circ}\text{C}$

* The power which can be dissipated assuming the device is mounted in a typical manner on a P.C.B. with copper equal to 1 inch square minimum

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	45			V	$I_C=100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	45			V	$I_C=10\text{mA}^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5			V	$I_E=100\mu\text{A}$
Collector Cut-Off Current	I_{CBO}			0.1	μA	$V_{CB}=35\text{V}$
Emitter Cut-Off Current	I_{EBO}			0.1	μA	$V_{EB}=4\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			0.1	V	$I_C=0.1\text{A}$, $I_B=0.5\text{mA}^*$
				0.5	V	$I_C=1\text{A}$, $I_B=5\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$			0.9	V	$I_C=1\text{A}$, $I_B=10\text{mA}^*$
Base-Emitter Turn-On Voltage	$V_{BE(on)}$			0.9	V	$I_C=1\text{A}$, $V_{CE}=2\text{V}^*$
Static Forward Current Transfer Ratio	h_{FE}	500				$I_C=100\text{mA}$, $V_{CE}=2\text{V}^*$
		400				$I_C=1\text{A}$, $V_{CE}=2\text{V}^*$
		150				$I_C=2\text{A}$, $V_{CE}=2\text{V}^*$

ZTX690B

TYPICAL CHARACTERISTICS

