

Quality | Careers | Investors | Sales Contacts | Contact Us Search by part # or keyword

Parametric Search | MyMicrosemi Login

Products | Applications | Design Support | Ordering | Company

| | Incations Design Support Ordering Company | | P | 01 | NE | er | M | atters. |
|--|---|------------------------------------|-----|-----|----------------|-----------|---|--|
| Products Product Directory Applications Directory Parametric Search | Home > 2N7237 (#45819) 2N7237 (#45819) Overview Diagrams | 2N7237 (#45819) | | | | | | Related Links Technical support Sales Contacts Available Stock |
| | Electrical Rating On-State Resistance (Static Drain to Source) | Symbol R _{DS(on)} | Min | Тур | Max 0.51 | Unit Ω | | Sales Contacts RFQ/Samples |
| | Maximum Electrical Rating Breakdown Voltage, Drain-Source (Gate Short-Circui | Symbol V _{BR(DSS)} | Min | Тур | Max 200.00 | Unit V | | |
| | Drain Current (dc) Drain Current (dc) | I _D | | | 11.00 7.00 | A A | | |
| | Power Dissipation (watts) Thermal Resistance, Junction to Case | P _D R _{euc} | | | 125.00 1.00 | °C/W | | |
| | This part can be found in the following product cate Discretes Transistors MOSFET P-Channel | gories: | | | | | | |
| | Applications Design Support Company Careers Investors yright © 2015 Microsemi Corporation. All rights reserved. The Microser | | 5 | | | | _ | |

