

High Temperature Capacitors

85°C

- \bullet High temperature tolerant (-25 to +85°C) and highly reliable.
- Ideal for backing up of controls, electronic rice cooking jars, home bakeries and the like.



Miniaturized


 DX DB

DH

Specifications

Item	Performance						
Category temperature range (°C)	-25 to +85						
Folerance at rated capacitance (%)	-20 to +80						
Internal resistance at 1 kHz	Rated capacitance (F)	0.047	0.1	0.22	0.47	0.68	1
	Internal resistance (Ω Max.)	300	200	120	50	50	30
Characteristics at high and low temperature	Percentage of capacitance change Internal resistance	Within ±30% of the value at 20°C Less than five times of the value at 20°C					
Endurance (85°C)	Test time	1000 hours					
	Percentage of capacitance change Internal resistance	Within ±30% of the initial measured value Less than four times of the initial specified value					
Shelf life (85°C)	Test time: 1000 hours; Same as endurance.						
Applicable standards	Conforms to JIS C5160-1 2009 (IEC 62391-1 2006)						

Outline Drawing



Part numbering system (example: 5.5V0.1F)

DH 5R5 104 Т Max.operating voltage Rated capacitance Series code symbol symbol

Part number is refer to following table.

Standard Ratings

Max. operating voltage (V)	Rated capacitance (F)	ELNA Parts No.	φD×L (mm)	
5.5	0.047	DH-5R5D473T	13.5×9.5	
5.5	0.1	DH-5R5D104T	13.5×9.5	
5.5	0.22	DH-5R5D224T	13.5×9.5	
5.5	0.47	DH-5R5D474T	21.5×9.5	
5.5	0.68	DH-5R5D684T	21.5×9.5	
5.5	1	DH-5R5D105T	21.5×9.5	